



45 *years* ANNIVERSARY



PEDROLLO S.p.A.

Via Enrico Fermi 7

37047 San Bonifacio (Verona) ITALIA

Paid-up capital € 100,000,000.00

Founded in 1974

tel. +39 045 6136311

fax +39 045 7612253

sales@pedrollo.com

www.pedrollo.com

Follow us on:



www.pedrollo4people.com



Facebook
PedrolloCorporate
Pedrollo4People



YouTube



Vimeo



LinkedIn

STANDARD VERSIONS

VOLTAGES

- Single-phase: **230 V – 50 Hz** with built-in thermal overload protector.
- Three-phase up to 4 kW and 4 poles three-phase: **230/400 V – 50 Hz**.
- Three-phase from 5.5 kW: **400/690 V – 50 Hz**.

PERFORMANCE AND ENERGY EFFICIENCY

- **Pumps fitted with the three-phase option are equipped with high efficiency motors**

Power P ₂	Class of efficiency (IEC 60034-30-1)
Up to 0.55 kW	IE2
From 0.60 to 75 kW	IE3

- **The electric water pumps which comply with EU rule N. 547/2012 have a minimum efficiency index of MEI≥0.40**

SPECIAL VERSIONS

- Pumps with other options: voltages or 60 Hz frequency.
- Pumps with special mechanical seals suitable for use with other liquids.
- Surface pumps with IP X5 grade protection.
- Submersible pumps without float switch.

SPECIAL WINDINGS ON REQUEST

- 110 V - 50 Hz (Single-phase)
- 240 V - 50 Hz (Single-phase)
- 110 V - 60 Hz (Single-phase)
- 220 V - 60 Hz (Single-phase)
- 110/220 V - 60 Hz (Single-phase)
- 240/415 V - 50 Hz (Three-phase)
- 220/380 V - 60 Hz (Three-phase)

CERTIFICATION AND TRADEMARKS



PK – PQ – PKS 6



Peripheral pumps

CKR – CK 7



Self-priming pumps

CP 8



Centrifugal pumps

CP-ST4 – ST6 9



Stainless steel centrifugal pumps

MK 10



Vertical centrifugal pumps

2-7CR 10



Multi-stage centrifugal pumps

2-4CP – 2CP 12



Multi-stage centrifugal pumps

JSW – SPRINKLER 13



Self-priming centrifugal pumps

JCR – PLURIJET 14



Self-priming centrifugal pumps

NGA – NGA-PRO 16



Centrifugal pumps with open impeller

DG PED 17



Pressurisation system with inverter

DHL 18



Circulators for heating systems

TISSEL-100 – 200 18



Pumps with inverter

HF 20



Centrifugal pumps

F 22



Monoblock centrifugal pumps

FG 26



Bare axle centrifugal pumps

FLUID SOLAR 28



Solar pumps

3SR 29



3" submersible pumps

DAVIS 29



4" peripheral submersible pump

4BLOCK 29



4" monoblock submersible pumps

4SR – 4HR 30



4" submersible pumps

6SR – 6HR 38



6" submersible pumps

4PD – 4PS – 6PD 42



4" and 6" submersible motors

UP – NK 44



Multi-stage submersible pumps

TOP MULTI 46



Multi-stage submersible pumps

TOP 48



Submersible pumps

TEX 49



Submersible pumps "VORTEX"

PLUG & DRAIN 50



Kit for preventing floods

RX	51
	
Stainless steel submersible pumps	
VX-ST – BC-ST	52
	
Submersible pumps	
VX-MF – BC-MF	54
	
Submersible pumps	
D	56
	
Submersible pumps	
ZX2	56
	
Submersible pumps	
ZX1	57
	
Submersible pumps	
VX – BC	57
	
Submersible pumps	
VXC – MC	58
	
Submersible pumps	

DC	59
	
Submersible pumps	
TRITUS	60
	
Submersible pumps with grinder	
VXC – MC	62
	
Submersible pumps	
VXC-F – MC-F	64
	
Submersible pumps	
VX40-50-65 – BC35	66
	
Submersible pumps	
VXC4 – MC4	68
	
Submersible pumps	
SAR	70
	
Accumulation and lifting stations	

PQ-EKO – PQ-PRO – PQ-Bs	74
	
Peripheral pumps for industrial use	
PQA	74
	
Peripheral pumps for industrial use	
PQ3000	75
	
Peripheral pumps for industrial use	
PV	75
	
Peripheral pumps for industrial use	
TOP MULTI-AD	75
	
Submersible pumps for AdBlue®	
HYDROFRESH	76
	
Automatic pressure boosting sets	
CB2	77
	
Automatic sets fitted for autoclaves	
EASYPUMP	78
	
Pumps with pressure regulator	
EASYPRESS	79
	
Pumps with pressure regulator	
ACCESSORIES	80

PK PUMPS WITH PERIPHERAL IMPELLER



MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
PKm 60	41PNK60A1	0.37	0.50	-	5 - 40	38 - 5	1"	1"	86.00
PKm 60 - MD	41PNK63A1	0.37	0.50		5 - 55	21 - 3			88.00
PKm 65	41PNK67A1	0.55	0.75		5 - 50	50 - 8			103.00
PKm 70	41PM71A1	0.60	0.85		5 - 50	62 - 18			162.00
PKm 80	41PM81A1	0.75	1		5 - 50	66 - 22	3/4"	3/4"	167.00
PKm 90	41PM901A1	0.75	1		5 - 40	82 - 5			205.00
PKm 100	41PM9117A1	1.1	1.5		5 - 70	80 - 15	1"	1"	290.00
PKm 200	41PM9217A1	1.5	2		5 - 80	86 - 10			314.00
PKm 300	41PM9317A1	2.2	3		5 - 90	95 - 10			340.00

Three-phase

PK 60	41PNK60A	0.37	0.50	IE2	5 - 40	38 - 5	1"	1"	101.00
PK 60 - MD	41PNK63A	0.37	0.50		5 - 55	21 - 3			103.00
PK 65	41PNK67A	0.55	0.75		5 - 50	50 - 8			118.00
PK 70	41PT71A	0.60	0.85		5 - 50	62 - 18			177.00
PK 80	41PT81A	0.75	1	IE3	5 - 50	66 - 22	3/4"	3/4"	182.00
PK 90	41PT901A	0.75	1		5 - 40	82 - 5			220.00
PK 100	41PT9117A	1.1	1.5		5 - 70	80 - 15	1"	1"	300.00
PK 200	41PT9217A	1.5	2		5 - 80	86 - 10			314.00
PK 300	41PT9317A	2.2	3		5 - 90	95 - 10			340.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: brass
- Motor bracket: Patent n. IT1243605
- Shaft: connection of the impeller, Patent n. 0000275945 (PK60, PK65)
- Pump body: Patent n. 0000275946 (PK60, PK65)
- Registered EU Design n. 004673192
- PKm 60® Registered trade mark n. 009875394

PQ PUMPS WITH PERIPHERAL IMPELLER



MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
PQm 60	41PNQ60A1	0.37	0.50	-	5 - 40	38 - 5	1"	1"	86.00
PQm 65	41PNQ67A1	0.55	0.75		5 - 50	50 - 8			103.00
PQm 70	41PQ70A1	0.60	0.85		5 - 50	62 - 18			162.00
PQm 80	41PQ80A1	0.75	1		5 - 50	66 - 22	3/4"	3/4"	167.00
PQm 90	41PQ90A1	0.75	1		5 - 40	82 - 5			205.00
PQm 100	41PQ917A1	1.1	1.5		5 - 70	80 - 15	1"	1"	290.00
PQm 200	41PQ927A1	1.5	2		5 - 80	86 - 10			314.00
PQm 300	41PQ937A1	2.2	3		5 - 90	95 - 10			340.00

Three-phase

PQ 60	41PNQ60A	0.37	0.50	IE2	5 - 40	38 - 5	1"	1"	101.00
PQ 65	41PNQ67A	0.55	0.75		5 - 50	50 - 8			118.00
PQ 70	41PQT70A	0.60	0.85		5 - 50	62 - 18			177.00
PQ 80	41PQT80A	0.75	1		5 - 50	66 - 22	3/4"	3/4"	182.00
PQ 90	41PQT90A	0.75	1	IE3	5 - 40	82 - 5			220.00
PQ 100	41PQT917A	1.1	1.5		5 - 70	80 - 15	1"	1"	300.00
PQ 200	41PQT927A	1.5	2		5 - 80	86 - 10			314.00
PQ 300	41PQT937A	2.2	3		5 - 90	95 - 10			340.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: brass
- Motor bracket: Patent n. IT1243605
- Shaft: connection of the impeller, Patent n. 0000275945 (PQ60, PQ65)
- Registered EU Design n. 002146548
- PQm 60® Registered trade mark n. 0001520591

SELF-PRIMING PERIPHERAL PUMPS

PKS SELF-PRIMING PUMPS WITH PERIPHERAL IMPELLER

MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
PKSm 60	41PNKS60A1	0.37	0.50	-	5 – 40	38 – 5	1"	1"	96.00
PKSm 65	41PNKS67A1	0.55	0.75		5 – 50	50 – 8			144.00
PKSm 70	41PMA71A1	0.60	0.85		5 – 50	62 – 18			180.00
PKSm 80	41PMA81A1	0.75	1		5 – 50	66 – 22			185.00
Three-phase									
PKS 60	41PNKS60A	0.37	0.50	IE2	5 – 40	38 – 5	1"	1"	112.00
PKS 65	41PNKS67A	0.55	0.75		5 – 50	50 – 8			159.00
PKS 70	41PTA71A	0.60	0.85	IE3	5 – 50	62 – 18			195.00
PKS 80	41PTA81A	0.75	1		5 – 50	66 – 22			200.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: brass
- Check valve: built in
- Motor bracket: Patent n. IT1243605
- Shaft: connection of the impeller, Patent n. 0000275945 (PKS60, PKS65)

SELF-PRIMING PUMPS

CKR SELF-PRIMING LIQUID RING PUMPS

Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
CKRm 80	46CKER80A1	0.55	0.75	-	5 – 50	46 – 10	1"	1"	247.00
CKRm 90	46CKER90A1	0.75	1		5 – 50	49 – 13			257.00
Three-phase									
CKR 80	46CKER80A	0.55	0.75	IE3	5 – 50	46 – 10	1"	1"	262.00
CKR 90	46CKER90A	0.75	1		5 – 50	49 – 13			272.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron, with stainless steel insert
- Impeller: brass
- Motor bracket: Patent n. IT1243605
- Registered EU Design n. 342159-0008

CKR = special version with double anti-seize inserts

CK SELF-PRIMING LIQUID RING PUMPS

MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
CKm 50	46CKM55A1	0.37	0.50	-	5 - 40	31 - 5	3/4"	3/4"	168.00
CKm 80	46CKE80A1	0.55	0.75		5 - 50	46 - 10	1"	1"	197.00
CKm 90	46CKE90A1	0.75	1		5 - 50	49 - 13			207.00
CKm 50 - BP (*)	46CKM56A1	0.25	0.33	-	5 - 40	20 - 5	3/4"	3/4"	186.00
Three-phase									
CK 50	46CKT55A	0.37	0.50	IE2	5 - 40	31 - 5	3/4"	3/4"	183.00
CK 80	46CKE80A	0.55	0.75	IE3	5 - 50	46 - 10	1"	1"	213.00
CK 90	46CKE90A	0.75	1		5 - 50	49 - 13			223.00
CK 50 - BP (*)	46CKT56A	0.25	0.33	IE2	5 - 40	20 - 5	3/4"	3/4"	201.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: brass
- Motor bracket: Patent n. IT1243605
- Registered EU Design n. 342159-0008 (CK 80-90)

(*) Water pump with bypass that limits maximum dynamic head to 20 metres

We recommend using the CKm 50-BP or the CK 50-BP pump in combination with the NZ dispensing nozzle and the MT1 flow meter (see ACCESSORIES on page 83)



CP CENTRIFUGAL PUMPS										
MODEL			POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	■	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
CPm 100	44CI00A1	1	0.25	0.33	-	10 – 60	15 – 7	1"	1"	122.00
CPm 130	44CI03A1		0.37	0.50		10 – 80	22 – 14			128.00
CPm 132	44CI04A1		0.55	0.75		20 – 120	22.5 – 12			144.00
CPm 150	44CI160A1		0.75	1		20 – 120	29 – 15			174.00
CPm 158	44CI16A1		0.75	1		10 – 90	34 – 25	1¼"	1"	174.00
CPm 170	44CI175A1		1.1	1.5		30 – 120	38 – 22			298.00
CPm 170M	44CI17MA1		1.1	1.5		30 – 160	35 – 19			304.00
CPm 190	44CI19A1		1.5	2		30 – 140	46 – 26			345.00
CPm 200	44CI20A1		2.2	3		30 – 150	55 – 36			365.00
CPm 160C	44CM26CA1	1	1.1	1.5	50 – 200	31 – 20	1½"	1"	308.00	
CPm 160B	44CM26BA1		1.5	2	50 – 220	36 – 23			330.00	
CPm 210C	44CM27CA1	2	2.2	3	50 – 250	45.5 – 27	2"	2"	622.00	
CPm 220C	44CM216C1A1		2.2	3	50 – 450	31.5 – 21			635.00	
Three-phase										
CP 100	44CIT00A	1	0.25	0.33	IE2	10 – 60	15 – 7	1"	1"	137.00
CP 130	44CIT03A		0.37	0.50	IE3	10 – 80	22 – 14			143.00
CP 132	44CIT04A		0.55	0.75		20 – 120	22.5 – 12			159.00
CP 150	44CIT160A		0.75	1		20 – 120	29 – 15			189.00
CP 158	44CIT16A		0.75	1		10 – 90	34 – 25	189.00		
CP 170	44CIT175A		1.1	1.5		30 – 120	38 – 22	1¼"	1"	308.00
CP 170M	44CIT17MA		1.1	1.5		30 – 160	35 – 19			319.00
CP 190	44CIT19A		1.5	2		30 – 140	46 – 26			345.00
CP 200	44CIT20A		2.2	3		30 – 150	55 – 36			365.00
CP 160C	44CT26CA	1	1.1	1.5	50 – 200	31 – 20	1½"			1"
CP 160B	44CT26BA		1.5	2	50 – 220	36 – 23		340.00		
CP 160A	44CT26AA		2.2	3	50 – 240	42 – 26		360.00		
CP 210C	44CT27CA	2	2.2	3	50 – 250	45.5 – 27		560.00		
CP 210B	44CT27BA		3	4	50 – 270	53 – 34		577.00		
CP 210A	44CT27AA		4	5.5	50 – 280	61 – 40		622.00		
CP 220C	44CT216C7A	2	2.2	3	50 – 450	31.5 – 21	2"	2"	532.00	
CP 220B	44CT216B1A		3	4	IE3	50 – 450			37.5 – 25	602.00
CP 220A	44CT216AA		4	5.5	50 – 450	48.5 – 36			697.00	
CP 220AH	44CT217HAE		5.5	7.5	50 – 450	51.5 – 42			766.00	
CP 230C	44CT217C1A	3	3	4	100 – 850	29.5 – 9			602.00	
CP 230B	44CT217BA		4	5.5	100 – 900	38.5 – 13			697.00	
CP 230A	44CT217AE		5.5	7.5	100 – 900	45.5 – 15			766.00	
CP 250B	44CP250BNE		7.5	10	100 – 800	57.4 – 31.3			978.00	
CP 250A	44CP250ANE		11	15	100 – 900	76 – 45.2			1,600.00	

■ Impeller: 1=AISI 304 stainless steel; 2=brass; 3=cast iron ▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Protection: IP X5 for CP 220, CP 230, CP 250
- Registered EU Design n. 002098434 (CP 100÷210, CP 250)
- Registered Italian Design n. 72753 (CP 220÷230)
- CPm 158® Registered trade mark n. 0001516350



CP-ST4 (AISI 304)

CP-ST4 STAINLESS STEEL AISI 304 CENTRIFUGAL PUMPS

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
CPm 100-ST4	44CP100IA1	0.25	0.33	-	10 – 90	15.5 – 6.5	1¼"	1"	192.00
CPm 130-ST4	44CP130IA1	0.37	0.50		10 – 100	21.5 – 9			202.00
CPm 132-ST4	44CP132IA1	0.55	0.75		20 – 120	23 – 12			213.00
CPm 150-ST4	44CP150IA1	0.75	1		20 – 150	31 – 14			240.00
CPm 158-ST4	44CP158IA1	0.75	1		10 – 120	35.5 – 19			240.00
CPm 170-ST4	44CP170IA1	1.1	1.5		10 – 140	40 – 20			329.00
CPm 170M-ST4	44CP170MIA1	1.1	1.5		20 – 160	35.5 – 19			332.00
CPm 180-ST4	44CP180IA1	1.1	1.5		40 – 230	30 – 13			340.00
CPm 190-ST4	44CP190IA1	1.5	2		40 – 250	35 – 15.5			355.00
CPm 200-ST4	44CP200IA1	2.2	3		40 – 270	43 – 18			380.00

Three-phase		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
CP 100-ST4	44CP100IA	0.25	0.33	IE2	10 – 90	15.5 – 6.5	1¼"	1"	207.00
CP 130-ST4	44CP130IA	0.37	0.50	IE3	10 – 100	21.5 – 9			217.00
CP 132-ST4	44CP132IA	0.55	0.75		20 – 120	23 – 12			228.00
CP 150-ST4	44CP150IA	0.75	1		20 – 150	31 – 14			250.00
CP 158-ST4	44CP158IA	0.75	1		10 – 120	35.5 – 19			250.00
CP 170-ST4	44CP170IA	1.1	1.5		10 – 140	40 – 20			339.00
CP 170M-ST4	44CP170MIA	1.1	1.5		20 – 160	35.5 – 19			342.00
CP 180-ST4	44CP180IA	1.1	1.5		40 – 230	30 – 13			350.00
CP 190-ST4	44CP190IA	1.5	2		40 – 250	35 – 15.5			355.00
CP 200-ST4	44CP200IA	2.2	3		40 – 270	43 – 18			380.00

- Pump body: **AISI 304 stainless steel**
- Impeller: **AISI 304 stainless steel**
- Shaft: **AISI 431 stainless steel**



CP-ST6 (AISI 316L)

CP-ST6 STAINLESS STEEL AISI 316L CENTRIFUGAL PUMPS

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
CPm 100-ST6	44CP100I16A1	0.25	0.33	-	10 – 90	15.5 – 6.5	1¼"	1"	224.00
CPm 130-ST6	44CP130I16A1	0.37	0.50		10 – 100	21.5 – 9			234.00
CPm 132-ST6	44CP132I16A1	0.55	0.75		20 – 120	23 – 12			245.00
CPm 150-ST6	44CP150I16A1	0.75	1		20 – 150	31 – 14			300.00
CPm 158-ST6	44CP158I16A1	0.75	1		10 – 120	35.5 – 19			300.00
CPm 170-ST6	44CP170I16A1	1.1	1.5		10 – 140	40 – 20			392.00
CPm 170M-ST6	44CP170MI16A1	1.1	1.5		20 – 160	35.5 – 19			397.00
CPm 180-ST6	44CP180I16A1	1.1	1.5		40 – 230	30 – 13			397.00
CPm 190-ST6	44CP190I16A1	1.5	2		40 – 250	35 – 15.5			413.00
CPm 200-ST6	44CP200I16A1	2.2	3		40 – 270	43 – 18			442.00

Three-phase		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
CP 100-ST6	44CP100I16A	0.25	0.33	IE2	10 – 90	15.5 – 6.5	1¼"	1"	239.00
CP 130-ST6	44CP130I16A	0.37	0.50	IE3	10 – 100	21.5 – 9			249.00
CP 132-ST6	44CP132I16A	0.55	0.75		20 – 120	23 – 12			260.00
CP 150-ST6	44CP150I16A	0.75	1		20 – 150	31 – 14			310.00
CP 158-ST6	44CP158I16A	0.75	1		10 – 120	35.5 – 19			310.00
CP 170-ST6	44CP170I16A	1.1	1.5		10 – 140	40 – 20			402.00
CP 170M-ST6	44CP170MI16A	1.1	1.5		20 – 160	35.5 – 19			407.00
CP 180-ST6	44CP180I16A	1.1	1.5		40 – 230	30 – 13			407.00
CP 190-ST6	44CP190I16A	1.5	2		40 – 250	35 – 15.5			413.00
CP 200-ST6	44CP200I16A	2.2	3		40 – 270	43 – 18			442.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 316L stainless steel**
- Impeller: **AISI 316L stainless steel**
- Shaft: **AISI 316L stainless steel**

MK VERTICAL CENTRIFUGAL PUMPS



MODEL		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
MKm 3/3	43PM3003A1	0.75	1	-	10 – 80	50 – 28	1 1/4"	1"	450.00
MKm 3/4	43PM3004A1	1.1	1.5		10 – 80	67 – 38			470.00
MKm 3/5	43PM3005A1	1.1	1.5		10 – 80	83 – 47			490.00
MKm 3/6	43PM3006A1	1.5	2		10 – 80	100 – 56			520.00
MKm 5/4	43PM5004A1	1.1	1.5		20 – 120	55 – 20			470.00
MKm 5/5	43PM5005A1	1.1	1.5		20 – 120	69 – 25			490.00
MKm 5/6	43PM5006A1	1.5	2		20 – 120	83 – 30			520.00
MKm 5/7	43PM5007A1	1.8	2.5		20 – 120	96 – 34			540.00
MKm 5/8	43PM5008A1	2.2	3		20 – 120	110 – 40			585.00
MKm 8/4	43PM8004A1	1.5	2		40 – 180	54 – 15			500.00
MKm 8/5	43PM8005A1	1.8	2.5		40 – 180	67.5 – 18			520.00
MKm 8/6	43PM8006A1	2.2	3		40 – 180	82 – 20			565.00

Three-phase		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
MK 3/3	43PM3003A	0.75	1	IE3	10 – 80	50 – 28	1 1/4"	1"	450.00
MK 3/4	43PM3004A	1.1	1.5		10 – 80	67 – 38			470.00
MK 3/5	43PM3005A	1.1	1.5		10 – 80	83 – 47			490.00
MK 3/6	43PM3006A	1.5	2		10 – 80	100 – 56			520.00
MK 5/4	43PM5004A	1.1	1.5		20 – 120	55 – 20			470.00
MK 5/5	43PM5005A	1.1	1.5		20 – 120	69 – 25			490.00
MK 5/6	43PM5006A	1.5	2		20 – 120	83 – 30			520.00
MK 5/7	43PM5007A	1.8	2.5		20 – 120	96 – 34			540.00
MK 5/8	43PM5008A	2.2	3		20 – 120	110 – 40			555.00
MK 8/4	43PM8004A	1.5	2		40 – 180	54 – 15			500.00
MK 8/5	43PM8005A	1.8	2.5		40 – 180	67.5 – 18			520.00
MK 8/6	43PM8006A	2.2	3		40 – 180	82 – 20			535.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron and AISI 304 stainless steel
- Impellers: Noryl
- Patent n. EP14755156.8



Inlet and outlet threaded flanges kit | Cod. ASSMKF030

54.00 €

- Kit consisting of:
 - two flanges in threaded cast iron ISO 228/1 (Suction 1 1/4" – Delivery 1"),
 - two seals
 - four screws for fixing to the ports of the MK pump

2-5CR MULTI-STAGE CENTRIFUGAL PUMPS



MODEL		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
2CRm 80	43CR08N2A1	0.37	0.50	-	5 – 70	26 – 5	1"	1"	168.00
3CRm 60	43CR06N3A1	0.37	0.50		5 – 70	30 – 7			173.00
3CRm 80	43CR08D3A1	0.45	0.60		5 – 80	38 – 5			173.00
4CRm 80	43CR08D4A1	0.55	0.75		5 – 80	50 – 10			189.00
5CRm 80	43CR0805A1	0.75	1		5 – 80	66 – 12			228.00
3CRm 100	43CR10D3A1	0.55	0.75		5 – 120	37 – 5			185.00
4CRm 100	43CR10D4A1	0.75	1		5 – 130	50 – 5			224.00
5CRm 100	43CR1005A1	1.1	1.5		5 – 130	62 – 8			250.00

Three-phase		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
2CR 80	43CR08N2A	0.37	0.50	IE2	5 – 70	26 – 5	1"	1"	183.00
3CR 60	43CR06N3A	0.37	0.50		5 – 70	30 – 7			189.00
3CR 80	43CR08D3A	0.45	0.60		5 – 80	38 – 5			188.00
4CR 80	43CR08D4A	0.55	0.75		5 – 80	50 – 10			204.00
5CR 80	43CR0805A	0.75	1	IE3	5 – 80	66 – 12			243.00
3CR 100	43CR10D3A	0.55	0.75	IE2	5 – 120	37 – 5			200.00
4CR 100	43CR10D4A	0.75	1	IE3	5 – 130	50 – 5			239.00
5CR 100	43CR1005A	1.1	1.5		5 – 130	62 – 8			260.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 304 stainless steel**
- Impellers: Noryl

3-7CR STAINLESS STEEL MULTI-STAGE CENTRIFUGAL PUMPS



Impellers in **AISI 304 stainless steel**

MODEL		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
5CRm 90	43CRI0905A1	1.1	1.5	-	5 – 90	78 – 38	1¼"	1"	553.00
6CRm 90	43CRI0906A1	1.5	2		5 – 90	94 – 45			596.00
7CRm 90	43CRI0907A1	1.8	2.5		5 – 90	110 – 53			650.00
3CRm 130	43CRI1303A1	1.1	1.5		5 – 130	49 – 24			490.00
4CRm 130	43CRI1304A1	1.5	2		5 – 130	65 – 31			532.00
5CRm 130	43CRI1305A1	1.8	2.5		5 – 130	81 – 39			585.00
3CRm 200	43CRI2003A1	1.1	1.5		20 – 200	43 – 13			490.00
4CRm 200	43CRI2004A1	1.5	2		20 – 200	57 – 17			532.00
5CRm 200	43CRI2005A1	1.8	2.5		20 – 200	71 – 22			585.00

Three-phase				▲					
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
5CR 90	43CRI0905A	1.1	1.5	IE3	5 – 90	78 – 38	1¼"	1"	563.00
6CR 90	43CRI0906A	1.5	2		5 – 90	94 – 45			596.00
7CR 90	43CRI0907A	1.8	2.5		5 – 90	110 – 53			650.00
3CR 130	43CRI1303A	1.1	1.5		5 – 130	49 – 24			500.00
4CR 130	43CRI1304A	1.5	2		5 – 130	65 – 31			532.00
5CR 130	43CRI1305A	1.8	2.5		5 – 130	81 – 39			585.00
6CR 130	43CRI1306A	2.2	3		5 – 130	97 – 46			620.00
3CR 200	43CRI2003A	1.1	1.5		20 – 200	43 – 13			500.00
4CR 200	43CRI2004A	1.5	2		20 – 200	57 – 17			532.00
5CR 200	43CRI2005A	1.8	2.5		20 – 200	71 – 22			585.00
6CR 200	43CRI2006A	2.2	3		20 – 200	85 – 26			620.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 304 stainless steel**
- Impellers and diffusers: **AISI 304 stainless steel**

VERSIONS WITH TECHNOPOLYMER IMPELLERS



Impellers in **Noryl**

Single-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
5CRm 90X	43CR0905A1	1.1	1.5	-	5 – 80	76 – 33	1¼"	1"	504.00
6CRm 90X	43CR0906A1	1.5	2		5 – 80	93 – 43			538.00
3CRm 130X	43CR1303A1	1.1	1.5		5 – 130	49 – 24			460.00
4CRm 130X	43CR1304A1	1.5	2		5 – 130	65 – 31			474.00
3CRm 200X	43CR2003A1	1.1	1.5		20 – 200	43 – 13			460.00
4CRm 200X	43CR2004A1	1.5	2		20 – 200	57 – 17			474.00

Three-phase				▲					
Single-phase	Code	kW	HP		Q l/min	H m	DN ₁	DN ₂	€
5CR 90X	43CR0905A	1.1	1.5	IE3	5 – 80	76 – 33	1¼"	1"	514.00
6CR 90X	43CR0906A	1.5	2		5 – 80	93 – 43			538.00
3CR 130X	43CR1303A	1.1	1.5		5 – 130	49 – 24			470.00
4CR 130X	43CR1304A	1.5	2		5 – 130	65 – 31			474.00
5CR 130X	43CR1305A	1.8	2.5		5 – 130	81 – 39			520.00
6CR 130X	43CR1306A	2.2	3		5 – 130	97 – 46			559.00
3CR 200X	43CR2003A	1.1	1.5		20 – 200	43 – 13			470.00
4CR 200X	43CR2004A	1.5	2		20 – 200	57 – 17			474.00
5CR 200X	43CR2005A	1.8	2.5		20 – 200	71 – 22			520.00
6CR 200X	43CR2006A	2.2	3		20 – 200	85 – 26			559.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 304 stainless steel**
- Impellers: Noryl
- Patent n. EP14755156.8



2-4CP MULTI-STAGE CENTRIFUGAL PUMPS

MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
2CPm 80	43CPN277AA1	0.37	0.50	-	5 – 70	26 – 5	1"	1"	150.00
3CPm 60	43CPN278A1	0.37	0.50		5 – 70	30 – 7			162.00
3CPm 80	43CPN382A1	0.45	0.60		5 – 80	38 – 5			162.00
4CPm 80	43CPN283A1	0.55	0.75		5 – 80	50 – 10			180.00
3CPm 100	43CPN384A1	0.55	0.75		5 – 120	37 – 5			177.00
4CPm 100	43CPN286A1	0.75	1		5 – 130	50 – 5			211.00

Three-phase

2CP 80	43CPN277AA	0.37	0.50	IE2	5 – 70	26 – 5	1"	1"	165.00
3CP 60	43CPN278A	0.37	0.50		5 – 70	30 – 7			177.00
3CP 80	43CPN382A	0.45	0.60		5 – 80	38 – 5			177.00
4CP 80	43CPN283A	0.55	0.75		5 – 80	50 – 10			195.00
3CP 100	43CPN384A	0.55	0.75		5 – 120	37 – 5			192.00
4CP 100	43CPN286A	0.75	1	IE3	5 – 130	50 – 5			226.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impellers: Noryl
- Registered EU Design n. 002073635-0001

2CP CENTRIFUGAL TWIN-IMPELLER PUMPS

MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	■ kW	HP	▲	l/min	m	DN ₁	DN ₂	€
2CPm 25/130	452CM130A1	1	0.75	1	20 – 100	39 – 15	1¼"	1"	239.00
2CPm 25/14B	452CM2616BA1	1.1	1.5	-	20 – 100	52 – 22			365.00
2CPm 25/14A	452CM2616AA1	1.5	2		20 – 100	65 – 32			410.00
2CPm 25/16C	452CM2614CA1	2	1.1		20 – 120	46 – 24			365.00
2CPm 25/16B	452CM2614BA1	1.5	2		20 – 140	56 – 30			410.00
2CPm 25/16A	452CM2614AA1	2.2	3		20 – 160	67 – 32			490.00

Three-phase

2CP 25/130	452CT130A	1	0.75	1	20 – 100	39 – 15	1¼"	1"	254.00
2CP 25/14B	452CT2616BA		1.1	1.5	20 – 100	52 – 22			375.00
2CP 25/14A	452CT2616AA		1.5	2	20 – 100	65 – 32			410.00
2CP 25/16C	452CT2614CA		1.1	1.5	20 – 120	46 – 24			375.00
2CP 25/16B	452CT2614BA		1.5	2	20 – 140	56 – 30			410.00
2CP 25/16A	452CT2614AA		2.2	3	20 – 160	67 – 32			430.00
2CP 32/200C	452CT303CA		3	4	40 – 250	66.5 – 36	1½"	1¼"	775.00
2CP 32/200B	452CT313BA	2	4	5.5	40 – 250	81 – 49			790.00
2CP 32/210B	452CT343BE		5.5	7.5	40 – 250	94 – 56			915.00
2CP 32/210A	452CT353AE		7.5	10	40 – 250	111 – 74	2"	1½"	962.00
2CP 40/180C	452CT383CA		4	5.5	100 – 350	62 – 35			880.00
2CP 40/180B	452CT393BE		5.5	7.5	100 – 400	73 – 42			905.00
2CP 40/180A	452CT403AE		7.5	10	100 – 400	85 – 60			955.00
2CP 40/200B	452CT420BE		9.2	12.5	100 – 450	94 – 61			1,630.00
2CP 40/200A	452CT420AE		11	15	100 – 450	102 – 69			1,650.00

■ Impellers: 1=AISI 304 stainless steel; 2=brass

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron

SELF-PRIMING CENTRIFUGAL PUMPS

JSW SELF-PRIMING "JET" PUMPS



Impeller in AISI 304 stainless steel

MODEL		POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP		Q l/min	H m	DN1	DN2	€
JSWm 1C	46JSN1CA1	0.37	0.50	-	5 - 60	32 - 10	1"	1"	148.00
JSWm 1B	46JSN1BA1	0.48	0.65		5 - 60	34 - 12			150.00
JSWm 1A	46JSN1AA1	0.55	0.75		5 - 60	43 - 17			159.00
JSWm 2C	46JSN7A10A1	0.75	1	-	5 - 70	47 - 20	1"	1"	177.00
JSWm 2B	46JSN7A12A1	0.90	1.25		5 - 70	51 - 24			190.00
JSWm 2A	46JSN7A15A1	1.1	1.5		5 - 70	55 - 28			200.00
JSWm 2CL	46JSN7AL10A1	0.75	1	-	5 - 85	36 - 12	1"	1"	180.00
JSWm 2CM	46JSN7AM10A1	0.75	1		5 - 80	42 - 18			180.00
JSWm 2AH	46JSN7AH15A1	1.1	1.5		5 - 45	65 - 32			206.00
JSWm 3CH	46JS8AH05A1	1.1	1.5	-	10 - 80	55 - 30	1 1/4"	1"	352.00
JSWm 3BH	46JS8AH10A1	1.5	2		10 - 80	68 - 38			370.00
JSWm 3AH	46JS8AH15A1	2.2	3		10 - 80	88 - 52			415.00
JSWm 3CM	46JS8AM05A1	1.1	1.5	-	20 - 120	46 - 20	1 1/4"	1"	352.00
JSWm 3BM	46JS8AM10A1	1.5	2		20 - 120	56 - 30			370.00
JSWm 3AM	46JS8AM15A1	2.2	3		20 - 120	70 - 40			415.00
JSWm 3CL	46JS8AL05A1	1.1	1.5	-	30 - 160	39 - 14	1 1/4"	1"	352.00
JSWm 3BL	46JS8AL10A1	1.5	2		30 - 160	46 - 24			370.00
JSWm 3AL	46JS8AL15A1	2.2	3		30 - 160	58 - 36			415.00

Three-phase				▲					
Single-phase	Code	kW	HP		Q l/min	H m	DN1	DN2	€
JSW 1C	46JSN1CA	0.37	0.50	IE2	5 - 60	32 - 10	1"	1"	163.00
JSW 1B	46JSN1BA	0.48	0.65	IE2	5 - 60	34 - 12			165.00
JSW 1A	46JSN1AA	0.55	0.75	IE3	5 - 60	43 - 17			174.00
JSW 2C	46JSN7A10A	0.75	1	IE3	5 - 70	47 - 20	1"	1"	192.00
JSW 2B	46JSN7A12A	0.90	1.25		5 - 70	51 - 24			205.00
JSW 2A	46JSN7A15A	1.1	1.5		5 - 70	55 - 28			210.00
JSW 2CL	46JSN7AL10A	0.75	1	IE3	5 - 85	36 - 12	1"	1"	195.00
JSW 2CM	46JSN7AM10A	0.75	1		5 - 80	42 - 18			195.00
JSW 2AH	46JSN7AH15A	1.1	1.5		5 - 45	65 - 32			216.00
JSW 3CH	46JS8AH05A	1.1	1.5	IE3	10 - 80	55 - 30	1 1/4"	1"	362.00
JSW 3BH	46JS8AH10A	1.5	2		10 - 80	68 - 38			370.00
JSW 3AH	46JS8AH15A	2.2	3		10 - 80	88 - 52			388.00
JSW 3CM	46JS8AM05A	1.1	1.5	IE3	20 - 120	46 - 20	1 1/4"	1"	362.00
JSW 3BM	46JS8AM10A	1.5	2		20 - 120	56 - 30			370.00
JSW 3AM	46JS8AM15A	2.2	3		20 - 120	70 - 40			388.00
JSW 3CL	46JS8AL05A	1.1	1.5	IE3	30 - 160	39 - 14	1 1/4"	1"	362.00
JSW 3BL	46JS8AL10A	1.5	2		30 - 160	46 - 24			370.00
JSW 3AL	46JS8AL15A	2.2	3		30 - 160	58 - 36			388.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: AISI 304 stainless steel

VERSIONS WITH TECHNOPOLYMER IMPELLER

Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
JSWm 1CX	46JSNP1CA1	0.37	0.50	-	5 - 60	32 - 10	1"	1"	140.00
JSWm 1BX	46JSNP1BA1	0.48	0.65		5 - 60	34 - 12			142.00
JSWm 1AX	46JSNP1AA1	0.55	0.75		5 - 60	43 - 17			150.00
JSWm 2CX	46JSNP7A10A1	0.75	1	-	5 - 70	47 - 20	1"	1"	167.00
JSWm 2BX	46JSNP7A12A1	0.90	1.25		5 - 70	51 - 24			179.00
JSWm 2AX	46JSNP7A15A1	1.1	1.5		5 - 70	55 - 28			189.00

Three-phase				▲					
Single-phase	Code	kW	HP		Q l/min	H m	DN1	DN2	€
JSW 1CX	46JSNP1CA	0.37	0.50	IE2	5 - 60	32 - 10	1"	1"	155.00
JSW 1BX	46JSNP1BA	0.48	0.65	IE2	5 - 60	34 - 12			157.00
JSW 1AX	46JSNP1AA	0.55	0.75	IE3	5 - 60	43 - 17			165.00
JSW 2CX	46JSNP7A10A	0.75	1	IE3	5 - 70	47 - 20	1"	1"	182.00
JSW 2BX	46JSNP7A12A	0.90	1.25		5 - 70	51 - 24			189.00
JSW 2AX	46JSNP7A15A	1.1	1.5		5 - 70	55 - 28			199.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: Noryl
- Registered EU Design n. 002218610
- European Patent n. 1 510 696 (JSW 1, JSW 2)
- JSW Registered trade mark n. 013073135

SPRINKLER SELF-PRIMING CENTRIFUGAL PUMPS



MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
SKRm 1.5	46SKRA15A1	1.5	2	–	50 – 300	25 – 15	1½"	1½"	372.00

Three-phase		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
SKR 1.5	46SKRA15A	1.5	2	IE3	50 – 300	25 – 15	1½"	1½"	372.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: Noryl

JCR SELF-PRIMING "JET" PUMPS



MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
JCRm 1C	46JCN1C0A1	0.37	0.50	–	5 – 60	32 – 10	1"	1"	163.00
JCRm 1B	46JCN1B0A1	0.48	0.65	–	5 – 60	34 – 12			165.00
JCRm 1A	46JCN1A0A1	0.55	0.75	–	5 – 60	43 – 17			172.00
JCRm 2C	46JCR2A10A1	0.75	1	–	5 – 70	47 – 19			196.00
JCRm 2B	46JCR2A12A1	0.90	1.25	–	5 – 70	52 – 23			208.00
JCRm 2A	46JCR2A15A1	1.1	1.5	–	5 – 70	56 – 27			218.00
JCRm 2CL	46JCR2A16A1	0.75	1	–	5 – 85	36 – 12			199.00

Three-phase		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
JCR 1C	46JCN1C0A	0.37	0.50	IE2	5 – 60	32 – 10	1"	1"	178.00
JCR 1B	46JCN1B0A	0.48	0.65	IE2	5 – 60	34 – 12			180.00
JCR 1A	46JCN1A0A	0.55	0.75	IE3	5 – 60	43 – 17			187.00
JCR 2C	46JCR2A10A	0.75	1	IE3	5 – 70	47 – 19			211.00
JCR 2B	46JCR2A12A	0.90	1.25	IE3	5 – 70	52 – 23			223.00
JCR 2A	46JCR2A15A	1.1	1.5	IE3	5 – 70	56 – 27			228.00
JCR 2CL	46JCR2A16A	0.75	1	IE3	5 – 85	36 – 12			214.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 304 stainless steel**
- Impeller: **AISI 304 stainless steel**
- European Patent n. 1 510 696

PLURIJET SELF-PRIMING MULTI-STAGE PUMPS



MODEL		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
PLURIJETm 3/60X	43PJA6053A1	0.37	0.50	–	5 – 70	30 – 7	1"	1"	179.00
PLURIJETm 3/80X	43PJA6063A1	0.48	0.65	–	5 – 80	38 – 5			184.00
PLURIJETm 4/80X	43PJA6084A1	0.55	0.75	–	5 – 80	50 – 10			195.00
PLURIJETm 3/100X	43PJA6083A1	0.55	0.75	–	5 – 120	37 – 5			195.00
PLURIJETm 4/100X	43PJA5104A1	0.75	1	–	5 – 130	50 – 5			236.00

Three-phase		POWER P ₂			PERFORMANCE Q H		PORTS		PRICE
PLURIJET 3/60X	43PJA6053A	0.37	0.50	IE2	5 – 70	30 – 7	1"	1"	194.00
PLURIJET 3/80X	43PJA6063A	0.48	0.65	IE2	5 – 80	38 – 5			199.00
PLURIJET 4/80X	43PJA6084A	0.55	0.75	IE2	5 – 80	50 – 10			210.00
PLURIJET 3/100X	43PJA6083A	0.55	0.75	IE2	5 – 120	37 – 5			210.00
PLURIJET 4/100X	43PJA5104A	0.75	1	IE3	5 – 130	50 – 5			251.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: **AISI 304 stainless steel**
- Impellers: Noryl
- PLURIJET® Registered trade mark n. 003974301

PLURIJET STAINLESS STEEL SELF-PRIMING MULTI-STAGE PUMPS

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
PLURIJETm 5/90	43PJB125058A1	1.1	1.5	-	5 – 90	78 – 38	1 1/4"	1"	560.00
PLURIJETm 6/90	43PJB130068A1	1.5	2		5 – 90	94 – 45			602.00
PLURIJETm 3/130	43PJC115038A1	1.1	1.5		5 – 130	49 – 24			495.00
PLURIJETm 4/130	43PJC120048A1	1.5	2		5 – 130	65 – 31			540.00
PLURIJETm 5/130	43PJC125058A1	1.8	2.5		5 – 130	81 – 39			592.00
PLURIJETm 3/200	43PJD115038A1	1.1	1.5		20 – 200	43 – 13			495.00
PLURIJETm 4/200	43PJD120048A1	1.5	2		20 – 200	57 – 17			540.00
PLURIJETm 5/200	43PJD125058A1	1.8	2.5		20 – 200	71 – 22			592.00

Three-phase									
PLURIJET 5/90	43PJB125058A	1.1	1.5	IE3	5 – 90	78 – 38	1 1/4"	1"	570.00
PLURIJET 6/90	43PJB130068A	1.5	2		5 – 90	94 – 45			602.00
PLURIJET 3/130	43PJC115038A	1.1	1.5		5 – 130	49 – 24			505.00
PLURIJET 4/130	43PJC120048A	1.5	2		5 – 130	65 – 31			540.00
PLURIJET 5/130	43PJC125058A	1.8	2.5		5 – 130	81 – 39			592.00
PLURIJET 6/130	43PJC130068A	2.2	3		5 – 130	97 – 46			625.00
PLURIJET 3/200	43PJD115038A	1.1	1.5		20 – 200	43 – 13			505.00
PLURIJET 4/200	43PJD120048A	1.5	2		20 – 200	57 – 17			540.00
PLURIJET 5/200	43PJD125058A	1.8	2.5		20 – 200	71 – 22			592.00
PLURIJET 6/200	43PJD130068A	2.2	3		20 – 200	85 – 26			625.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body and diffusers: **AISI 304 stainless steel**
- Impellers: **AISI 304 stainless steel**
- PLURIJET® Registered trade mark n. 003974301
- Patent n. EP14755156.8

VERSIONS WITH TECHNOPOLYMER IMPELLER

Single-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
PLURIJETm 5/90X	43PJB25058A1	1.1	1.5	-	5 – 80	76 – 33	1 1/4"	1"	505.00
PLURIJETm 6/90X	43PJB30068A1	1.5	2		5 – 80	93 – 43			540.00
PLURIJETm 3/130X	43PJC15038A1	1.1	1.5		5 – 130	49 – 24			462.00
PLURIJETm 4/130X	43PJC20048A1	1.5	2		5 – 130	65 – 31			478.00
PLURIJETm 5/130X	43PJC25058A1	1.8	2.5		5 – 130	81 – 39			524.00
PLURIJETm 3/200X	43PJD15038A1	1.1	1.5		20 – 200	43 – 13			462.00
PLURIJETm 4/200X	43PJD20048A1	1.5	2		20 – 200	57 – 17			478.00
PLURIJETm 5/200X	43PJD25058A1	1.8	2.5		20 – 200	71 – 22			524.00

Three-phase									
PLURIJET 5/90X	43PJB25058A	1.1	1.5	IE3	5 – 80	76 – 33	1 1/4"	1"	515.00
PLURIJET 6/90X	43PJB30068A	1.5	2		5 – 80	93 – 43			540.00
PLURIJET 3/130X	43PJC15038A	1.1	1.5		5 – 130	49 – 24			472.00
PLURIJET 4/130X	43PJC20048A	1.5	2		5 – 130	65 – 31			478.00
PLURIJET 5/130X	43PJC25058A	1.8	2.5		5 – 130	81 – 39			524.00
PLURIJET 6/130X	43PJC30068A	2.2	3		5 – 130	97 – 46			560.00
PLURIJET 3/200X	43PJD15038A	1.1	1.5		20 – 200	43 – 13			472.00
PLURIJET 4/200X	43PJD20048A	1.5	2		20 – 200	57 – 17			478.00
PLURIJET 5/200X	43PJD25058A	1.8	2.5		20 – 200	71 – 22			524.00
PLURIJET 6/200X	43PJD30068A	2.2	3		20 – 200	85 – 26			560.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body and diffusers: **AISI 304 stainless steel**
- Impellers: **Noryl**
- PLURIJET® Registered trade mark n. 003974301
- Patent n. EP14755156.8



Impellers in **AISI 304 stainless steel**



Impellers in **Noryl**



NGA PUMPS WITH OPEN IMPELLER

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
NGAm 1B	44GEX51BA1	0.55	0.75	—	50 – 300	17 – 8	1½"	1½"	208.00
NGAm 1A	44GEX51AA1	0.75	1		50 – 350	19.5 – 6			218.00
Three-phase									
NGA 1B	44GEX51BA	0.55	0.75	IE3	50 – 300	17 – 8	1½"	1½"	223.00
NGA 1A	44GEX51AA	0.75	1		50 – 350	19.5 – 6			233.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Impeller: AISI 316 stainless steel
- Registered EU Design n. 002098434

**Suitable for the removal of liquids comparatively full of impurities.
Passage of suspended solids up to Ø 10 mm.**



NGA-PRO STAINLESS STEEL PUMPS WITH OPEN IMPELLER

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
NGAm 1B - PRO	44GEX32BA1	0.55	0.75	-	50 – 300	17 – 8	1½"	1½"	475.00
NGAm 1A - PRO	44GEX32AA1	0.75	1		50 – 350	19.5 – 6			485.00
Three-phase									
NGA 1B - PRO	44GEX32BA	0.55	0.75	IE3	50 – 300	17 – 8	1½"	1½"	490.00
NGA 1A - PRO	44GEX32AA	0.75	1		50 – 350	19.5 – 6			500.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body and impeller: precision cast AISI 316 stainless steel
- Shaft: AISI 316L stainless steel
- Registered EU Design n. 002098434

**Suitable for the removal of aggressive liquids comparatively full of impurities.
Passage of suspended solids up to Ø 10 mm.**



AUTOMATIC PRESSURISATION SYSTEM WITH INVERTER

MODEL	Code	POWER		▲	PERFORMANCE		PORTS		PRICE
		P ₂ kW	HP		Q l/min	H m	DN ₁	DN ₂	€
Single-phase									
DG PED 3	KDGP03A1	0.75	1	IE3	5 – 80	55 – 10	1"	1"	640.00
DG PED 5	KDGP05A1	1.1	1.5		5 – 120	55 – 10			800.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- **DG PED** is an automatic pressurisation system with an inverter which integrates a built-in high efficiency self-priming pump, a large accumulator tank, flow and rate sensors and a non-return valve: a compact autonomous quiet and high performance pumping system.
- The sophisticated electronically controlled inverter, at the heart of the system, in an intuitive way:
 - maintains the pressure of the installation constant by regulating the velocity of the pump in accordance with the water required;
 - controls the hydraulic and electric operating parameters and protects the pump from abnormalities;
 - can be equipped with an expansion card that makes it possible to work in parallel with other inverters in the pumping groups and to manage input and output signals;
 - it adapts to every type of pressurisation system, including existing ones;
 - it limits the starting and operating currents in order to provide a greater saving of energy.

OPTIONAL ACCESSORIES



Connection kit for two
DG PED units
Code ASSKITDGP01
€ 340.00



Kit for wall-mounting a
single DG PED
Code ASSKITDGP02
€ 60.00



Kit for wall-mounting a
group of two units
Code ASSKITDGP03
€ 80.00



Electronic expansion
circuit board
Code ASSKITDGP04
€ 75.00



ALL IN ONE

Main components:

- Multistage self-priming pump
- Expansion tank
- Non-return valve
- Intuitive control panel



LOW-NOISE



CONSTANT PRESSURE




EASY TO USE



INSTALLABLE ANYWHERE

Thanks to its compactness and low noise level the DG PED can be installed anywhere.



COMPACT DIMENSIONS



DOMESTIC USE

A single DG PED meets the requirements of single apartments or small houses.



RESIDENTIAL USE

Two DG PED assembled as a set meet the requirements of more than one apartment.





DHL ELECTRONIC CIRCULATORS FOR HEATING SYSTEMS

MODEL		Input power (P ₁)	Volt	Hz	Absorbed current (I ₁)	Ports	Spacing mm	PRICE €
Single-phase	Code							
DHL 25-60/130	4CDHLT2560130	Min 3 W Max 42 W	230	50	Min 0.03 A Max 0.33 A	G 1½" G 1½"	130	144.00
DHL 25-60/180	4CDHLT2560180						180	144.00

- Improved Class A low energy consumption electronic circulators
- Recommended for domestic and residential heating systems
- Management of the preferred working range by means of three operation programmes



TISSEL-100 MULTI-STAGE CENTRIFUGAL PUMPS

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
TS1-4CP 100	KTS1A4CP100A1	0.75	1	IE3	5 – 130	44 – 5	1"	1"	810.00
TS1-4CR 100	KTS1A4CR100A1	0.75	1		5 – 130	44 – 5			829.00
TS1-5CR 100	KTS1A5CR100A1	1.1	1.5		5 – 130	56 – 8			845.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Multi-stage centrifugal pumps with a variable speed inverter
- Single-phase power supply 230 V - 50 Hz
- Three-phase motor 230 V - 50 Hz



TISSEL-100 CENTRIFUGAL TWIN-IMPELLER PUMPS

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
TS1-2CP 25/130	KTS1A2CP130A1	0.75	1	IE3	5 – 100	36 – 15	1¼"	1"	840.00
TS1-2CP 25/14B	KTS1A2CP14BA1	1.1	1.5		5 – 100	48 – 22			955.00
TS1-2CP 25/14A	KTS1A2CP14AA1	1.5	2		5 – 100	61 – 32			1,080.00
TS1-2CP 25/16C	KTS1A2CP16CA1	1.1	1.5		5 – 120	41 – 24			955.00
TS1-2CP 25/16B	KTS1A2CP16BA1	1.5	2		5 – 140	52 – 30			1,080.00
TS1-2CP 25/16A	KTS1A2CP16AA1	2.2	3		5 – 160	62 – 32			1,100.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Centrifugal twin-impeller pumps with a variable speed inverter
- Single-phase power supply 230 V - 50 Hz
- Three-phase motor 230 V - 50 Hz

The group consists of:

- Pump
- **TISSEL 100** frequency converter programmed for a constant pressure with an incorporated pressure transducer
- Cables to connect the INVERTER to the pump

TISSSEL-200 VERTICAL CENTRIFUGAL PUMPS



MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
TS2-MK 3/3	KTS2AMK0303A1	0.75	1	IE3	5 – 80	46 – 28	1 1/4"	1"	1,080.00
TS2-MK 3/4	KTS2AMK0304A1	1.1	1.5		5 – 80	62 – 38			1,100.00
TS2-MK 3/5	KTS2AMK0305A1	1.1	1.5		5 – 80	80 – 47			1,120.00
TS2-MK 3/6	KTS2AMK0306A1	1.5	2		5 – 80	96 – 56			1,255.00
TS2-MK 5/4	KTS2AMK0504A1	1.1	1.5		5 – 120	50 – 20			1,100.00
TS2-MK 5/5	KTS2AMK0505A1	1.1	1.5		5 – 120	63 – 25			1,120.00
TS2-MK 5/6	KTS2AMK0506A1	1.5	2		5 – 120	78 – 30			1,255.00
TS2-MK 5/7	KTS2AMK0507A1	1.8	2.5		5 – 120	92 – 34			1,275.00
TS2-MK 5/8	KTS2AMK0508A1	2.2	3		5 – 120	102 – 40			1,285.00
TS2-MK 8/4	KTS2AMK0804A1	1.5	2		5 – 180	50 – 15			1,235.00
TS2-MK 8/5	KTS2AMK0805A1	1.8	2.5		5 – 180	64 – 18			1,255.00
TS2-MK 8/6	KTS2AMK0806A1	2.2	3		5 – 180	80 – 20			1,265.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Variable speed vertical multi-stage centrifugal pumps fitted with an inverter
- Single-phase power supply 230 V - 50 Hz
- Three-phase motor 230 V - 50 Hz

TISSSEL-200 MULTI-STAGE CENTRIFUGAL PUMPS



MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
TS2-5CR 90	KTS2A5CR090A1	1.1	1.5	IE3	5 – 90	78 – 38	1 1/4"	1"	1,185.00
TS2-6CR 90	KTS2A6CR090A1	1.5	2		5 – 90	94 – 45			1,335.00
TS2-7CR 90	KTS2A7CR090A1	1.8	2.5		5 – 90	110 – 53			1,390.00
TS2-3CR 130	KTS2A3CR130A1	1.1	1.5		5 – 130	49 – 24			1,120.00
TS2-4CR 130	KTS2A4CR130A1	1.5	2		5 – 130	65 – 31			1,275.00
TS2-5CR 130	KTS2A5CR130A1	1.8	2.5		5 – 130	81 – 39			1,325.00
TS2-6CR 130	KTS2A6CR130A1	2.2	3		5 – 130	97 – 45			1,360.00
TS2-3CR 200	KTS2A3CR200A1	1.1	1.5		5 – 200	43 – 13			1,120.00
TS2-4CR 200	KTS2A4CR200A1	1.5	2		5 – 200	57 – 17			1,275.00
TS2-5CR 200	KTS2A5CR200A1	1.8	2.5		5 – 200	72 – 22			1,325.00
TS2-6CR 200	KTS2A6CR200A1	2.2	3		5 – 200	86 – 26			1,360.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Variable speed multi-stage centrifugal pumps fitted with an inverter
- Single-phase power supply 230 V - 50 Hz
- Three-phase motor 230 V - 50 Hz
- Impellers and diffusers: **AISI 304 stainless steel**

TISSSEL-200 SELF-PRIMING MULTI-STAGE PUMPS



MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN1	DN2	€
TS2-PLURIJET 5/90	KTS2APJ5090A1	1.1	1.5	IE3	5 – 90	78 – 38	1 1/4"	1"	1,190.00
TS2-PLURIJET 6/90	KTS2APJ6090A1	1.5	2		5 – 90	94 – 45			1,340.00
TS2-PLURIJET 3/130	KTS2APJ3130A1	1.1	1.5		5 – 130	49 – 24			1,125.00
TS2-PLURIJET 4/130	KTS2APJ4130A1	1.5	2		5 – 130	65 – 31			1,280.00
TS2-PLURIJET 5/130	KTS2APJ5130A1	1.8	2.5		5 – 130	81 – 39			1,330.00
TS2-PLURIJET 6/130	KTS2APJ6130A1	2.2	3		5 – 130	97 – 45			1,365.00
TS2-PLURIJET 3/200	KTS2APJ3200A1	1.1	1.5		5 – 200	43 – 13			1,125.00
TS2-PLURIJET 4/200	KTS2APJ4200A1	1.5	2		5 – 200	57 – 17			1,280.00
TS2-PLURIJET 5/200	KTS2APJ5200A1	1.8	2.5		5 – 200	72 – 22			1,330.00
TS2-PLURIJET 6/200	KTS2APJ6200A1	2.2	3		5 – 200	86 – 26			1,365.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Variable speed self-priming multi-stage pumps fitted with an inverter
- Single-phase power supply 230 V - 50 Hz
- Three-phase motor 230 V - 50 Hz
- Impellers and diffusers: **AISI 304 stainless steel**

The group consists of:

- Pump
- **TISSSEL 200** frequency converter programmed for a constant pressure
- Pressure transducer
- Cables to connect the INVERTER to the pump



HF CENTRIFUGAL PUMPS (MEDIUM FLOW)

MODEL			POWER P ₂		▲	PERFORMANCE		PORTS		PRICE
Single-phase	Code		kW	HP		Q l/min	H m	DN ₁	DN ₂	€
HFm 50B	47HF50M6BA1	1	0.37	0.50	-	50 – 300	10 – 4	1½"	1½"	168.00
HFm 50A	47HF50M6AA1		0.55	0.75		50 – 300	12 – 6			173.00
HFm 51B	47HF5M1BA1		0.55	0.75		50 – 300	17.2 – 5.4			205.00
HFm 51A	47HF5M1AA1		0.75	1		50 – 300	20.2 – 8.4			210.00
HFm 70C	47HF61MC7A1		1.1	1.5		50 – 300	28 – 15			320.00
HFm 70B	47HF61MB7A1		1.5	2		50 – 300	32 – 19			345.00
HFm 5C	47HF5M0CA1	1	0.55	0.75	-	100 – 400	12 – 6.5	2"	2"	210.00
HFm 5B	47HF5M0BA1		0.75	1		100 – 500	13.2 – 5			218.00
HFm 5A	47HF5M0AA1		1.1	1.5		100 – 600	13.8 – 3			230.00
HFm 5BM	47HF5M2B7A1		1.1	1.5		100 – 600	18.5 – 6			315.00
HFm 5AM	47HF5M2A7A1		1.5	2		100 – 600	21.5 – 10			330.00

Three-phase					▲					
HF	Code									
HF 50B	47HF50T6BA	1	0.37	0.50	IE2	50 – 300	10 – 4	1½"	1½"	183.00
HF 50A	47HF50T6AA		0.55	0.75		50 – 300	12 – 6			188.00
HF 51B	47HF5T1BA		0.55	0.75		50 – 300	17.2 – 5.4			220.00
HF 51A	47HF5T1AA		0.75	1		50 – 300	20.2 – 8.4			225.00
HF 70C	47HF61TC7A		1.1	1.5		50 – 300	28 – 15			330.00
HF 70B	47HF61TB7A		1.5	2		50 – 300	32 – 19			345.00
HF 70A	47HF61TA7A	1	2.2	3	IE3	50 – 300	38 – 25	2"	2"	356.00
HF 5C	47HF5T0CA		0.55	0.75		100 – 400	12 – 6.5			225.00
HF 5B	47HF5T0BA		0.75	1		100 – 500	13.2 – 5			233.00
HF 5A	47HF5T0AA		1.1	1.5		100 – 600	13.8 – 3			240.00
HF 5BM	47HF5T2B7A		1.1	1.5		100 – 600	18.5 – 6			325.00
HF 5AM	47HF5T2A7A		1.5	2		100 – 600	21.5 – 10			330.00

■ Impeller: 1=AISI 304 stainless steel; ▲ Three phase motor efficiency class (IEC 60034-30-1)

• Pump body: cast iron



HF CENTRIFUGAL PUMPS (HIGH FLOW)

MODEL			POWER			PERFORMANCE		PORTS		PRICE
Single-phase	Code	■	kW	P2 HP	▲	Q l/min	H m	DN1	DN2	€
HFm 4	47HF5M0LA1	1	0.75	1	–	200 – 800	9.3 – 3	2½"	2½"	210.00
HFm 6C	47HF6M0C7A1		1.1	1.5		200 – 1000	11.7 – 3	3"	3"	370.00
HFm 6B	47HF6M0B7A1		1.5	2		200 – 1100	14.5 – 5			385.00
HFm 6A	47HF6M0A7A1		2.2	3		200 – 1200	18.1 – 6			450.00
Three-phase										
HF 4	47HF5T0LA	1	0.75	1	IE3	200 – 800	9.3 – 3	2½"	2½"	225.00
HF 6C	47HF6T0C7A		1.1	1.5		200 – 1000	11.7 – 3	3"	3"	380.00
HF 6B	47HF6T0B7A		1.5	2		200 – 1100	14.5 – 5			385.00
HF 6A	47HF6T0A7A		2.2	3		200 – 1200	18.1 – 6			400.00
HF 8B	47HF8T0B1A	2	3	4	IE3	200 – 1200	21 – 9	4"	4"	630.00
HF 8A	47HF83T0AA		4	5.5		200 – 1200	24 – 13			690.00
HF 20B	47HF826BA		3	4		400 – 1600	19 – 8			640.00
HF 20A	47HF826AA		4	5.5		400 – 1800	21.5 – 6			690.00
HF 30B	47HF93TBE		5.5	7.5		600 – 2000	18 – 13			840.00
HF 30A	47HF93TAE		7.5	10		600 – 2200	23 – 18			870.00

■ Impeller: 1=AISI 304 stainless steel; 2=brass ▲ Three phase motor efficiency class (IEC 60034-30-1)

• Pump body: cast iron

STANDARDIZED CENTRIFUGAL PUMPS

F MONOBLOCK CENTRIFUGAL PUMPS (EN 733)

MODEL (n= 2900 min ⁻¹)			POWER P ₂			PERFORMANCE		PRICE	Counterflanges *		
Single-phase	Code		kW	HP	▲	Q l/min	H m	Pumps €	DN	Code	PRICE €
Fm 32/160C	4FN32148C7A1	1	1.5	2	–	100 – 350	24 – 14	550.00	DN 50 x 32 (2" x 1¼")	ASS14FL0320	51.00
Fm 32/160B	4FN32159B1A1		2.2	3		100 – 400	30 – 17	670.00			
Fm 40/125C	4FN40125CA1	1	1.1	1.5	–	100 – 550	16 – 6	525.00	DN 65 x 40 (2½" x 1½")	ASS14FL0400	57.00
Fm 40/125B	4FN40125BA1		1.5	2		100 – 600	20.5 – 9	550.00			
Fm 40/160C	4FN40158C1A1	1	2.2	3		100 – 600	27 – 14	670.00	DN 65 x 50 (2½" x 2")	ASS14FL0500	58.00
Fm 50/125C	4FN50162C1A1	1	2.2	3	–	300 – 1200	17.5 – 6	660.00			
Three-phase											
F 32/160C	4FN32148C7A	1	1.5	2	IE3	100 – 350	24 – 14	550.00	DN 50 x 32 (2" x 1¼")	ASS14FL0320	51.00
F 32/160B	4FN32149B7A		2.2	3		100 – 400	30 – 17	570.00			
F 32/160A	4FN32160A1A		3	4		100 – 450	37 – 24	635.00			
F 32/200C	4FN32203CA	1	4	5.5	IE3	100 – 450	44 – 31.5	745.00			
F 32/200B	4FN32203BE		5.5	7.5		100 – 500	51 – 36	800.00			
F 32/200A	4FN32203AE		7.5	10		100 – 500	57 – 44	830.00			
F 32/200BH	4FN3220HBA	1	3	4	IE3	100 – 300	45 – 37	720.00			
F 32/200AH	4FN3220HAA		4	5.5		100 – 320	55 – 44	745.00			
F 32/250C	4FN32250CE		9.2	12.5		100 – 450	75 – 60	1,650.00			
F 32/250B	4FN32250BE	2	11	15	IE3	100 – 500	87 – 70	1,660.00			
F 32/250A	4FN32250AE		15	20		100 – 500	97 – 80	1,770.00			
F 40/125C	4FN40125CA	1	1.1	1.5	IE3	100 – 550	16 – 6	525.00	DN 65 x 40 (2½" x 1½")	ASS14FL0400	57.00
F 40/125B	4FN40125BA		1.5	2		100 – 600	20.5 – 9	550.00			
F 40/125A	4FN40125AA		2.2	3		100 – 700	26 – 10	570.00			
F 40/160C	4FN40158C7A	1	2.2	3	IE3	100 – 600	27 – 14	570.00			
F 40/160B	4FN40159B1A		3	4		100 – 600	32 – 20	635.00			
F 40/160A	4FN40163AA		4	5.5		100 – 700	38 – 20	690.00			
F 40/200B	4FN40203BE	1	5.5	7.5	IE3	100 – 700	47 – 28	824.00			
F 40/200A	4FN40203AE		7.5	10		100 – 700	55 – 41	866.00			
F 40/250C	4FN40250CE		9.2	12.5		100 – 700	64 – 47	1,650.00			
F 40/250B	4FN40250BE	2	11	15	IE3	100 – 700	71 – 55	1,660.00			
F 40/250A	4FN40250AE		15	20		100 – 700	88 – 72	1,770.00			
F 50/125C	4FN50162C7A	1	2.2	3	IE3	300 – 1200	17.5 – 6	570.00	DN 65 x 50 (2½" x 2")	ASS14FL0500	58.00
F 50/125B	4FN50162B1A		3	4		300 – 1200	20.7 – 9	635.00			
F 50/125A	4FN50161AA		4	5.5		300 – 1200	23.5 – 13	700.00			
F 50/160C	4FN50163CA	1	4	5.5	IE3	300 – 1000	27 – 16	755.00			
F 50/160B	4FN50163BE		5.5	7.5		300 – 1100	32 – 21	800.00			
F 50/160A	4FN50163AE		7.5	10		300 – 1100	37 – 27	830.00			
F 50/200C	4FN50165CE	2	11	15	IE3	400 – 1700	44 – 30	1,635.00			
F 50/200B	4FN50165BE		15	20		400 – 1700	52 – 38	1,745.00			
F 50/200A	4FN50165AE		18.5	25		400 – 1800	61 – 45	1,840.00			
F 50/200AR	4FN50166AE	2	22	30	IE3	400 – 1800	69 – 53	1,990.00			
F 50/250D	4FN50167E		9.2	12.5		300 – 900	51 – 32	1,650.00			
F 50/250C	4FN50168E		11	15		300 – 900	59 – 42	1,660.00			
F 50/250B	4FN50169E	2	15	20	IE3	300 – 1000	72 – 59	1,752.00	DN 80 x 65 (3" x 2½")	ASS14FL0650	65.00
F 50/250A	4FN50170E		18.5	25		300 – 1000	85 – 73	1,855.00			
F 50/250AR	4FN50172AE		22	30		300 – 1000	95 – 83	1,990.00			
F 65/125C	4FN65125CA	2	4	5.5	IE3	600 – 1800	16 – 11	840.00			
F 65/125B	4FN65125BE		5.5	7.5		600 – 2000	18 – 13	876.00			
F 65/125A	4FN65125AE		7.5	10		600 – 2200	23 – 18	910.00			
F 65/160C	4FN65158E	2	9.2	12.5	IE3	600 – 2200	32 – 22	1,620.00			
F 65/160B	4FN65159E		11	15		600 – 2400	36.5 – 23	1,635.00			
F 65/160A	4FN65160E		15	20		600 – 2400	40.5 – 28	1,720.00			
F 65/200B	4FN65165BE	2	15	20	IE3	200 – 2400	44 – 30.5	1,770.00			
F 65/200A	4FN65165AE		18.5	25		200 – 2500	50 – 36.5	1,868.00			
F 65/200AR	4FN65170AE		22	30		200 – 2600	57 – 42	2,020.00			
F 65/250C	4FN65250CE	2	30	40	IE3	400 – 2350	76 – 53	4,330.00			
F 65/250B	4FN65250BE		37	50		400 – 2500	87 – 62	4,575.00			
F 65/250A	4FN65250AE		45	60		400 – 2600	95 – 68	4,675.00			

F MONOBLOCK CENTRIFUGAL PUMPS (EN 733)

MODEL (n= 2900 min ⁻¹)		POWER P ₂			PERFORMANCE		PRICE Pumps	Counterflanges *												
Three-phase	Code		kW	HP	▲	Q l/min	H m	€	DN	Code	PRICE €									
F 80/160D	4FN80160DE	2	11	15	IE3	500 – 4000	25 – 10	1,645.00	DN 100 x 80 (4" x 3")	ASS14FL0800	80.00									
F 80/160C	4FN80160CE		15	20		500 – 4000	30 – 15	1,770.00												
F 80/160B	4FN80160BE		18.5	25		500 – 4000	35 – 20	1,840.00												
F 80/160A	4FN80160AE		22	30		500 – 4000	40 – 25	1,990.00												
F 80/200B	4FN80200BE	2	30	40	IE3	500 – 3650	56 – 34.5	4,320.00												
F 80/200A	4FN80200AE		37	50		500 – 3900	62 – 40	4,560.00												
F 80/250B	4FN80250BE	2	45	60		600 – 3600	77 – 54	4,790.00							DN 125 x 100 (5" x 4")	ASS14FL1000	96.00			
F 80/250A	4FN80250AE		55	75		600 – 3900	88.5 – 60	9,580.00												
F 100/160C	4FNA10160CNE	2	15	20		1000 – 5000	30 – 12	1,860.00												
F 100/160B	4FNA10160BNE		18.5	25		1000 – 5200	34 – 14.5	1,930.00												
F 100/160A	4FNA10160ANE	2	22	30		1000 – 5500	38 – 17.5	2,080.00										DN 125 x 100 (5" x 4")	ASS14FL1000	96.00
F 100/200C	4FNA10200CE		30	40		833 – 4650	51 – 28	4,410.00												
F 100/200B	4FNA10200BE		37	50		833 – 4900	57 – 33	4,650.00												
F 100/200A	4FNA10200AE		45	60		833 – 5250	63 – 38	4,760.00												
F 100/250B	4FNA10250BE	2	55	75		800 – 5150	75 – 48	9,580.00												
F 100/250A	4FNA10250AE		75	100		800 – 5750	89 – 58	10,300.00												

■ Impeller: 1=brass; 2=cast iron

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: cast iron
- Protection: IP X5

*** Counterflanges KIT including screws, nuts and gaskets has to be ordered separately**



F-INOX MONOBLOCK STAINLESS STEEL CENTRIFUGAL PUMPS (EN 733)

MODEL (n= 2900 min ⁻¹)		POWER P ₂			PERFORMANCE		PRICE
Three-phase	Code	kW	HP	▲	Q l/min	H m	€
F 50/160C-I	4F50163XCA	4	5.5	IE3	300 – 1000	27 – 16	2,600.00
F 50/160B-I	4F50163XBE	5.5	7.5		300 – 1100	32 – 21	2,650.00
F 50/160A-I	4F50163XAE	7.5	10		300 – 1100	37 – 27	2,690.00
F 65/125C-I	4F65125XCA	4	5.5	IE3	600 – 1800	16 – 11	3,100.00
F 65/125B-I	4F65125XBE	5.5	7.5		600 – 2000	18 – 13	3,150.00
F 65/125A-I	4F65125XAE	7.5	10		600 – 2200	23 – 18	3,180.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: precision cast AISI 316 stainless steel (without counterflanges)
- Impeller: precision cast AISI 316 stainless steel
- Shaft: AISI 316L stainless steel
- Protection: IP X5



F4 MONOBLOCK CENTRIFUGAL PUMPS (EN 733)

MODEL (n= 1450 min ⁻¹)			POWER P ₂			PERFORMANCE		PRICE Pumps	Counterflanges *			
Three-phase	Code		kW	HP	▲	Q l/min	H m	€	DN	Code	PRICE €	
F4-32/160B	4FP32160BA	1	0.37	0.5	IE2	50 – 200	7.5 – 4.5	520.00	DN 50 x 32 (2" x 1¼")	ASS14FL0320	51.00	
F4-32/160A	4FP32160AA		0.37	0.5		50 – 225	9 – 5	520.00				
F4-32/200B	4FP32203BA	1	0.75	1	IE3	50 – 250	12.5 – 9	715.00				
F4-32/200A	4FP32203AA		1.1	1.5		50 – 250	14 – 10.5	745.00				
F4-32/200BH	4FP3220HBA	1	0.75	1		50 – 150	11.3 – 9.2	715.00				
F4-32/200AH	4FP3220HAA		0.75	1		50 – 160	13.8 – 11	715.00				
F4-32/250C	4FP32250CA	2	1.1	1.5		50 – 220	18.4 – 15	1,010.00				
F4-32/250B	4FP32250BA		1.5	2		50 – 250	21.7 – 17.4	1,030.00				
F4-32/250A	4FP32250AA		2.2	3		50 – 270	23.8 – 18.7	1,060.00				
F4-40/160B	4FP40160BA	1	0.37	0.5		IE2	50 – 320	7.5 – 3.5	520.00	DN 65 x 40 (2½" x 1½")	ASS14FL0400	57.00
F4-40/160A	4FP40160AA		0.55	0.75			50 – 350	9 – 4.5	540.00			
F4-40/200B	4FP40203BA	1	0.75	1	IE3	50 – 350	11.5 – 7	745.00				
F4-40/200A	4FP40203AA		1.1	1.5		50 – 350	13.8 – 10	765.00				
F4-40/250C	4FP40250CA	2	1.1	1.5		50 – 400	15.5 – 10	1,000.00				
F4-40/250B	4FP40250BA		1.5	2		50 – 400	17.5 – 12	1,020.00				
F4-40/250A	4FP40250AA		2.2	3		50 – 400	22 – 17	1,060.00				
F4-50/125B	4FP50160BA	1	0.55	0.75		IE2	150 – 600	5 – 2	540.00	DN 65 x 50 (2½" x 2")	ASS14FL0500	58.00
F4-50/125A	4FP50160AA		0.55	0.75	150 – 600		6 – 3	540.00				
F4-50/160B ⁽¹⁾	4FP50163BA	1	0.75	1	IE3	150 – 650	8 – 3.8	715.00				
F4-50/160A ⁽¹⁾	4FP50163AA		1.1	1.5		150 – 700	9.3 – 4.5	745.00				
F4-50/200C	4FP50165CA	2	1.5	2		200 – 850	11 – 7.5	1,000.00				
F4-50/200B	4FP50165BA		2.2	3		200 – 850	13 – 9.5	1,020.00				
F4-50/200A	4FP50165AA		2.2	3		200 – 900	15 – 11.2	1,020.00				
F4-50/200AR	4FP50166AA		3	4		200 – 900	17 – 13.2	1,060.00				
F4-50/250D	4FP50167A	2	1.1	1.5		150 – 650	12.5 – 5	1,000.00				
F4-50/250C	4FP50168A		1.5	2		150 – 700	14 – 5	1,010.00				
F4-50/250B	4FP50169A		2.2	3		150 – 700	18 – 10.5	1,050.00				
F4-50/250A	4FP50170A		2.2	3		150 – 700	20 – 13	1,050.00				
F4-50/250AR	4FP50172AA		3	4		150 – 700	23.5 – 17	1,060.00				
F4-65/125B ⁽¹⁾	4FP65125BA	2	0.75	1	IE3	300 – 1100	4.7 – 3	780.00	DN 80 x 65 (3" x 2½")	ASS14FL0650	65.00	
F4-65/125A ⁽¹⁾	4FP65125AA		1.1	1.5		300 – 1200	5.7 – 4	810.00				
F4-65/160C	4FP65158A	2	1.1	1.5		300 – 1100	7.5 – 5.5	930.00				
F4-65/160B	4FP65159A		1.5	2		300 – 1200	9 – 5.7	960.00				
F4-65/160A	4FP65160A		2.2	3		300 – 1200	10.1 – 7	990.00				
F4-65/200A	4FP65165AA	2	2.2	3		300 – 1250	12 – 8.5	1,060.00				
F4-65/200AR	4FP65170AA		3	4		300 – 1300	14 – 10	1,090.00				
F4-65/250B	4FP65250BA	2	4	5.5		200 – 1250	21.8 – 15	1,840.00				
F4-65/250A	4FP65250AA		5.5	7.5		200 – 1300	23.5 – 17	1,870.00				

F4 MONOBLOCK CENTRIFUGAL PUMPS (EN 733)

MODEL (n= 1450 min ⁻¹)			POWER P ₂			PERFORMANCE		PRICE Pumps	Counterflanges *		
Three-phase	Code	■	kW	HP	▲	Q l/min	H m	€	DN	Code	PRICE €
F4-80/160D	4FP80160DA	2	1.5	2	IE3	300 – 2000	6.3 – 2.5	1,000.00	DN 100 x 80 (4" x 3")	ASS14FL0800	80.00
F4-80/160C	4FP80160CA		2.2	3		300 – 2000	7.5 – 3.8	1,020.00			
F4-80/160B	4FP80160BA		2.2	3		300 – 2000	8.8 – 5	1,020.00			
F4-80/160A	4FP80160AA		3	4		300 – 2000	10 – 6.2	1,060.00			
F4-80/200B	4FP80200BA	2	4	5.5		300 – 1800	14 – 9	1,770.00			
F4-80/200A	4FP80200AA		5.5	7.5		300 – 1900	15.5 – 10.5	1,800.00			
F4-80/250B	4FP80250BA	2	5.5	7.5		300 – 1800	19.5 – 13.5	2,195.00			
F4-80/250A	4FP80250AA		7.5	10		300 – 1950	22 – 15	2,310.00			
F4-100/160B	4FPA10160BNA	2	2.2	3	IE3	400 – 2600	8.3 – 3.5	1,180.00	DN 125 x 100 (5" x 4")	ASS14FL1000	96.00
F4-100/160A	4FPA10160ANA		3	4		400 – 2800	10 – 4.7	1,215.00			
F4-100/200C	4FPA10200CA	2	4	5.5		400 – 2300	12.7 – 7	1,920.00			
F4-100/200B	4FPA10200BA		5.5	7.5		400 – 2400	14.2 – 8.5	1,950.00			
F4-100/200A	4FPA10200AA		5.5	7.5		400 – 2600	15.8 – 9.5	1,950.00			
F4-100/250B	4FPA10250BA		7.5	10		400 – 2600	18.5 – 11.5	2,430.00			
F4-100/250A	4FPA10250AA	2	9.2	12.5		400 – 2900	22 – 13.5	2,600.00			

■ Impeller: 1=brass; 2=cast iron

▲ Three phase motor efficiency class (IEC 60034-30-1)

⁽¹⁾ Pumps cast in AISI 316 stainless steel available on request

- Pump body: cast iron
- Protection: IP X5

* Counterflanges KIT including screws, nuts and gaskets has to be ordered separately



STANDARDIZED CENTRIFUGAL PUMPS

FG BARE AXLE CENTRIFUGAL PUMPS (EN 733)

MODEL			2 POLES n= 2900 min ⁻¹				4 POLES n= 1450 min ⁻¹				PRICE	PRICE
Pump	Code		Motor to connect P ₂		PERFORMANCE		Motor to connect P ₂		PERFORMANCE		Pumps	Counterflanges *
			kW	HP	Q m ³ /h	H m	kW	HP	Q m ³ /h	H m	€	€
FG 32/160C	4FG3216C010	1	1.5	2	6 – 21	24 – 14	0.25	0.33	3 – 10.5	6 – 3.5	680.00	51.00 DN 50 x 32 (2" x 1 1/4") Cod. ASS14FL0320
FG 32/160B	4FG3216B010		2.2	3	6 – 24	30 – 17	0.37	0.5	3 – 12	7.5 – 4	680.00	
FG 32/160A	4FG3216A010		3	4	6 – 27	37 – 24	0.37	0.5	3 – 13.5	9 – 6	680.00	
FG 32/200C	4FG3220C010	1	4	5.5	6 – 27	44 – 31.5	0.55	0.75	3 – 13.5	11 – 8	760.00	
FG 32/200B	4FG3220B010		5.5	7.5	6 – 30	51 – 36	0.75	1	3 – 15	12.5 – 9	760.00	
FG 32/200A	4FG3220A010		7.5	10	6 – 30	57 – 44	1.1	1.5	3 – 15	14 – 11	760.00	
FG 32/200BH	4FG3221BH010	1	3	4	6 – 18	45 – 37	0.55	0.75	3 – 9	11 – 9	760.00	
FG 32/200AH	4FG3221AH010		4	5.5	6 – 19.2	55 – 44	0.55	0.75	3 – 9.6	13.8 – 11	760.00	
FG 32/250C	4FG3225C010	2	9.2	12.5	6 – 27	75 – 60	1.1	1.5	3 – 13.2	18.4 – 15	990.00	57.00 DN 65 x 40 (2 1/2" x 1 1/2") cod. ASS14FL0400
FG 32/250B	4FG3225B010		11	15	6 – 30	87 – 70	1.5	2	3 – 15	21.7 – 17.4	990.00	
FG 32/250A	4FG3225A010		15	20	6 – 30	97 – 80	2.2	3	3 – 16.2	23.8 – 18.7	990.00	
FG 40/125C	4FG4012C010	1	1.1	1.5	6 – 33	16 – 6	–	–	–	–	700.00	
FG 40/125B	4FG4012B010		1.5	2	6 – 36	20.5 – 9	–	–	–	–	700.00	
FG 40/125A	4FG4012A010		2.2	3	6 – 42	26 – 10	–	–	–	–	700.00	
FG 40/160C	4FG4016C010	1	2.2	3	6 – 36	27 – 14	0.37	0.5	3 – 18	6.5 – 3.5	680.00	
FG 40/160B	4FG4016B010		3	4	6 – 36	32 – 20	0.37	0.5	3 – 18	8 – 5	680.00	
FG 40/160A	4FG4016A010		4	5.5	6 – 42	38 – 20	0.55	0.75	3 – 21	9.5 – 5	680.00	
FG 40/200B	4FG4020B010	1	5.5	7.5	6 – 42	47 – 28	0.75	1	3 – 21	11.5 – 7	790.00	58.00 DN 65 x 50 (2 1/2" x 2") cod. ASS14FL0500
FG 40/200A	4FG4020A010		7.5	10	6 – 42	55 – 41	1.1	1.5	3 – 21	13.5 – 10	790.00	
FG 40/250C	4FG4025C010	2	9.2	12.5	6 – 42	64 – 47	1.1	1.5	3 – 21	16 – 11.5	980.00	
FG 40/250B	4FG4025B010		11	15	6 – 42	71 – 55	1.5	2	3 – 21	17.5 – 13.5	980.00	
FG 40/250A	4FG4025A010		15	20	6 – 42	88 – 72	2.2	3	3 – 21	22 – 18	980.00	
FG 50/125C	4FG5012C010	1	2.2	3	18 – 72	17.5 – 6	0.37	0.5	9 – 36	4.3 – 1.5	690.00	
FG 50/125B	4FG5012B010		3	4	18 – 72	20.7 – 9	0.55	0.75	9 – 36	5.1 – 2.3	690.00	
FG 50/125A	4FG5012A010		4	5.5	18 – 72	23.5 – 13	0.55	0.75	9 – 36	5.8 – 3.2	690.00	
FG 50/160C	4FG5016C010	1	4	5.5	18 – 60	27 – 16	0.55	0.75	9 – 30	7 – 4	760.00	65.00 DN 80 x 65 (3" x 2 1/2") cod. ASS14FL0650
FG 50/160B	4FG5016B010		5.5	7.5	18 – 66	32 – 21	0.75	1	9 – 33	8 – 5	760.00	
FG 50/160A	4FG5016A010		7.5	10	18 – 66	37 – 27	1.1	1.5	9 – 33	9 – 7	760.00	
FG 50/200C	4FG5020C010	2	11	15	24 – 102	44 – 30	1.5	2	12 – 51	11 – 7.5	960.00	
FG 50/200B	4FG5020B010		15	20	24 – 102	52 – 38	2.2	3	12 – 51	13 – 9.5	960.00	
FG 50/200A	4FG5020A010		18.5	25	24 – 108	61 – 45	2.2	3	12 – 54	15 – 11	960.00	
FG 50/200AR	4FG5021AR010		22	30	24 – 108	69 – 53	3	4	12 – 54	17 – 13	960.00	
FG 50/250D	4FG5025D010	2	9.2	12.5	18 – 54	51 – 32	1.1	1.5	9 – 27	12.5 – 8	960.00	
FG 50/250C	4FG5025C010		11	15	18 – 54	59 – 42	1.5	2	9 – 27	14.5 – 10.5	960.00	
FG 50/250B	4FG5025B010		15	20	18 – 60	72 – 59	2.2	3	9 – 30	18 – 14.5	960.00	
FG 50/250A	4FG5025A010		18.5	25	18 – 60	85 – 73	2.2	3	9 – 30	21 – 18	960.00	65.00 DN 80 x 65 (3" x 2 1/2") cod. ASS14FL0650
FG 50/250AR	4FG5026AR010		22	30	18 – 60	95 – 83	3	4	9 – 30	24 – 21	960.00	
FG 65/125C	4FG6512C010	2	4	5.5	36 – 108	16 – 11	0.55	0.75	18 – 54	4 – 2.7	830.00	
FG 65/125B	4FG6512B010		5.5	7.5	36 – 120	18 – 13	0.75	1	18 – 60	4.5 – 3.2	830.00	
FG 65/125A	4FG6512A010		7.5	10	36 – 132	23 – 18	1.1	1.5	18 – 66	5.8 – 4.5	830.00	
FG 65/160C	4FG6516C010	2	9.2	12.5	36 – 132	32 – 22	1.1	1.5	18 – 66	8 – 5.5	960.00	65.00 DN 80 x 65 (3" x 2 1/2") cod. ASS14FL0650
FG 65/160B	4FG6516B010		11	15	36 – 144	36.5 – 23	1.5	2	18 – 72	9 – 5.5	960.00	
FG 65/160A	4FG6516A010		15	20	36 – 144	40.5 – 28	2.2	3	18 – 72	10 – 7	960.00	

STANDARDIZED CENTRIFUGAL PUMPS

FG BARE AXLE CENTRIFUGAL PUMPS (EN 733)

MODEL			2 POLES n= 2900 min ⁻¹				4 POLES n= 1450 min ⁻¹				PRICE	PRICE
			Motor to connect P ₂		PERFORMANCE		Motor to connect P ₂		PERFORMANCE		Pumps	Counterflanges *
Pump	Code		kW	HP	Q m ³ /h	H m	kW	HP	Q m ³ /h	H m	€	€
FG 65/200B	4FG6520B010	2	15	20	12 – 144	44 – 30.5	2.2	3	6 – 72	10.5 – 7.3	990.00	65.00
FG 65/200A	4FG6520A010		18.5	25	12 – 150	50 – 36.5	2.2	3	6 – 75	12 – 8.5	990.00	
FG 65/200AR	4FG6521AR010		22	30	12 – 156	57 – 42	3	4	6 – 78	14 – 10	990.00	
FG 65/250C	4FG6525C010	2	30	40	24 – 141	76 – 53	3	4	12 – 70.5	19 – 13	1,470.00	DN 80 x 65 (3" x 2½") cod. ASS14FL0650
FG 65/250B	4FG6525B010		37	50	24 – 150	87 – 62	4	5.5	12 – 75	21.5 – 15.5	1,470.00	
FG 65/250A	4FG6525A010		45	60	24 – 156	95 – 68	5.5	7.5	12 – 78	23.5 – 17	1,470.00	
FG 80/160D	4FG8016D010	2	11	15	30 – 240	25 – 10	1.5	2	15 – 120	6 – 2.5	980.00	80.00
FG 80/160C	4FG8016C010		15	20	30 – 240	30 – 15	2.2	3	15 – 120	7.5 – 3.5	980.00	
FG 80/160B	4FG8016B010		18.5	25	30 – 240	35 – 20	2.2	3	15 – 120	8.5 – 5	980.00	
FG 80/160A	4FG8016A010	2	22	30	30 – 240	40 – 25	3	4	15 – 120	10 – 6	980.00	DN 100 x 80 (4" x 3") cod. ASS14FL0800
FG 80/200B	4FG8020B010		30	40	30 – 219	56 – 34.5	4	5.5	15 – 109.5	14 – 8.5	1,190.00	
FG 80/200A	4FG8020A010		37	50	30 – 234	62 – 40	5.5	7.5	15 – 117	15.5 – 10	1,190.00	
FG 80/250B	4FG8025B010	2	45	60	36 – 216	77 – 54	5.5	7.5	18 – 108	19 – 13.5	1,600.00	96.00
FG 80/250A	4FG8025A010		55	75	36 – 234	88.5 – 60	7.5	10	18 – 117	22 – 15	1,600.00	
FG 100/160C	4FG9116CN010	2	15	20	60 – 300	30 – 12	2.2	3	24 – 144	7.5 – 3	1,110.00	DN 125 x 100 (5" x 4") cod. ASS14FL1000
FG 100/160B	4FG9116BN010		18.5	25	60 – 312	34 – 14.5	2.2	3	24 – 156	8.3 – 3.5	1,110.00	
FG 100/160A	4FG9116AN010		22	30	60 – 330	38 – 17.5	3	4	24 – 168	9.5 – 3.8	1,110.00	
FG 100/200C	4FG9120C010	2	30	40	48 – 279	51 – 28	4	5.5	24 – 139.5	12.5 – 7	1,330.00	DN 125 x 100 (5" x 4") cod. ASS14FL1000
FG 100/200B	4FG9120B010		37	50	48 – 294	57 – 33	5.5	7.5	24 – 147	14 – 8	1,330.00	
FG 100/200A	4FG9120A010		45	60	48 – 315	63 – 38	5.5	7.5	24 – 157.5	15.5 – 9.5	1,330.00	
FG 100/250B	4FG9125B010	2	55	75	48 – 309	75 – 48	7.5	10	24 – 154.5	18.5 – 12	1,700.00	
FG 100/250A	4FG9125A010		75	100	48 – 345	89 – 58	9.2	12.5	24 – 172.5	22 – 14.5	1,700.00	

■ Impeller: 1=brass; 2=cast iron

• Pump body: cast iron

* Counterflanges KIT including screws, nuts and gaskets has to be ordered separately



● If requested the FG pumps can be trialled and tested in accordance with standard EN 12845 for use in fire prevention units.

FLUID SOLAR SOLAR PUMPS KIT

MODEL		INPUT POWER P ₁	MAXIMUM PERFORMANCE*		PORT DN	PRICE €
Pumps	Code		Q l/min	H m		
FLUID SOLAR 1/10	49M4SK110A	750 W	5 – 38	79 – 12	1"	1,448.00
FLUID SOLAR 1/20	49M4SK120A	1500 W	5 – 38	165 – 35		1,830.00
FLUID SOLAR 2/6	49M4SK206A	750 W	5 – 75	64 – 12		1,415.00
FLUID SOLAR 2/14	49M4SK214A	1500 W	5 – 70	140 – 20		1,790.00
FLUID SOLAR 4/4	49M4SK404A	750 W	5 – 102	38.5 – 12		1,415.00
FLUID SOLAR 4/8	49M4SK408A	1500 W	5 – 120	85 – 24	1 1/4"	1,790.00
FLUID SOLAR 6/3	49M4SK603A	750 W	5 – 150	30 – 9		1,415.00
FLUID SOLAR 6/6	49M4SK606A	1500 W	5 – 180	65 – 18		1,790.00

* Performance with:

- solar radiation of 1000 W/m²;
- available voltage of the photovoltaic panels 100 VDC;
- photovoltaic panels facing SOUTH (facing NORTH for installations in the southern hemisphere) and optimised angle of inclination to the horizon according to the latitude of the installation site..

COMPONENTS

- Pump with 2 metres long power cable
- Control box to protect the pump from dry running (1)
- N° 2 male connectors type SMK (2)
- N° 2 female connectors type SMK (3)
- N° 2 Y female/male-male connectors type MC4 (4)
(only for FLUID SOLAR with P₁=1500 W)
- N° 2 Y male/female-female connectors type MC4 (5)
(only for FLUID SOLAR with P₁=1500 W)
- RPS2 electrical cable resin joint (6)
- Patent n. 0001413386, EP2419642
- Patent n. EP2300717
- FLUID SOLAR® Registered trade mark n. 0001516301



CABLES FOR PHOTOVOLTAIC SOLAR SYSTEM

MODEL	Code	WEIGHT	PRICE € per metre
1 x 4 mm ² Red color	117SF104R	60 g/m	2.70
1 x 4 mm ² Black color	117SF104N	60 g/m	2.70
1 x 6 mm ² Red color	117SF106R	80 g/m	3.20
1 x 6 mm ² Black color	117SF106N	80 g/m	3.20

- ➡ These cables should be used to connect the control unit to the photovoltaic modules according to the diagram in the installation manual.
- ➡ The overall length of the connections must comply with the following regulations:
 - utilize cables of 4 mm² cross-section for connections of a maximum of 40 metres in length
 - utilize cables of 6 mm² cross-section for connections from 40 metres in length up to a maximum of 80 metres
- ➡ In order to connect the control box to the pump utilize four polar cables in accordance with the diagram in the installation manual.

PHOTOVOLTAIC MODULES

MODEL	Code	QUANTITY	PRICE €
PANASONIC mod. VBHN240SJ25	538MF001	n° 4 modules	2,290.00
	538MF002	n° 8 modules	4,570.00

- To run FLUID SOLAR at **P₁=750 W n. 4 photovoltaic modules are required.**
- To run FLUID SOLAR at **P₁=1500 W n. 8 photovoltaic modules are required.**
- No load voltage of each module 50 VDC.
- The total rated power of the four photovoltaic modules is 980 Wp
- The total rated power of the eight photovoltaic modules is 1960 Wp

HIT Original HIT® high efficiency photovoltaic modules (PANASONIC Patent)



3SR 3" SUBMERSIBLE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
3SRm 2/15	4930215PLA1	0.37	0.50	10 – 45	42 – 10	1"	375.00
3SRm 2/22	4930222PLA1	0.55	0.75	10 – 45	62 – 15		408.00
3SRm 2/30	4930230PLA1	0.75	1	10 – 45	84.5 – 20.5		448.00
3SRm 2/43	4930243PLA1	1.1	1.5	10 – 45	121 – 29		522.00
Three-phase							
3SR 2/15	4930215PLA	0.37	0.50	10 – 45	42 – 10	1"	375.00
3SR 2/22	4930222PLA	0.55	0.75	10 – 45	62 – 15		408.00
3SR 2/30	4930230PLA	0.75	1	10 – 45	84.5 – 20.5		448.00
3SR 2/43	4930243PLA	1.1	1.5	10 – 45	121 – 29		522.00

- Oil filled rewindable motor
- Motor power cable: 1.5 metres

DAVIS 4" SUBMERSIBLE PUMP WITH PERIPHERAL IMPELLER

MODEL		PUMP DIAMETER	POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	mm	kW	HP	Q l/min	H m	DN	€
DAVIS®	484SK40A1	101	0.75	1	5 – 50	68 – 5	1"	340.00

- Power cable: supplied with 20 metres long power cable
- Impeller: brass
- Two mechanical seals separated by an oil chamber
- Capacitor and motor with built-in thermal overload protector
- Patent n. EP2300717 - EP2419642
- DAVIS® Registered trade mark n. 0001552668

DAVIS®: Ready to fit monoblock stainless steel submersible pump. Supplied with capacitor and motor with built-in motor protector.
N.B. Suitable for clean water without sand.

4BLOCK 4" MONOBLOCK SUBMERSIBLE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
4BLOCKm 2/10	49M41210LA1	0.55	0.75	10 – 60	65 – 20	1¼"	400.00
4BLOCKm 2/13	49M41213LA1	0.75	1	10 – 60	85 – 26		428.00
4BLOCKm 2/20	49M41220LA1	1.1	1.5	10 – 60	125 – 39		544.00
4BLOCKm 4/7	49M41407LA1	0.55	0.75	20 – 100	44 – 17	1¼"	390.00
4BLOCKm 4/9	49M41409LA1	0.75	1	20 – 100	56 – 23		410.00
4BLOCKm 4/14	49M41414LA1	1.1	1.5	20 – 100	88 – 35		513.00
4BLOCKm 6/4	49M41604LA1	0.55	0.75	25 – 150	26 – 11	1¼"	384.00
4BLOCKm 6/6	49M41606LA1	0.75	1	25 – 150	38 – 17		406.00
4BLOCKm 6/9	49M41609LA1	1.1	1.5	25 – 150	58 – 26		494.00
4BLOCKm 8/4	49M41804LA1	0.75	1	40 – 200	26 – 7.5	1¼"	400.00
4BLOCKm 8/7	49M41807LA1	1.1	1.5	40 – 200	45 – 13		480.00

- Power cable: supplied with 20 metres long power cable
- Two mechanical seals separated by an oil chamber
- Capacitor and motor with built-in thermal overload protector
- Patent n. EP2300717 - EP2419642

4BLOCK: Ready to fit monoblock stainless steel submersible pumps. Supplied with capacitor and motor with built-in motor protector. Suitable for use in clear water wells with a maximum sand content of up to 150 g/m³).

For the version with a 30 metres long power supply cable apply a surcharge of

€ 32.00

4" SUBMERSIBLE PUMPS

SUBMERSIBLE PUMPS WITH PATENTED FLOATING IMPELLERS

4SR F PUMPS PAIRED WITH 4PD OR 4PS SUBMERSIBLE MOTORS



4SR1 F

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE €	
	Pump with motor 4PD	Pump with motor 4PS	P ₂ kW	HP	Q l/min	H m		Pump with motor 4PD	4PS
Single-phase							DN		
4SRm 1/12 F	49480012WLA1	49480012WNA1	0.37	0.50	5 – 30	71 – 30	1¼"	380.00	440.00
4SRm 1/17 F	49480017WLA1	49480017WNA1	0.55	0.75	5 – 30	100 – 42.5		421.00	500.00
4SRm 1/22 F	49480022WLA1	49480022WNA1	0.75	1	5 – 30	130 – 55		477.00	560.00
4SRm 1/32 F	49480032WLA1	49480032WNA1	1.1	1.5	5 – 30	188 – 80		570.00	670.00
4SRm 1/42 F	49480042WLA1	49480042WNA1	1.5	2	5 – 30	247 – 105		706.00	843.00
Three-phase									
4SR 1/12 F	49480012WLA	49480012WNA	0.37	0.50	5 – 30	71 – 30	1¼"	380.00	440.00
4SR 1/17 F	49480017WLA	49480017WNA	0.55	0.75	5 – 30	100 – 42.5		421.00	500.00
4SR 1/22 F	49480022WLA	49480022WNA	0.75	1	5 – 30	130 – 55		477.00	560.00
4SR 1/32 F	49480032WLA	49480032WNA	1.1	1.5	5 – 30	188 – 80		570.00	652.00
4SR 1/42 F	49480042WLA	49480042WNA	1.5	2	5 – 30	247 – 105		681.00	798.00

4SR1.5 F

Single-phase								4PD	4PS
4SRm 1.5/7 F	49480107WLA1	49480107WNA1	0.37	0.50	5 – 45	47 – 14.5	1¼"	355.00	415.00
4SRm 1.5/11 F	49480111WLA1	49480111WNA1	0.55	0.75	5 – 45	74 – 23		378.00	457.00
4SRm 1.5/15 F	49480115WLA1	49480115WNA1	0.75	1	5 – 45	101 – 31.5		422.00	505.00
4SRm 1.5/22 F	49480122WLA1	49480122WNA1	1.1	1.5	5 – 45	148 – 46		501.00	601.00
4SRm 1.5/30 F	49480130WLA1	49480130WNA1	1.5	2	5 – 45	202 – 63		588.00	725.00
4SRm 1.5/44 F	49480144WLA1	49480144WNA1	2.2	3	5 – 45	296 – 92		920.00	1,096.00
Three-phase									
4SR 1.5/7 F	49480107WLA	49480107WNA	0.37	0.50	5 – 45	47 – 14.5	1¼"	355.00	415.00
4SR 1.5/11 F	49480111WLA	49480111WNA	0.55	0.75	5 – 45	74 – 23		378.00	457.00
4SR 1.5/15 F	49480115WLA	49480115WNA	0.75	1	5 – 45	101 – 31.5		422.00	505.00
4SR 1.5/22 F	49480122WLA	49480122WNA	1.1	1.5	5 – 45	148 – 46		501.00	583.00
4SR 1.5/30 F	49480130WLA	49480130WNA	1.5	2	5 – 45	202 – 63		563.00	680.00
4SR 1.5/44 F	49480144WLA	49480144WNA	2.2	3	5 – 45	296 – 92		880.00	1,035.00

4SR2 F

Single-phase								4PD	4PS
4SRm 2/6 F	49480206WLA1	49480206WNA1	0.37	0.50	10 – 65	45 – 13	1¼"	355.00	415.00
4SRm 2/9 F	49480209WLA1	49480209WNA1	0.55	0.75	10 – 65	67 – 19.5		366.00	445.00
4SRm 2/12 F	49480212WLA1	49480212WNA1	0.75	1	10 – 65	90 – 25.7		390.00	473.00
4SRm 2/17 F	49480217WLA1	49480217WNA1	1.1	1.5	10 – 65	127 – 36.4		453.00	553.00
4SRm 2/23 F	49480223WLA1	49480223WNA1	1.5	2	10 – 65	172 – 49		531.00	668.00
4SRm 2/33 F	49480233WLA1	49480233WNA1	2.2	3	10 – 65	246 – 71		665.00	841.00
Three-phase									
4SR 2/6 F	49480206WLA	49480206WNA	0.37	0.50	10 – 65	45 – 13	1¼"	355.00	415.00
4SR 2/9 F	49480209WLA	49480209WNA	0.55	0.75	10 – 65	67 – 19.5		366.00	445.00
4SR 2/12 F	49480212WLA	49480212WNA	0.75	1	10 – 65	90 – 25.7		390.00	473.00
4SR 2/17 F	49480217WLA	49480217WNA	1.1	1.5	10 – 65	127 – 36.4		453.00	535.00
4SR 2/23 F	49480223WLA	49480223WNA	1.5	2	10 – 65	172 – 49		506.00	623.00
4SR 2/33 F	49480233WLA	49480233WNA	2.2	3	10 – 65	246 – 71		625.00	780.00

4PD = rewindable oil filled submersible motor

4PS = encapsulated water cooled submersible motor

● The pumps fitted with a single phase motor are supplied with the capacitor included in the price

- 2 m long power cable
- Patent n. EP2419642, EP14721501.6

4SR F: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

4" SUBMERSIBLE PUMPS

SUBMERSIBLE PUMPS WITH PATENTED FLOATING IMPELLERS

4SR F PUMPS PAIRED WITH 4PD OR 4PS SUBMERSIBLE MOTORS

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE €	
	Pump with motor 4PD	Pump with motor 4PS	P ₂		Q	H		Pump with motor	
			kW	HP				4PD	4PS
Single-phase					l/min	m	DN		
4SRm 4/6 F	49480406WLA1	49480406WNA1	0.55	0.75	20 – 100	45.5 – 17	2"	356.00	435.00
4SRm 4/8 F	49480408WLA1	49480408WNA1	0.75	1	20 – 100	60.5 – 22.5		377.00	460.00
4SRm 4/12 F	49480412WLA1	49480412WNA1	1.1	1.5	20 – 100	91 – 33.5		416.00	516.00
4SRm 4/15 F	49480415WLA1	49480415WNA1	1.5	2	20 – 100	114 – 42		483.00	620.00
4SRm 4/22 F	49480422WLA1	49480422WNA1	2.2	3	20 – 100	167 – 61.5		590.00	766.00
4SR4 F									
Three-phase									
4SR 4/6 F	49480406WLA	49480406WNA	0.55	0.75	20 – 100	45.5 – 17	2"	356.00	435.00
4SR 4/8 F	49480408WLA	49480408WNA	0.75	1	20 – 100	60.5 – 22.5		377.00	460.00
4SR 4/12 F	49480412WLA	49480412WNA	1.1	1.5	20 – 100	91 – 33.5		416.00	498.00
4SR 4/15 F	49480415WLA	49480415WNA	1.5	2	20 – 100	114 – 42		458.00	575.00
4SR 4/22 F	49480422WLA	49480422WNA	2.2	3	20 – 100	167 – 61.5		550.00	705.00
4SR 4/30 F	49480430WLA	49480430WNA	3	4	20 – 100	228 – 84		711.00	943.00
4SR 4/40 F	49480440WLA	49480440WNA	4	5.5	20 – 100	304 – 112		1,088.00	1,275.00
4SR 4/54 F	49480454WLA	49480454WNA	5.5	7.5	20 – 100	410 – 151		1,308.00	1,510.00
Single-phase								4PD	4PS
4SRm 6/4 F	49480604WLA1	49480604WNA1	0.55	0.75	25 – 150	25.5 – 9.5	2"	351.00	430.00
4SRm 6/6 F	49480606WLA1	49480606WNA1	0.75	1	25 – 150	38 – 14.5		367.00	450.00
4SRm 6/9 F	49480609WLA1	49480609WNA1	1.1	1.5	25 – 150	57 – 21.5		395.00	495.00
4SRm 6/13 F	49480613WLA1	49480613WNA1	1.5	2	25 – 150	83 – 31.5		473.00	610.00
4SRm 6/17 F	49480617WLA1	49480617WNA1	2.2	3	25 – 150	108 – 41		570.00	746.00
4SR6 F									
Three-phase									
4SR 6/4 F	49480604WLA	49480604WNA	0.55	0.75	25 – 150	25.5 – 9.5	2"	351.00	430.00
4SR 6/6 F	49480606WLA	49480606WNA	0.75	1	25 – 150	38 – 14.5		367.00	450.00
4SR 6/9 F	49480609WLA	49480609WNA	1.1	1.5	25 – 150	57 – 21.5		395.00	477.00
4SR 6/13 F	49480613WLA	49480613WNA	1.5	2	25 – 150	83 – 31.5		448.00	565.00
4SR 6/17 F	49480617WLA	49480617WNA	2.2	3	25 – 150	108 – 41		530.00	685.00
4SR 6/24 F	49480624WLA	49480624WNA	3	4	25 – 150	152 – 58		676.00	908.00
4SR 6/32 F	49480632WLA	49480632WNA	4	5.5	25 – 150	203 – 77		894.00	1,081.00
4SR 6/43 F	49480643WLA	49480643WNA	5.5	7.5	25 – 150	273 – 104		1,123.00	1,325.00
4SR 6/58 F	49480658WLA	49480658WNA	7.5	10	25 – 150	368 – 140		1,454.00	1,820.00
Single-phase								4PD	4PS
4SRm 8/4 F	49480804WLA1	49480804WNA1	0.75	1	40 – 200	27 – 8	2"	362.00	445.00
4SRm 8/7 F	49480807WLA1	49480807WNA1	1.1	1.5	40 – 200	47 – 14.5		393.00	493.00
4SRm 8/9 F	49480809WLA1	49480809WNA1	1.5	2	40 – 200	60.5 – 18.5		435.00	572.00
4SRm 8/13 F	49480813WLA1	49480813WNA1	2.2	3	40 – 200	87 – 26.5		525.00	701.00
4SR8 F									
Three-phase									
4SR 8/4 F	49480804WLA	49480804WNA	0.75	1	40 – 200	27 – 8	2"	362.00	445.00
4SR 8/7 F	49480807WLA	49480807WNA	1.1	1.5	40 – 200	47 – 14.5		393.00	475.00
4SR 8/9 F	49480809WLA	49480809WNA	1.5	2	40 – 200	60.5 – 18.5		410.00	527.00
4SR 8/13 F	49480813WLA	49480813WNA	2.2	3	40 – 200	87 – 26.5		485.00	640.00
4SR 8/17 F	49480817WLA	49480817WNA	3	4	40 – 200	114 – 35		603.00	835.00
4SR 8/24 F	49480824WLA	49480824WNA	4	5.5	40 – 200	161 – 49		808.00	995.00
4SR 8/32 F	49480832WLA	49480832WNA	5.5	7.5	40 – 200	214 – 65.5		989.00	1,191.00
4SR 8/43 F	49480843WLA	49480843WNA	7.5	10	40 – 200	288 – 88		1,204.00	1,570.00

4PD = rewindable oil filled submersible motor

4PS = encapsulated water cooled submersible motor

● The pumps fitted with a single phase motor are supplied with the capacitor included in the price

- Power cable: 2 m for power from 0.55 to 2.2 kW, 3.6 m for power from 3 to 7.5 kW
- Patent n. EP2419642, EP14721501.6

4SR F: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

4" SUBMERSIBLE PUMPS

4SR N PUMPS PAIRED WITH 4PD OR 4PS SUBMERSIBLE MOTORS

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE	
	Pump with motor 4PD	Pump with motor 4PS	P ₂ kW	HP	Q l/min	H m		Pump with motor 4PD	4PS
Single-phase									
4SRm 10/4 N	49481004WLA1	49481004WNA1	0.75	1	50 – 250	24 – 5	2"	392.00	475.00
4SRm 10/6 N	49481006WLA1	49481006WNA1	1.1	1.5	50 – 250	36 – 7.5		423.00	523.00
4SRm 10/8 N	49481008WLA1	49481008WNA1	1.5	2	50 – 250	48 – 10		488.00	625.00
4SRm 10/12 N	49481012WLA1	49481012WNA1	2.2	3	50 – 250	71 – 15		600.00	776.00

4SR10 N

Three-phase									
4SR 10/4 N	49481004WLA	49481004WNA	0.75	1	50 – 250	24 – 5	2"	392.00	475.00
4SR 10/6 N	49481006WLA	49481006WNA	1.1	1.5	50 – 250	36 – 7.5		423.00	505.00
4SR 10/8 N	49481008WLA	49481008WNA	1.5	2	50 – 250	48 – 10		463.00	580.00
4SR 10/12 N	49481012WLA	49481012WNA	2.2	3	50 – 250	71 – 15		560.00	715.00
4SR 10/17 N	49481017WLA	49481017WNA	3	4	50 – 250	101 – 21.3		721.00	953.00
4SR 10/23 N	49481023WLA	49481023WNA	4	5.5	50 – 250	137 – 29		978.00	1,165.00
4SR 10/31 N	49481031WLA	49481031WNA	5.5	7.5	50 – 250	185 – 39		1,193.00	1,395.00
4SR 10/42 N	49481042WLA	49481042WNA	7.5	10	50 – 250	251 – 52.5		1,404.00	1,770.00

4SR12 N

Single-phase								4PD	4PS
4SRm 12/5 N	49412N05WLA1	49412N05WNA1	0.75	1	50 – 300	24 – 5	2"	427.00	510.00
4SRm 12/7 N	49412N07WLA1	49412N07WNA1	1.1	1.5	50 – 300	33.5 – 7		498.00	598.00
4SRm 12/9 N	49412N09WLA1	49412N09WNA1	1.5	2	50 – 300	43 – 9		568.00	705.00
4SRm 12/14 N	49412N14WLA1	49412N14WNA1	2.2	3	50 – 300	67 – 14		730.00	906.00

Three-phase									
4SR 12/5 N	49412N05WLA	49412N05WNA	0.75	1	50 – 300	24 – 5	2"	427.00	510.00
4SR 12/7 N	49412N07WLA	49412N07WNA	1.1	1.5	50 – 300	33.5 – 7		498.00	580.00
4SR 12/9 N	49412N09WLA	49412N09WNA	1.5	2	50 – 300	43 – 9		543.00	660.00
4SR 12/14 N	49412N14WLA	49412N14WNA	2.2	3	50 – 300	67 – 14		690.00	845.00
4SR 12/19 N	49412N19WLA	49412N19WNA	3	4	50 – 300	91 – 19		891.00	1,123.00
4SR 12/25 N	49412N25WLA	49412N25WNA	4	5.5	50 – 300	120 – 25		1,193.00	1,380.00
4SR 12/34 N	49412N34WLA	49412N34WNA	5.5	7.5	50 – 300	163 – 34		1,478.00	1,680.00
4SR 12/41 N	49412N41WLA	49412N41WNA	7.5	10	50 – 300	197 – 41		1,694.00	2,060.00

4SR15 N

Single-phase								4PD	4PS
4SRm 15/6 N	49415N06WLA1	49415N06WNA1	1.1	1.5	50 – 340	30 – 3.5	2"	463.00	563.00
4SRm 15/8 N	49415N08WLA1	49415N08WNA1	1.5	2	50 – 340	40 – 5		553.00	690.00
4SRm 15/12 N	49415N12WLA1	49415N12WNA1	2.2	3	50 – 340	60 – 7		685.00	861.00

Three-phase									
4SR 15/6 N	49415N06WLA	49415N06WNA	1.1	1.5	50 – 340	30 – 3.5	2"	463.00	545.00
4SR 15/8 N	49415N08WLA	49415N08WNA	1.5	2	50 – 340	40 – 5		528.00	645.00
4SR 15/12 N	49415N12WLA	49415N12WNA	2.2	3	50 – 340	60 – 7		645.00	800.00
4SR 15/16 N	49415N16WLA	49415N16WNA	3	4	50 – 340	80 – 9.5		826.00	1,058.00
4SR 15/21 N	49415N21WLA	49415N21WNA	4	5.5	50 – 340	105 – 12.5		1,113.00	1,300.00
4SR 15/29 N	49415N29WLA	49415N29WNA	5.5	7.5	50 – 340	145 – 17.5		1,363.00	1,565.00
4SR 15/39 N	49415N39WLA	49415N39WNA	7.5	10	50 – 340	195 – 23.5		1,644.00	2,010.00

4PD = rewindable oil filled submersible motor

4PS = incapsulated water cooled submersible motor

● The pumps fitted with a single phase motor are supplied with the capacitor included in the price

- Power cable: 2 m for power from 0.75 to 2.2 kW, 3.6 m for power from 3 to 7.5 kW
- Patent n. EP2419642

4SR N: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

● MODELS COMPLYING WITH EU RULE N. 547/2012 WITH MINIMUM EFFICIENCY INDEX OF MEI≥0.40

4" SUBMERSIBLE PUMPS

4SR PUMPS PAIRED WITH 4PD OR 4PS SUBMERSIBLE MOTORS

4SR12

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE	
	Pump with motor 4PD	Pump with motor 4PS	P ₂ kW	HP	Q l/min	H m		Pump with motor 4PD	4PS
Single-phase							DN		
4SRm 12/4	4941204WLA1	4941204WNA1	1.1	1.5	50 – 300	24 – 8	2"	405.00	505.00
4SRm 12/6	4941206WLA1	4941206WNA1	1.5	2	50 – 300	37 – 14		458.00	595.00
4SRm 12/9	4941209WLA1	4941209WNA1	2.2	3	50 – 300	55 – 22		580.00	756.00
Three-phase									
4SR 12/4	4941204WLA	4941204WNA	1.1	1.5	50 – 300	24 – 8	2"	405.00	487.00
4SR 12/6	4941206WLA	4941206WNA	1.5	2	50 – 300	37 – 14		433.00	550.00
4SR 12/9	4941209WLA	4941209WNA	2.2	3	50 – 300	55 – 22		540.00	695.00
4SR 12/12	4941212WLA	4941212WNA	3	4	50 – 300	73 – 29		661.00	893.00
4SR 12/16	4941216WLA	4941216WNA	4	5.5	50 – 300	97 – 38		858.00	1,045.00
4SR 12/22	4941222WLA	4941222WNA	5.5	7.5	50 – 300	135 – 53		1,033.00	1,235.00
4SR 12/29	494L9229AX	494N9229A	7.5	10	50 – 300	176 – 71		1,254.00	1,620.00

4SR15

Single-phase								4PD	4PS
4SRm 15/5	4941505WLA1	4941505WNA1	1.5	2	50 – 375	30 – 7.5	2"	453.00	590.00
4SRm 15/7	4941507WLA1	4941507WNA1	2.2	3	50 – 375	42 – 10		530.00	706.00
Three-phase									
4SR 15/5	4941505WLA	4941505WNA	1.5	2	50 – 375	30 – 7.5	2"	428.00	545.00
4SR 15/7	4941507WLA	4941507WNA	2.2	3	50 – 375	42 – 10		490.00	645.00
4SR 15/10	4941510WLA	4941510WNA	3	4	50 – 375	60 – 15		641.00	873.00
4SR 15/13	4941513WLA	4941513WNA	4	5.5	50 – 375	77 – 19		808.00	995.00
4SR 15/18	4941518WLA	4941518WNA	5.5	7.5	50 – 375	108 – 27		993.00	1,195.00
4SR 15/24	494L9324AX	494N9324A	7.5	10	50 – 375	145 – 36		1,199.00	1,565.00

4PD = rewindable oil filled submersible motor

4PS = incapsulated water cooled submersible motor

● The pumps fitted with a single phase motor are supplied with the capacitor included in the price

- Power cable: 2 m for power from 1.1 to 2.2 kW, 3.6 m for power from 3 to 7.5 kW
- Patent n. EP2419642

4SR: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

● ● MODELS NOT SALEABLE INSIDE THE EUROPEAN UNION

4" SUBMERSIBLE PUMPS

SUBMERSIBLE PUMPS WITH PATENTED FLOATING IMPELLERS

4SR F - HYD 4" SUBMERSIBLE PUMPS



	MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
	Pump	Code	kW	HP	Q l/min	H m	DN	€
4SR1 F - HYD	4SR 1/12 F - HYD	49480012WI5	0.37	0.50	5 – 30	71 – 30	1¼"	200.00
	4SR 1/17 F - HYD	49480017WI5	0.55	0.75	5 – 30	100 – 42.5		240.00
	4SR 1/22 F - HYD	49480022WI5	0.75	1	5 – 30	130 – 55		285.00
	4SR 1/32 F - HYD	49480032WI5	1.1	1.5	5 – 30	188 – 80		362.00
	4SR 1/42 F - HYD	49480042WI5	1.5	2	5 – 30	247 – 105		468.00
4SR1.5 F - HYD	4SR 1.5/7 F - HYD	49480107WI5	0.37	0.50	5 – 45	47 – 14.5	1¼"	175.00
	4SR 1.5/11 F - HYD	49480111WI5	0.55	0.75	5 – 45	74 – 23		197.00
	4SR 1.5/15 F - HYD	49480115WI5	0.75	1	5 – 45	101 – 31.5		230.00
	4SR 1.5/22 F - HYD	49480122WI5	1.1	1.5	5 – 45	148 – 46		293.00
	4SR 1.5/30 F - HYD	49480130WI5	1.5	2	5 – 45	202 – 63		350.00
	4SR 1.5/44 F - HYD	49480144WI5	2.2	3	5 – 45	296 – 92		630.00
4SR2 F - HYD	4SR 2/6 F - HYD	49480206WI5	0.37	0.50	10 – 65	45 – 13	1¼"	175.00
	4SR 2/9 F - HYD	49480209WI5	0.55	0.75	10 – 65	67 – 19.5		185.00
	4SR 2/12 F - HYD	49480212WI5	0.75	1	10 – 65	90 – 25.7		198.00
	4SR 2/17 F - HYD	49480217WI5	1.1	1.5	10 – 65	127 – 36.4		245.00
	4SR 2/23 F - HYD	49480223WI5	1.5	2	10 – 65	172 – 49		293.00
	4SR 2/33 F - HYD	49480233WI5	2.2	3	10 – 65	246 – 71		375.00
4SR4 F - HYD	4SR 4/6 F - HYD	49480406WI5	0.55	0.75	20 – 100	45.5 – 17	1¼"	175.00
	4SR 4/8 F - HYD	49480408WI5	0.75	1	20 – 100	60.5 – 22.5		185.00
	4SR 4/12 F - HYD	49480412WI5	1.1	1.5	20 – 100	91 – 33.5		208.00
	4SR 4/15 F - HYD	49480415WI5	1.5	2	20 – 100	114 – 42		245.00
	4SR 4/22 F - HYD	49480422WI5	2.2	3	20 – 100	167 – 61.5		300.00
	4SR 4/30 F - HYD	49480430WI5	3	4	20 – 100	228 – 84		385.00
	4SR 4/40 F - HYD	49480440WI5	4	5.5	20 – 100	304 – 112		630.00
	4SR 4/54 F - HYD	49480454WI5	5.5	7.5	20 – 100	410 – 151		755.00
4SR6 F - HYD	4SR 6/4 F - HYD	49480604WI5	0.55	0.75	25 – 150	25.5 – 9.5	2"	170.00
	4SR 6/6 F - HYD	49480606WI5	0.75	1	25 – 150	38 – 14.5		175.00
	4SR 6/9 F - HYD	49480609WI5	1.1	1.5	25 – 150	57 – 21.5		187.00
	4SR 6/13 F - HYD	49480613WI5	1.5	2	25 – 150	83 – 31.5		235.00
	4SR 6/17 F - HYD	49480617WI5	2.2	3	25 – 150	108 – 41		280.00
	4SR 6/24 F - HYD	49480624WI5	3	4	25 – 150	152 – 58		350.00
	4SR 6/32 F - HYD	49480632WI5	4	5.5	25 – 150	203 – 77		436.00
	4SR 6/43 F - HYD	49480643WI5	5.5	7.5	25 – 150	273 – 104		570.00
	4SR 6/58 F - HYD	49480658WI5	7.5	10	25 – 150	368 – 140		820.00
4SR8 F - HYD	4SR 8/4 F - HYD	49480804WI5	0.75	1	40 – 200	27 – 8	2"	170.00
	4SR 8/7 F - HYD	49480807WI5	1.1	1.5	40 – 200	47 – 14.5		185.00
	4SR 8/9 F - HYD	49480809WI5	1.5	2	40 – 200	60.5 – 18.5		197.00
	4SR 8/13 F - HYD	49480813WI5	2.2	3	40 – 200	87 – 26.5		235.00
	4SR 8/17 F - HYD	49480817WI5	3	4	40 – 200	114 – 35		277.00
	4SR 8/24 F - HYD	49480824WI5	4	5.5	40 – 200	161 – 49		350.00
	4SR 8/32 F - HYD	49480832WI5	5.5	7.5	40 – 200	214 – 65.5		436.00
	4SR 8/43 F - HYD	49480843WI5	7.5	10	40 – 200	288 – 88		570.00

• Patent n. EP2419642, EP14721501.6

4SR F-HYD: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

4" SUBMERSIBLE PUMPS



4SR N - HYD 4" SUBMERSIBLE PUMPS

MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
Pump	Code	kW	HP	Q l/min	H m	DN	€
4SR10 N - HYD	4SR 10/4 N - HYD	0.75	1	50 – 250	24 – 5	2"	200.00
	4SR 10/6 N - HYD	1.1	1.5	50 – 250	36 – 7.5		215.00
	4SR 10/8 N - HYD	1.5	2	50 – 250	48 – 10		250.00
	4SR 10/12 N - HYD	2.2	3	50 – 250	71 – 15		310.00
	4SR 10/17 N - HYD	3	4	50 – 250	101 – 21.3		395.00
	4SR 10/23 N - HYD	4	5.5	50 – 250	137 – 29		520.00
	4SR 10/31 N - HYD	5.5	7.5	50 – 250	185 – 39		640.00
	4SR 10/42 N - HYD	7.5	10	50 – 250	251 – 52.5		770.00
4SR12 N - HYD	4SR 12/5 N - HYD	0.75	1	50 – 300	24 – 5	2"	235.00
	4SR 12/7 N - HYD	1.1	1.5	50 – 300	33.5 – 7		290.00
	4SR 12/9 N - HYD	1.5	2	50 – 300	43 – 9		330.00
	4SR 12/14 N - HYD	2.2	3	50 – 300	67 – 14		440.00
	4SR 12/19 N - HYD	3	4	50 – 300	91 – 19		565.00
	4SR 12/25 N - HYD	4	5.5	50 – 300	120 – 25		735.00
	4SR 12/34 N - HYD	5.5	7.5	50 – 300	163 – 34		925.00
	4SR 12/41 N - HYD	7.5	10	50 – 300	197 – 41		1,060.00
4SR15 N - HYD	4SR 15/6 N - HYD	1.1	1.5	50 – 340	30 – 3.5	2"	255.00
	4SR 15/8 N - HYD	1.5	2	50 – 340	40 – 5		315.00
	4SR 15/12 N - HYD	2.2	3	50 – 340	60 – 7		395.00
	4SR 15/16 N - HYD	3	4	50 – 340	80 – 9.5		500.00
	4SR 15/21 N - HYD	4	5.5	50 – 340	105 – 12.5		655.00
	4SR 15/29 N - HYD	5.5	7.5	50 – 340	145 – 17.5		810.00
	4SR 15/39 N - HYD	7.5	10	50 – 340	195 – 23.5		1,010.00

● MODELS COMPLYING WITH EU RULE N. 547/2012 WITH MINIMUM EFFICIENCY INDEX OF MEI≥0.40

4SR - HYD 4" SUBMERSIBLE PUMPS

MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
Pump	Code	kW	HP	Q l/min	H m	DN	€
4SR12 - HYD	4SR 12/4 - HYD	1.1	1.5	50 – 300	24 – 8	2"	197.00
	4SR 12/6 - HYD	1.5	2	50 – 300	37 – 14		220.00
	4SR 12/9 - HYD	2.2	3	50 – 300	55 – 22		290.00
	4SR 12/12 - HYD	3	4	50 – 300	73 – 29		335.00
	4SR 12/16 - HYD	4	5.5	50 – 300	97 – 38		400.00
	4SR 12/22 - HYD	5.5	7.5	50 – 300	135 – 53		480.00
	4SR 12/29 - HYD	7.5	10	50 – 300	176 – 71		620.00
4SR15 - HYD	4SR 15/5 - HYD	1.5	2	50 – 375	30 – 7.5	2"	215.00
	4SR 15/7 - HYD	2.2	3	50 – 375	42 – 10		240.00
	4SR 15/10 - HYD	3	4	50 – 375	60 – 15		315.00
	4SR 15/13 - HYD	4	5.5	50 – 375	77 – 19		350.00
	4SR 15/18 - HYD	5.5	7.5	50 – 375	108 – 27		440.00
	4SR 15/24 - HYD	7.5	10	50 – 375	145 – 36		565.00

• Patent n. EP2419642

4SR N-HYD e 4SR-HYD: suitable for pumping clean water with a maximum sand content of up to 150 g/m³

● ● MODELS NOT SALEABLE INSIDE THE EUROPEAN UNION

4" SUBMERSIBLE STAINLESS STEEL PUMPS

4HR PUMPS PAIRED WITH 4PD OR 4PS SUBMERSIBLE MOTORS

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE €	
	Pump with motor 4PD	Pump with motor 4PS	P ₂ kW	HP	Q l/min	H m		Pump with motor 4PD	4PS
Single-phase									
4HRm 10/5	494H1005WLA1	494H1005WNA1	0.75	1	50 – 250	25.5 – 7	2"	907.00	990.00
4HRm 10/7	494H1007WLA1	494H1007WNA1	1.1	1.5	50 – 250	36 – 10		1,083.00	1,183.00
4HRm 10/10	494H1010WLA1	494H1010WNA1	1.5	2	50 – 250	51.5 – 14		1,368.00	1,505.00
4HRm 10/15	494H1015WLA1	494H1015WNA1	2.2	3	50 – 250	77 – 21		1,930.00	2,106.00

4HR 10

Three-phase									
4HR 10/5	494H1005WLA	494H1005WNA	0.75	1	50 – 250	25.5 – 7	2"	907.00	990.00
4HR 10/7	494H1007WLA	494H1007WNA	1.1	1.5	50 – 250	36 – 10		1,083.00	1,165.00
4HR 10/10	494H1010WLA	494H1010WNA	1.5	2	50 – 250	51.5 – 14		1,343.00	1,460.00
4HR 10/15	494H1015WLA	494H1015WNA	2.2	3	50 – 250	77 – 21		1,890.00	2,045.00
4HR 10/20	494H1020WLA	494H1020WNA	3	4	50 – 250	103 – 28		2,476.00	2,708.00
4HR 10/28	494H1028WLA	494H1028WNA	4	5.5	50 – 250	144 – 39		3,258.00	3,445.00

Single-phase								4PD	4PS
4HRm 14/6	494H1406WLA1	494H1406WNA1	1.1	1.5	50 – 340	29.5 – 9	2"	923.00	1,023.00
4HRm 14/8	494H1408WLA1	494H1408WNA1	1.5	2	50 – 340	39.5 – 12		1,113.00	1,250.00
4HRm 14/12	494H1412WLA1	494H1412WNA1	2.2	3	50 – 340	59 – 18		1,500.00	1,676.00

4HR 14

Three-phase									
4HR 14/6	494H1406WLA	494H1406WNA	1.1	1.5	50 – 340	29.5 – 9	2"	923.00	1,005.00
4HR 14/8	494H1408WLA	494H1408WNA	1.5	2	50 – 340	39.5 – 12		1,088.00	1,205.00
4HR 14/12	494H1412WLA	494H1412WNA	2.2	3	50 – 340	59 – 18		1,460.00	1,615.00
4HR 14/16	494H1416WLA	494H1416WNA	3	4	50 – 340	79 – 23.5		1,886.00	2,118.00
4HR 14/21	494H1421WLA	494H1421WNA	4	5.5	50 – 340	104 – 31		2,438.00	2,625.00
4HR 14/29	494H1429WLA	494H1429WNA	5.5	7.5	50 – 340	143 – 43		3,193.00	3,395.00

Single-phase								4PD	4PS
4HRm 18/4	494H1804WLA1	494H1804WNA1	1.1	1.5	50 – 420	22 – 5	2"	748.00	848.00
4HRm 18/6	494H1806WLA1	494H1806WNA1	1.5	2	50 – 420	33.5 – 7		963.00	1,100.00
4HRm 18/9	494H1809WLA1	494H1809WNA1	2.2	3	50 – 420	50 – 11		1,250.00	1,426.00

4HR 18

Three-phase									
4HR 18/4	494H1804WLA	494H1804WNA	1.1	1.5	50 – 420	22 – 5	2"	748.00	830.00
4HR 18/6	494H1806WLA	494H1806WNA	1.5	2	50 – 420	33.5 – 7		938.00	1,055.00
4HR 18/9	494H1809WLA	494H1809WNA	2.2	3	50 – 420	50 – 11		1,210.00	1,365.00
4HR 18/12	494H1812WLA	494H1812WNA	3	4	50 – 420	66.5 – 14.5		1,546.00	1,778.00
4HR 18/16	494H1816WLA	494H1816WNA	4	5.5	50 – 420	89 – 19		2,028.00	2,215.00
4HR 18/22	494H1822WLA	494H1822WNA	5.5	7.5	50 – 420	122 – 26.5		2,613.00	2,815.00
4HR 18/30	494H1830WLA	494H1830WNA	7.5	10	50 – 420	167 – 36		3,354.00	3,720.00

4PD = rewindable oil filled submersible motor

4PS = incapsulated water cooled submersible motor

● The pumps fitted with a single phase motor are supplied with the capacitor included in the price

- Pumps entirely in AISI 304 cast stainless steel
- Power cable: 2 m for power from 0.75 to 2.2 kW, 3.6 m for power from 3 to 7.5 kW
- Registered EU Design n. 004128619

4HR: suitable for pumping clean water with a maximum sand content of up to 100 g/m³

4" SUBMERSIBLE STAINLESS STEEL PUMPS



4HR - HYD 4" SUBMERSIBLE PUMPS

	MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
	Pump	Code	kW	HP	Q l/min	H m	DN	€
4HR 10 - HYD	4HR 10/5 - HYD	494H1005WI5	0.75	1	50 – 250	25.5 – 7	2"	715.00
	4HR 10/7 - HYD	494H1007WI5	1.1	1.5	50 – 250	36 – 10		875.00
	4HR 10/10 - HYD	494H1010WI5	1.5	2	50 – 250	51.5 – 14		1,130.00
	4HR 10/15 - HYD	494H1015WI5	2.2	3	50 – 250	77 – 21		1,640.00
	4HR 10/20 - HYD	494H1020WI5	3	4	50 – 250	103 – 28		2,150.00
	4HR 10/28 - HYD	494H1028WI5	4	5.5	50 – 250	144 – 39		2,800.00

4HR 14 - HYD	4HR 14/6 - HYD	494H1406WI5	1.1	1.5	50 – 340	29.5 – 9	2"	715.00
	4HR 14/8 - HYD	494H1408WI5	1.5	2	50 – 340	39.5 – 12		875.00
	4HR 14/12 - HYD	494H1412WI5	2.2	3	50 – 340	59 – 18		1,210.00
	4HR 14/16 - HYD	494H1416WI5	3	4	50 – 340	79 – 23.5		1,560.00
	4HR 14/21 - HYD	494H1421WI5	4	5.5	50 – 340	104 – 31		1,980.00
	4HR 14/29 - HYD	494H1429WI5	5.5	7.5	50 – 340	143 – 43		2,640.00

4HR 18 - HYD	4HR 18/4 - HYD	494H1804WI5	1.1	1.5	50 – 420	22 – 5	2"	540.00
	4HR 18/6 - HYD	494H1806WI5	1.5	2	50 – 420	33.5 – 7		725.00
	4HR 18/9 - HYD	494H1809WI5	2.2	3	50 – 420	50 – 11		960.00
	4HR 18/12 - HYD	494H1812WI5	3	4	50 – 420	66.5 – 14.5		1,220.00
	4HR 18/16 - HYD	494H1816WI5	4	5.5	50 – 420	89 – 19		1,570.00
	4HR 18/22 - HYD	494H1822WI5	5.5	7.5	50 – 420	122 – 26.5		2,060.00
	4HR 18/30 - HYD	494H1830WI5	7.5	10	50 – 420	167 – 36		2,720.00

- Pumps entirely in AISI 304 cast stainless steel
- Registered EU Design n. 004128619

4HR-HYD: suitable for pumping clean water with a maximum sand content of up to 100 g/m³

6" SUBMERSIBLE PUMPS

6SR PUMPS PAIRED WITH 6PD OR 6PSR SUBMERSIBLE MOTORS

	MODEL	Code		POWER		PERFORMANCE		PORT	PRICE €	
		Pump with motor	Pump with motor	P ₂		Q	H		Pump with motor	
	Three-phase	6PD	6PSR	kW	HP	l/min	m		6PD	6PSR
6SR 12	6SR12/8	496B1208A	496B1208NA	4	5.5 ⁽¹⁾	50 – 330	106 – 32	3"	1,438.00	1,478.00
	6SR12/11	496B1211A	496B1211NA	5.5	7.5	50 – 330	146 – 44		1,513.00	1,533.00
	6SR12/15	496B1215A	496B1215NA	7.5	10	50 – 330	199 – 60		1,670.00	1,690.00
	6SR12/18	496B1218A	496B1218NA	9.2	12.5	50 – 330	239 – 72		1,784.00	1,799.00
	6SR12/21	496B1221A	496B1221NA	11	15	50 – 330	279 – 84		1,880.00	1,970.00
	6SR12/25	496B1225A	496B1225NA	13	17.5 ⁽²⁾	50 – 330	331 – 100		2,145.00	2,205.00
	6SR12/28	496B1228A	496B1228NA	15	20	50 – 330	371 – 112		2,200.00	2,260.00
6SR 18	6SR18/4	496B1804A	496B1804NA	4	5.5 ⁽¹⁾	50 – 450	53.8 – 22	3"	1,380.00	1,420.00
	6SR18/6	496B1806A	496B1806NA	5.5	7.5	50 – 450	80.5 – 32		1,438.00	1,458.00
	6SR18/9	496B1809A	496B1809NA	7.5	10	50 – 450	121 – 48		1,528.00	1,548.00
	6SR18/11	496B1811A	496B1811NA	9.2	12.5	50 – 450	148 – 59		1,624.00	1,639.00
	6SR18/13	496B1813A	496B1813NA	11	15	50 – 450	175 – 70		1,715.00	1,805.00
	6SR18/15	496B1815A	496B1815NA	13	17.5 ⁽²⁾	50 – 450	202 – 80		1,926.00	1,986.00
	6SR18/18	496B1818A	496B1818NA	15	20	50 – 450	242 – 96		1,984.00	2,044.00
	6SR18/22	496B1822A	496B1822NA	18.5	25	50 – 450	296 – 118		2,294.00	2,314.00
	6SR18/26	496B1826A	496B1826NA	22	30	50 – 450	350 – 139		2,590.00	2,520.00
6SR 27	6SR27/4	496B2704A	496B2704NA	4	5.5 ⁽¹⁾	100 – 600	53 – 18	3"	1,380.00	1,420.00
	6SR27/5	496B2705A	496B2705NA	5.5	7.5	100 – 600	66 – 22		1,438.00	1,458.00
	6SR27/7	496B2707A	496B2707NA	7.5	10	100 – 600	92 – 31		1,510.00	1,530.00
	6SR27/8	496B2708A	496B2708NA	9.2	12.5	100 – 600	106 – 35		1,588.00	1,603.00
	6SR27/10	496B2710A	496B2710NA	11	15	100 – 600	132 – 44		1,644.00	1,734.00
	6SR27/12	496B2712A	496B2712NA	13	17.5 ⁽²⁾	100 – 600	159 – 53		1,895.00	1,955.00
	6SR27/14	496B2714A	496B2714NA	15	20	100 – 600	185 – 62		1,940.00	2,000.00
	6SR27/17	496B2717A	496B2717NA	18.5	25	100 – 600	224 – 75		2,200.00	2,220.00
	6SR27/20	496B2720A	496B2720NA	22	30	100 – 600	264 – 88		2,488.00	2,418.00
	6SR27/27	496B2727A	496B2727NA	30	40	100 – 600	356 – 119		2,890.00	2,840.00
6SR 36	6SR 36/4	496B3604A	496B3604NA	4	5.5 ⁽¹⁾	100 – 800	45 – 14	3"	1,880.00	1,920.00
	6SR 36/6	496B3606A	496B3606NA	5.5	7.5	100 – 800	67 – 20		2,050.00	2,070.00
	6SR 36/8	496B3608A	496B3608NA	7.5	10	100 – 800	89 – 27		2,240.00	2,260.00
	6SR 36/10	496B3610A	496B3610NA	9.2	12.5	100 – 800	111 – 34		2,450.00	2,465.00
	6SR 36/11	496B3611A	496B3611NA	11	15	100 – 800	123 – 37		2,550.00	2,640.00
	6SR 36/13	496B3613A	496B3613NA	13	17.5 ⁽²⁾	100 – 800	145 – 44		2,890.00	2,950.00
	6SR 36/15	496B3615A	496B3615NA	15	20	100 – 800	167 – 51		3,050.00	3,110.00
	6SR 36/19	496B3619A	496B3619NA	18.5	25	100 – 800	212 – 65		3,540.00	3,560.00
	6SR 36/23	496B3623A	496B3623NA	22	30	100 – 800	256 – 78		4,070.00	4,000.00
6SR 44	6SR 44/3	496B4403A	496B4403NA	4	5.5 ⁽¹⁾	200 – 1000	33 – 13	3"	1,810.00	1,850.00
	6SR 44/4	496B4404A	496B4404NA	5.5	7.5	200 – 1000	44 – 18		1,900.00	1,920.00
	6SR 44/5	496B4405A	496B4405NA	7.5	10	200 – 1000	54 – 22		2,020.00	2,040.00
	6SR 44/6	496B4406A	496B4406NA	9.2	12.5	200 – 1000	65 – 26		2,160.00	2,175.00
	6SR 44/8	496B4408A	496B4408NA	11	15	200 – 1000	87 – 35		2,320.00	2,410.00
	6SR 44/9	496B4409A	496B4409NA	13	17.5 ⁽²⁾	200 – 1000	98 – 39		2,580.00	2,640.00
	6SR 44/11	496B4411A	496B4411NA	15	20	200 – 1000	120 – 48		2,730.00	2,790.00
	6SR 44/13	496B4413A	496B4413NA	18.5	25	200 – 1000	141 – 57		3,090.00	3,110.00
	6SR 44/16	496B4416A	496B4416NA	22	30	200 – 1000	174 – 70		3,555.00	3,485.00
	6SR 44/21	496B4421A	496B4421NA	30	40	200 – 1000	228 – 92		4,140.00	4,090.00

⁽¹⁾ Only for pumps with a 6PSR motor: 7.5 HP motor

⁽²⁾ Pump fitted with a 20 HP motor

● 6PD = rewindable oil filled submersible motor

● 6PSR = rewindable water cooled submersible motor

• Power cable: 4 metres standard equipment

OPTIONS AVAILABLE ON REQUEST

• Pumps with dual voltage 400/690 V (star/delta) motor from 11 kW to 30 kW

6SR: suitable for pumping clean water with a maximum sand content of up to 100 g/m³

6" SUBMERSIBLE PUMPS

6SR - HYD 6" SUBMERSIBLE PUMPS



MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
		kW	HP	Q l/min	H m	DN	€
6SR 12 - HYD	Pumps	Code					
	6SR12/8 - HYD	49I6A1208A1	4	5.5	50 – 330	106 – 32	658.00
	6SR12/11 - HYD	49I6A1211A1	5.5	7.5	50 – 330	146 – 44	713.00
	6SR12/15 - HYD	49I6A1215A1	7.5	10	50 – 330	199 – 60	830.00
	6SR12/18 - HYD	49I6A1218A1	9.2	12.5	50 – 330	239 – 72	884.00
	6SR12/21 - HYD	49I6A1221A1	11	15	50 – 330	279 – 84	960.00
	6SR12/25 - HYD	49I6A1225A1	13	17.5	50 – 330	331 – 100	1,045.00
	6SR12/28 - HYD	49I6A1228A1	15	20	50 – 330	371 – 112	1,100.00
6SR 18 - HYD	6SR18/4 - HYD	49I6A1804A1	4	5.5	50 – 450	53.8 – 22	600.00
	6SR18/6 - HYD	49I6A1806A1	5.5	7.5	50 – 450	80.5 – 32	638.00
	6SR18/9 - HYD	49I6A1809A1	7.5	10	50 – 450	121 – 48	688.00
	6SR18/11 - HYD	49I6A1811A1	9.2	12.5	50 – 450	148 – 59	724.00
	6SR18/13 - HYD	49I6A1813A1	11	15	50 – 450	175 – 70	795.00
	6SR18/15 - HYD	49I6A1815A1	13	17.5	50 – 450	202 – 80	826.00
	6SR18/18 - HYD	49I6A1818A1	15	20	50 – 450	242 – 96	884.00
	6SR18/22 - HYD	49I6A1822A1	18.5	25	50 – 450	296 – 118	994.00
	6SR18/26 - HYD	49I6A1826A1	22	30	50 – 450	350 – 139	1,060.00
6SR 27 - HYD	6SR27/4 - HYD	49I6A2704A1	4	5.5	100 – 600	53 – 18	600.00
	6SR27/5 - HYD	49I6A2705A1	5.5	7.5	100 – 600	66 – 22	638.00
	6SR27/7 - HYD	49I6A2707A1	7.5	10	100 – 600	92 – 31	670.00
	6SR27/8 - HYD	49I6A2708A1	9.2	12.5	100 – 600	106 – 35	688.00
	6SR27/10 - HYD	49I6A2710A1	11	15	100 – 600	132 – 44	724.00
	6SR27/12 - HYD	49I6A2712A1	13	17.5	100 – 600	159 – 53	795.00
	6SR27/14 - HYD	49I6A2714A1	15	20	100 – 600	185 – 62	840.00
	6SR27/17 - HYD	49I6A2717A1	18.5	25	100 – 600	224 – 75	900.00
	6SR27/20 - HYD	49I6A2720A1	22	30	100 – 600	264 – 88	958.00
	6SR27/27 - HYD	49I6A2727A1	30	40	100 – 600	356 – 119	1,150.00
6SR 36 - HYD	6SR 36/4 - HYD	49I6A3604A	4	5.5	100 – 800	45 – 14	1,100.00
	6SR 36/6 - HYD	49I6A3606A	5.5	7.5	100 – 800	67 – 20	1,250.00
	6SR 36/8 - HYD	49I6A3608A	7.5	10	100 – 800	89 – 27	1,400.00
	6SR 36/10 - HYD	49I6A3610A	9.2	12.5	100 – 800	111 – 34	1,550.00
	6SR 36/11 - HYD	49I6A3611A	11	15	100 – 800	123 – 37	1,630.00
	6SR 36/13 - HYD	49I6A3613A	13	17.5	100 – 800	145 – 44	1,790.00
	6SR 36/15 - HYD	49I6A3615A	15	20	100 – 800	167 – 51	1,950.00
	6SR 36/19 - HYD	49I6A3619A	18.5	25	100 – 800	212 – 65	2,240.00
	6SR 36/23 - HYD	49I6A3623A	22	30	100 – 800	256 – 78	2,540.00
6SR 44 - HYD	6SR 44/3 - HYD	49I6A4403A	4	5.5	200 – 1000	33 – 13	1,030.00
	6SR 44/4 - HYD	49I6A4404A	5.5	7.5	200 – 1000	44 – 18	1,100.00
	6SR 44/5 - HYD	49I6A4405A	7.5	10	200 – 1000	54 – 22	1,180.00
	6SR 44/6 - HYD	49I6A4406A	9.2	12.5	200 – 1000	65 – 26	1,260.00
	6SR 44/8 - HYD	49I6A4408A	11	15	200 – 1000	87 – 35	1,400.00
	6SR 44/9 - HYD	49I6A4409A	13	17.5	200 – 1000	98 – 39	1,480.00
	6SR 44/11 - HYD	49I6A4411A	15	20	200 – 1000	120 – 48	1,630.00
	6SR 44/13 - HYD	49I6A4413A	18.5	25	200 – 1000	141 – 57	1,790.00
	6SR 44/16 - HYD	49I6A4416A	22	30	200 – 1000	174 – 70	2,025.00
	6SR 44/21 - HYD	49I6A4421A	30	40	200 – 1000	228 – 92	2,400.00

OPTIONS AVAILABLE ON REQUEST

• Pumps with double cable cover for coupling to dual voltage 400/690 V (star/delta) motors of 11 kW to 30 kW

+ 10%

6SR-HYD: suitable for pumping clean water with a maximum sand content of up to 100 g/m³

6HR PUMPS PAIRED WITH 6PD OR 6PSR SUBMERSIBLE MOTORS

MODEL	Code		POWER		PERFORMANCE		PORT	PRICE €	
	Pump with motor	Pump with motor	P ₂		Q	H		Pump with motor	
Three-phase	6PD	6PSR	kW	HP	l/min	m	DN	6PD	6PSR
6HR 34	6HR 34/3	496H3403WLA 496H3403WNA	4	5.5 ⁽¹⁾	100 – 800	40 – 19	3"	1,685.00	1,725.00
	6HR 34/4	496H3404WLA 496H3404WNA	5.5	7.5	100 – 800	53 – 25.5		1,860.00	1,880.00
	6HR 34/5	496H3405WLA 496H3405WNA	7.5	10	100 – 800	66.5 – 32		2,050.00	2,070.00
	6HR 34/6	496H3406WLA 496H3406WNA	9.2	12.5	100 – 800	80 – 38		2,260.00	2,275.00
	6HR 34/7	496H3407WLA 496H3407WNA	11	15	100 – 800	93 – 45		2,430.00	2,520.00
	6HR 34/8	496H3408WLA 496H3408WNA	11	15	100 – 800	106 – 51		2,580.00	2,670.00
	6HR 34/9	496H3409WLA 496H3409WNA	13	17.5 ⁽²⁾	100 – 800	120 – 58		2,900.00	2,960.00
	6HR 34/11	496H3411WLA 496H3411WNA	15	20	100 – 800	146 – 70		3,210.00	3,270.00
	6HR 34/13	496H3413WLA 496H3413WNA	18.5	25	100 – 800	173 – 83		3,700.00	3,720.00
	6HR 34/16	496H3416WLA 496H3416WNA	22	30	100 – 800	213 – 102		4,370.00	4,300.00
	6HR 34/19	496H3419WLA 496H3419WNA	26	35 ⁽³⁾	100 – 800	253 – 122		5,030.00	4,980.00
	6HR 34/22	496H3422WLA 496H3422WNA	30	40	100 – 800	293 – 141		5,480.00	5,430.00
	6HR 34/27	496H3427WLA 496H3427WNA	37	50	100 – 800	359 – 173		6,450.00	6,350.00
6HR 44	6HR 44/3	496H4403WLA 496H4403WNA	5.5	7.5	200 – 1000	38 – 17	3"	1,725.00	1,745.00
	6HR 44/4	496H4404WLA 496H4404WNA	7.5	10	200 – 1000	51 – 23		1,910.00	1,930.00
	6HR 44/5	496H4405WLA 496H4405WNA	7.5	10	200 – 1000	63.5 – 29		2,060.00	2,080.00
	6HR 44/6	496H4406WLA 496H4406WNA	9.2	12.5	200 – 1000	76 – 35		2,270.00	2,285.00
	6HR 44/7	496H4407WLA 496H4407WNA	11	15	200 – 1000	89 – 40.5		2,430.00	2,520.00
	6HR 44/9	496H4409WLA 496H4409WNA	13	17.5 ⁽²⁾	200 – 1000	114.5 – 52		2,900.00	2,960.00
	6HR 44/10	496H4410WLA 496H4410WNA	15	20	200 – 1000	127 – 58		3,040.00	3,100.00
	6HR 44/12	496H4412WLA 496H4412WNA	18.5	25	200 – 1000	152 – 70		3,530.00	3,550.00
	6HR 44/15	496H4415WLA 496H4415WNA	22	30	200 – 1000	191 – 87		4,200.00	4,130.00
	6HR 44/18	496H4418WLA 496H4418WNA	26	35 ⁽³⁾	200 – 1000	229 – 104		4,850.00	4,800.00
	6HR 44/20	496H4420WLA 496H4420WNA	30	40	200 – 1000	254 – 116		5,140.00	5,090.00
	6HR 44/25	496H4425WLA 496H4425WNA	37	50	200 – 1000	318 – 145		6,130.00	6,030.00
6HR 54	6HR 54/3	496H5403WLA 496H5403WNA	5.5	7.5	300 – 1200	34 – 16	3"	1,715.00	1,735.00
	6HR 54/4	496H5404WLA 496H5404WNA	7.5	10	300 – 1200	45.5 – 21		1,910.00	1,930.00
	6HR 54/5	496H5405WLA 496H5405WNA	9.2	12.5	300 – 1200	57 – 26.5		2,120.00	2,135.00
	6HR 54/6	496H5406WLA 496H5406WNA	11	15	300 – 1200	68.5 – 31.5		2,300.00	2,390.00
	6HR 54/8	496H5408WLA 496H5408WNA	13	17.5 ⁽²⁾	300 – 1200	91 – 42		2,770.00	2,830.00
	6HR 54/9	496H5409WLA 496H5409WNA	15	20	300 – 1200	103 – 47		2,910.00	2,970.00
	6HR 54/11	496H5411WLA 496H5411WNA	18.5	25	300 – 1200	125 – 58		3,430.00	3,450.00
	6HR 54/13	496H5413WLA 496H5413WNA	22	30	300 – 1200	148 – 68		3,950.00	3,880.00
	6HR 54/16	496H5416WLA 496H5416WNA	26	35 ⁽³⁾	300 – 1200	182 – 84		4,600.00	4,550.00
	6HR 54/18	496H5418WLA 496H5418WNA	30	40	300 – 1200	205 – 95		4,860.00	4,810.00
	6HR 54/22	496H5422WLA 496H5422WNA	37	50	300 – 1200	251 – 116		5,740.00	5,640.00
6HR 64	6HR 64/3	496H6403WLA 496H6403WNA	7.5	10	400 – 1500	33 – 15	3"	1,740.00	1,760.00
	6HR 64/4	496H6404WLA 496H6404WNA	9.2	12.5	400 – 1500	43.5 – 20		2,000.00	2,015.00
	6HR 64/5	496H6405WLA 496H6405WNA	11	15	400 – 1500	54.5 – 25		2,170.00	2,260.00
	6HR 64/6	496H6406WLA 496H6406WNA	13	17.5 ⁽²⁾	400 – 1500	65.5 – 30		2,500.00	2,560.00
	6HR 64/7	496H6407WLA 496H6407WNA	15	20	400 – 1500	76 – 35		2,630.00	2,690.00
	6HR 64/8	496H6408WLA 496H6408WNA	18.5	25	400 – 1500	87 – 40		2,980.00	3,000.00
	6HR 64/10	496H6410WLA 496H6410WNA	22	30	400 – 1500	109 – 50		3,490.00	3,420.00
	6HR 64/12	496H6412WLA 496H6412WNA	26	35 ⁽³⁾	400 – 1500	131 – 60		4,000.00	3,950.00
	6HR 64/14	496H6414WLA 496H6414WNA	30	40	400 – 1500	153 – 70		4,290.00	4,240.00
	6HR 64/17	496H6417WLA 496H6417WNA	37	50	400 – 1500	186 – 85		5,120.00	5,020.00

⁽¹⁾ Only for pumps with a 6PSR motor: 7.5 HP motor

⁽²⁾ Pump fitted with a 20 HP motor

⁽³⁾ Pump fitted with a 40 HP motor

● 6PD = rewindable oil filled submersible motor

● 6PSR = rewindable water cooled submersible motor

• Pumps entirely in AISI 304 cast stainless steel

• Power cable: 4 metres standard equipment

• Registered EU Design n. 004675106-0002

OPTIONS AVAILABLE ON REQUEST

• Pumps with dual voltage 400/690 V (star/delta) motor from 11 kW to 37 kW

6HR: suitable for pumping clean water with a maximum sand content of up to 100 g/m³

6" SUBMERSIBLE STAINLESS STEEL PUMPS

6HR - HYD 6" SUBMERSIBLE PUMPS

MODEL		P ₂ POWER REQUIRED		PERFORMANCE		PORT	PRICE
Pumps	Code	kW	HP	Q l/min	H m	DN	€
6HR 34 - HYD	6HR 34/3 - HYD	4	5.5	100 – 800	40 – 19	3"	905.00
	6HR 34/4 - HYD	5.5	7.5	100 – 800	53 – 25.5		1,060.00
	6HR 34/5 - HYD	7.5	10	100 – 800	66.5 – 32		1,210.00
	6HR 34/6 - HYD	9.2	12.5	100 – 800	80 – 38		1,360.00
	6HR 34/7 - HYD	11	15	100 – 800	93 – 45		1,510.00
	6HR 34/8 - HYD	11	15	100 – 800	106 – 51		1,660.00
	6HR 34/9 - HYD	13	17.5	100 – 800	120 – 58		1,800.00
	6HR 34/11 - HYD	15	20	100 – 800	146 – 70		2,110.00
	6HR 34/13 - HYD	18.5	25	100 – 800	173 – 83		2,400.00
	6HR 34/16 - HYD	22	30	100 – 800	213 – 102		2,840.00
	6HR 34/19 - HYD	26	35	100 – 800	253 – 122		3,290.00
	6HR 34/22 - HYD	30	40	100 – 800	293 – 141		3,740.00
	6HR 34/27 - HYD	37	50	100 – 800	359 – 173		4,470.00
6HR 44 - HYD	6HR 44/3 - HYD	5.5	7.5	200 – 1000	38 – 17	3"	925.00
	6HR 44/4 - HYD	7.5	10	200 – 1000	51 – 23		1,070.00
	6HR 44/5 - HYD	7.5	10	200 – 1000	63.5 – 29		1,220.00
	6HR 44/6 - HYD	9.2	12.5	200 – 1000	76 – 35		1,370.00
	6HR 44/7 - HYD	11	15	200 – 1000	89 – 40.5		1,510.00
	6HR 44/9 - HYD	13	17.5	200 – 1000	114.5 – 52		1,800.00
	6HR 44/10 - HYD	15	20	200 – 1000	127 – 58		1,940.00
	6HR 44/12 - HYD	18.5	25	200 – 1000	152 – 70		2,230.00
	6HR 44/15 - HYD	22	30	200 – 1000	191 – 87		2,670.00
	6HR 44/18 - HYD	26	35	200 – 1000	229 – 104		3,110.00
	6HR 44/20 - HYD	30	40	200 – 1000	254 – 116		3,400.00
	6HR 44/25 - HYD	37	50	200 – 1000	318 – 145		4,150.00
6HR 54 - HYD	6HR 54/3 - HYD	5.5	7.5	300 – 1200	34 – 16	3"	915.00
	6HR 54/4 - HYD	7.5	10	300 – 1200	45.5 – 21		1,070.00
	6HR 54/5 - HYD	9.2	12.5	300 – 1200	57 – 26.5		1,220.00
	6HR 54/6 - HYD	11	15	300 – 1200	68.5 – 31.5		1,380.00
	6HR 54/8 - HYD	13	17.5	300 – 1200	91 – 42		1,670.00
	6HR 54/9 - HYD	15	20	300 – 1200	103 – 47		1,810.00
	6HR 54/11 - HYD	18.5	25	300 – 1200	125 – 58		2,130.00
	6HR 54/13 - HYD	22	30	300 – 1200	148 – 68		2,420.00
	6HR 54/16 - HYD	26	35	300 – 1200	182 – 84		2,860.00
	6HR 54/18 - HYD	30	40	300 – 1200	205 – 95		3,120.00
	6HR 54/22 - HYD	37	50	300 – 1200	251 – 116		3,760.00
6HR 64 - HYD	6HR 64/3 - HYD	7.5	10	400 – 1500	33 – 15	3"	940.00
	6HR 64/4 - HYD	9.2	12.5	400 – 1500	43.5 – 20		1,100.00
	6HR 64/5 - HYD	11	15	400 – 1500	54.5 – 25		1,250.00
	6HR 64/6 - HYD	13	17.5	400 – 1500	65.5 – 30		1,400.00
	6HR 64/7 - HYD	15	20	400 – 1500	76 – 35		1,530.00
	6HR 64/8 - HYD	18.5	25	400 – 1500	87 – 40		1,680.00
	6HR 64/10 - HYD	22	30	400 – 1500	109 – 50		1,960.00
	6HR 64/12 - HYD	26	35	400 – 1500	131 – 60		2,260.00
	6HR 64/14 - HYD	30	40	400 – 1500	153 – 70		2,550.00
	6HR 64/17 - HYD	37	50	400 – 1500	186 – 85		3,140.00

- Pumps entirely in AISI 304 cast stainless steel
- Registered EU Design n. 004675106-0002

6HR-HYD: suitable for pumping clean water with a maximum sand content of up to 100 g/m³



4PD 4" SUBMERSIBLE MOTORS

MODEL		POWER P ₂		PRICE
Single-phase 230V / 50Hz	Code	kW	HP	€
4PDm / 0.50	4ZPC05A1	0.37	0.50	180.00
4PDm / 0.75	4ZPC07A1	0.55	0.75	181.00
4PDm / 1	4ZPC10A1	0.75	1	192.00
4PDm / 1.5	4ZPC15A1	1.1	1.5	208.00
4PDm / 2	4ZPC20A1	1.5	2	238.00
4PDm / 3	4ZPC30A1	2.2	3	290.00
Three-phase 400V / 50Hz				
4PD / 0.50	4ZPC05A	0.37	0.50	180.00
4PD / 0.75	4ZPC07A	0.55	0.75	181.00
4PD / 1	4ZPC10A	0.75	1	192.00
4PD / 1.5	4ZPC15A	1.1	1.5	208.00
4PD / 2	4ZPC20A	1.5	2	213.00
4PD / 3	4ZPC30A	2.2	3	250.00
4PD / 4	4ZPC40A	3	4	326.00
4PD / 5.5	4ZPC55A	4	5.5	458.00
4PD / 7.5	4ZPC75A	5.5	7.5	553.00
4PD / 10	4ZPC100A	7.5	10	634.00

- Rewindable submersible motors in a non-toxic oil bath (suitable for use in the foods sector)
- Motor sleeve: AISI 316 stainless steel
- Shaft: "DUPLEX" stainless steel
- Power cable: 2 m for power from 0.37 to 2.2 kW,
3.6 m for power from 3 to 7.5 kW

● The single phase motor is supplied with the capacitor included in the price



SACRIFICIAL ANODE FOR 4PD SUBMERSIBLE MOTORS

ANODO 4PD	ASS4PDA01	€ 51.00
-----------	-----------	---------

- The sacrificial anode is made of a special "cadmium free" zinc-aluminium alloy, suitable for contact with drinking water. It can be easily attached to the bottom of the 4PD motors to protect them from corrosion in the presence of stray currents or particularly aggressive water, greatly increasing the life of the motor components.

4PS 4" SUBMERSIBLE MOTORS

MODEL		POWER P ₂		PRICE
Single-phase 230V / 50Hz	Code	kW	HP	€
4PSm / 0.50	4ZPM05A1	0.37	0.50	240.00
4PSm / 0.75	4ZPM07A1	0.55	0.75	260.00
4PSm / 1	4ZPM10A1	0.75	1	275.00
4PSm / 1.5	4ZPM15A1	1.1	1.5	308.00
4PSm / 2	4ZPM20A1	1.5	2	375.00
4PSm / 3	4ZPM30A1	2.2	3	466.00
Three-phase 400V / 50Hz				
4PS / 0.50	4ZPM05A	0.37	0.50	240.00
4PS / 0.75	4ZPM07A	0.55	0.75	260.00
4PS / 1	4ZPM10A	0.75	1	275.00
4PS / 1.5	4ZPM15A	1.1	1.5	290.00
4PS / 2	4ZPM20A	1.5	2	330.00
4PS / 3	4ZPM30A	2.2	3	405.00
4PS / 4	4ZPM40A	3	4	558.00
4PS / 5.5	4ZPM55A	4	5.5	645.00
4PS / 7.5	4ZPM75A	5.5	7.5	755.00
4PS / 10	4ZPM910A	7.5	10	1,000.00

- Motor sleeve: AISI 316 stainless steel
- Shaft: "DUPLEX" stainless steel
- Submersible motors encapsulated in water
- Power cable: 2 m for power from 0.37 to 2.2 kW,
3.6 m for power from 3 to 7.5 kW

● The single phase motor is supplied with the capacitor included in the price




6PD 6" SUBMERSIBLE MOTORS

MODEL		POWER P ₂		PRICE
Three-phase 400V / 50Hz	Code	kW	HP	€
6PD / 5.5	6ZPC6055A	4	5.5	780.00
6PD / 7.5	6ZPC6075A	5.5	7.5	800.00
6PD / 10	6ZPC6100A	7.5	10	840.00
6PD / 12.5	6ZPC6125A	9.2	12.5	900.00
6PD / 15	6ZPC6150A	11	15	920.00
6PD / 20	6ZPC6200A	15	20	1,100.00
6PD / 25	6ZPC6250A	18.5	25	1,300.00
6PD / 30	6ZPC6300A	22	30	1,530.00
6PD / 40	6ZPC6400A	30	40	1,740.00
6PD / 50	6ZPC6500A	37	50	1,980.00

- Motor sleeve: AISI 316 stainless steel
- Shaft: "DUPLEX" stainless steel
- Rewindable submersible motors in a non-toxic oil bath (suitable for use in the foods sector)
- Power cable: 4 metres long

COOLING SLEEVES FOR 4" AND 6" SUBMERSIBLE PUMPS



Typical installation

COOLING SLEEVES FOR 4SR SUBMERSIBLE PUMPS

Pumps with 4PD submersible motors

MOTOR POWER (P ₂)		Code	SLEEVE LENGTH	PRICE €
kW	HP			
0.37	0.50	ASSKIT4SRCR1	535 mm	145.00
0.55	0.75			
0.75	1			
1.1	1.5	ASSKIT4SRCR2	650 mm	150.00
1.5	2			
2.2	3			
3	4	ASSKIT4SRCR3	820 mm	155.00
4	5.5			
5.5	7.5			
7.5	10	ASSKIT4SRCR4	1000 mm	170.00

Pumps with 4PS submersible motors

0.37	0.50	ASSKIT4SRCR1	535 mm	145.00
0.55	0.75			
0.75	1			
1.1	1.5			
1.5	2			
2.2	3	ASSKIT4SRCR2	650 mm	150.00
3	4	ASSKIT4SRCR3	820 mm	155.00
4	5.5			
5.5	7.5	ASSKIT4SRCR4	1000 mm	170.00
7.5	10			

COOLING SLEEVES FOR 6SR SUBMERSIBLE PUMPS

MOTOR POWER (P ₂)		Code	SLEEVE LENGTH	PRICE €
kW	HP			
4	5.5	ASSKIT6SRCR1	995 mm	355.00
5.5	7.5			
7.5	10			
9.2	12.5			
11	15	ASSKIT6SRCR2	1155 mm	375.00
15	20			
18.5	25	ASSKIT6SRCR3	1505 mm	400.00
22	30			
30	40			
37	50			



UP-GE SUBMERSIBLE PUMPS WITH FLOAT SWITCH



MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
UPm 2/2-GE	48SP2110A1U	0.37	0.5	10 – 80	32 – 17	1 1/4"	362.00
UPm 2/3-GE	48SP2115A1U	0.55	0.75	10 – 80	46 – 23		372.00
UPm 2/4-GE	48SP2120A1U	0.75	1	10 – 80	61 – 31		382.00
UPm 2/5-GE	48SP2125A1U	1.1	1.5	10 – 80	79 – 40		405.00
UPm 2/6-GE	48SP2130A1U	1.5	2	10 – 80	93 – 48		426.00
UPm 4/3-GE	48SP2140A1U	0.55	0.75	20 – 120	39 – 12		372.00
UPm 4/4-GE	48SP2145A1U	0.75	1	20 – 120	52 – 16		382.00
UPm 4/5-GE	48SP2150A1U	1.1	1.5	20 – 120	65 – 20		405.00
UPm 4/6-GE	48SP2155A1U	1.5	2	20 – 120	78 – 24		426.00
UPm 8/3-GE	48SP2170A1U	1.1	1.5	40 – 180	39 – 9		405.00
UPm 8/4-GE	48SP2175A1U	1.5	2	40 – 180	51 – 12		426.00

● 10 m long power cable

(DRINCABLE® type approved for use in drinking water by "WRAS" in compliance with BS 6920, approval n. 7513)

UP SUBMERSIBLE PUMPS WITHOUT FLOAT SWITCH



MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
UPm 2/2	48SP0110A1U	0.37	0.5	10 – 80	32 – 17	1 1/4"	352.00
UPm 2/3	48SP0115A1U	0.55	0.75	10 – 80	46 – 23		362.00
UPm 2/4	48SP0120A1U	0.75	1	10 – 80	61 – 31		372.00
UPm 2/5	48SP0125A1U	1.1	1.5	10 – 80	79 – 40		395.00
UPm 2/6	48SP0130A1U	1.5	2	10 – 80	93 – 48		416.00
UPm 4/3	48SP0140A1U	0.55	0.75	20 – 120	39 – 12		362.00
UPm 4/4	48SP0145A1U	0.75	1	20 – 120	52 – 16		372.00
UPm 4/5	48SP0150A1U	1.1	1.5	20 – 120	65 – 20		395.00
UPm 4/6	48SP0155A1U	1.5	2	20 – 120	78 – 24		416.00
UPm 8/3	48SP0170A1U	1.1	1.5	40 – 180	39 – 9		395.00
UPm 8/4	48SP0175A1U	1.5	2	40 – 180	51 – 12		416.00

Three-phase

UP 2/2	48SP0110AU	0.37	0.5	10 – 80	32 – 17	1 1/4"	367.00
UP 2/3	48SP0115AU	0.55	0.75	10 – 80	46 – 23		377.00
UP 2/4	48SP0120AU	0.75	1	10 – 80	61 – 31		387.00
UP 2/5	48SP0125AU	1.1	1.5	10 – 80	79 – 40		405.00
UP 2/6	48SP0130AU	1.5	2	10 – 80	93 – 48		416.00
UP 4/3	48SP0140AU	0.55	0.75	20 – 120	39 – 12		377.00
UP 4/4	48SP0145AU	0.75	1	20 – 120	52 – 16		387.00
UP 4/5	48SP0150AU	1.1	1.5	20 – 120	65 – 20		405.00
UP 4/6	48SP0155AU	1.5	2	20 – 120	78 – 24		416.00
UP 8/3	48SP0170AU	1.1	1.5	40 – 180	39 – 9		405.00
UP 8/4	48SP0175AU	1.5	2	40 – 180	51 – 12		416.00

● 10 m long power cable

(DRINCABLE® type approved for use in drinking water by "WRAS" in compliance with BS 6920, approval n. 7513)

- Impellers: Noryl
- Two mechanical seals separated by an oil chamber
- Windings with built-in thermal overload protector
- Patent n. EP14755156.8
- Patent Pending n. BO2015A000116
- Patent n. EP2419642


● For the version with a 20 metres long power supply cable apply a surcharge of

€ 21.00



SUPPORT KIT FOR HORIZONTAL OPERATION

Code ASSKITUPFO2	€ 48.00
------------------	---------





NK-GE SUBMERSIBLE PUMPS WITH FLOAT SWITCH

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
NKm 2/2-GE	48SN2110A1U	0.37	0.5	10 – 80	32 – 17	1 1/4"	390.00
NKm 2/3-GE	48SN2115A1U	0.55	0.75	10 – 80	46 – 23		400.00
NKm 2/4-GE	48SN2120A1U	0.75	1	10 – 80	61 – 31		410.00
NKm 2/5-GE	48SN2125A1U	1.1	1.5	10 – 80	79 – 40		434.00
NKm 2/6-GE	48SN2130A1U	1.5	2	10 – 80	93 – 48		455.00
NKm 4/3-GE	48SN2140A1U	0.55	0.75	20 – 120	39 – 12		400.00
NKm 4/4-GE	48SN2145A1U	0.75	1	20 – 120	52 – 16		410.00
NKm 4/5-GE	48SN2150A1U	1.1	1.5	20 – 120	65 – 20		434.00
NKm 4/6-GE	48SN2155A1U	1.5	2	20 – 120	78 – 24		455.00
NKm 8/3-GE	48SN2170A1U	1.1	1.5	40 – 160	39 – 16		434.00
NKm 8/4-GE	48SN2175A1U	1.5	2	40 – 160	51 – 21		455.00

● 10 m long power cable

(DRINCABLE® type approved for use in drinking water by "WRAS" in compliance with BS 6920, approval n. 7513)



NK SUBMERSIBLE PUMPS WITHOUT FLOAT SWITCH

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
NKm 2/2	48SN0110A1U	0.37	0.5	10 – 80	32 – 17	1 1/4"	380.00
NKm 2/3	48SN0115A1U	0.55	0.75	10 – 80	46 – 23		390.00
NKm 2/4	48SN0120A1U	0.75	1	10 – 80	61 – 31		400.00
NKm 2/5	48SN0125A1U	1.1	1.5	10 – 80	79 – 40		424.00
NKm 2/6	48SN0130A1U	1.5	2	10 – 80	93 – 48		445.00
NKm 4/3	48SN0140A1U	0.55	0.75	20 – 120	39 – 12		390.00
NKm 4/4	48SN0145A1U	0.75	1	20 – 120	52 – 16		400.00
NKm 4/5	48SN0150A1U	1.1	1.5	20 – 120	65 – 20		424.00
NKm 4/6	48SN0155A1U	1.5	2	20 – 120	78 – 24		445.00
NKm 8/3	48SN0170A1U	1.1	1.5	40 – 160	39 – 16		424.00
NKm 8/4	48SN0175A1U	1.5	2	40 – 160	51 – 21		445.00

Three-phase

NK 2/2	48SN0110AU	0.37	0.5	10 – 80	32 – 17	1 1/4"	395.00
NK 2/3	48SN0115AU	0.55	0.75	10 – 80	46 – 23		405.00
NK 2/4	48SN0120AU	0.75	1	10 – 80	61 – 31		415.00
NK 2/5	48SN0125AU	1.1	1.5	10 – 80	79 – 40		434.00
NK 2/6	48SN0130AU	1.5	2	10 – 80	93 – 48		445.00
NK 4/3	48SN0140AU	0.55	0.75	20 – 120	39 – 12		405.00
NK 4/4	48SN0145AU	0.75	1	20 – 120	52 – 16		415.00
NK 4/5	48SN0150AU	1.1	1.5	20 – 120	65 – 20		434.00
NK 4/6	48SN0155AU	1.5	2	20 – 120	78 – 24		445.00
NK 8/3	48SN0170AU	1.1	1.5	40 – 160	39 – 16		434.00
NK 8/4	48SN0175AU	1.5	2	40 – 160	51 – 21		445.00

● 10 m long power cable

(DRINCABLE® type approved for use in drinking water by "WRAS" in compliance with BS 6920, approval n. 7513)

- Impellers: Noryl
- Two mechanical seals separated by an oil chamber
- Windings with built-in thermal overload protector
- Patent n. EP14755156.8
- Patent n. EP2313658

For the version with a 20 metres long power supply cable apply a surcharge of

€ 21.00



TOP MULTI MULTI-STAGE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
TOP MULTI 1	48TPM050A1U	0.37	0.50	10 – 70	25 – 5	1 1/4"	181.00
TOP MULTI 2	48TPM070A1U	0.55	0.75	10 – 80	40 – 5		252.00
TOP MULTI 3	48TPM170A1U	0.55	0.75	10 – 120	32 – 4		262.00

- Power cable: 10 metres standard equipment with Schuko plug
- Two mechanical seals separated by an oil chamber for TOP MULTI 2-3
- Impellers: Noryl
- External float switch standard issue
- Registered EU Design n. 000885587 for TOP MULTI 2-3
- TOP MULTI® Registered trade mark n. 0001334477

➔ for clean water



TOP MULTI-EVO MULTI-STAGE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN1	DN2	€
TOP MULTI 1-EVO	48TPM060A1U	0.37	0.50	10 – 70	25 – 5	1 1/4"	1 1/4"	195.00
TOP MULTI 2-EVO	48TPM080A1U	0.55	0.75	10 – 80	40 – 5			266.00
TOP MULTI 3-EVO	48TPM180A1U	0.55	0.75	10 – 120	32 – 4			276.00

- Power cable: 10 metres standard equipment with Schuko plug
- Two mechanical seals separated by an oil chamber for TOP MULTI 2-3 EVO
- Impellers: Noryl
- External float switch standard issue
- TOP MULTI® Registered trade mark n. 0001334477

➔ for clean water

VERSION WITHOUT MAGNETIC FLOAT SWITCH

TOP MULTI 1-EVO	€ 189.00	TOP MULTI 2-EVO	€ 260.00	TOP MULTI 3-EVO	€ 270.00
Code 48TPM06MA1U		Code 48TPM08MA1U		Code 48TPM18MA1U	

STANDARD EQUIPMENT

Ø 35 mm hosetail fitting



Pipe coupling threaded 1 1/4"
complete with flap-check valve




KGE - Floating suction kit for TOP MULTI-EVO

MODEL	Code	Fitting	PRICE €
KGE	ASSKITKGE	1 1/4"	55.00



- KGE floating suction kit includes: 1.5 metres long PVC hose (Ø 30 mm), stainless steel suction filter, polyethylene spherical float, flexible hose fittings Ø 30 mm.
- TOP MULTI-EVO with KGE kit for aspiration at about 10 cm below the water surface, preventing the suction of any floating waste or sediment on the bottom of the tank thus avoiding any damage to the pump.

Standard installation TOP MULTI-EVO



TOP MULTI®: Suitable for use in applications such as clean water supply from reservoirs, tanks or relatively deep wells, for drawing rain water from cisterns, to water gardens by hand or to supply water to irrigation systems, etc.



TOP MULTI-TECH AUTOMATIC MULTI-STAGE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
TOP MULTI-TECH 2	48TPMA070A1U	0.55	0.75	10 – 80	40 – 5	1 1/4"	320.00
TOP MULTI-TECH 3	48TPMA170A1U	0.55	0.75	10 – 120	32 – 4		330.00

- Power cable: 10 metres standard equipment with Schuko plug
- Two mechanical seals separated by an oil chamber
- Impellers: Noryl
- Incorporated non-return valve
- Patent n. EP2990653
- TOP MULTI® Registered trade mark n. 0001334477

⇒ for clean water



TOP MULTI-EVOTECH AUTOMATIC MULTI-STAGE PUMPS

MODEL		POWER P ₂		PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN1	DN2	€
TOP MULTI-EVOTECH 2	48TPMA080A1U	0.55	0.75	10 – 80	40 – 5	1 1/4"	1 1/4"	332.00
TOP MULTI-EVOTECH 3	48TPMA180A1U	0.55	0.75	10 – 120	32 – 4			342.00

- Power cable: 10 metres standard equipment with Schuko plug
- Two mechanical seals separated by an oil chamber
- Impellers: Noryl
- Incorporated non-return valve
- Patent n. EP2990653
- TOP MULTI® Registered trade mark n. 0001334477

⇒ for clean water

Spare electronic card (code 1145A001)

€ 49.00

STANDARD EQUIPMENT

Nipple 1 1/4"



Ø 35 mm hosetail fitting



1 SF




NT 1.25

1 SF - Tank - NT - 3 way fitting

MODEL	Code	FITTING	CAPACITY	PRE-SET	MAXIMUM WORKING PRESSURE	PRICE €
1 SF	500667	1/2" (male)	1 liter	1.2 bar	10 bar	33.00
NT 1.25	500160001	1 1/4" - 1 1/4" - 1/2" gas	–	–	–	6.00

Standard installation



To operate correctly avoiding frequent restarts and for greater energy saving it is necessary to install the 1 SF tank (or a similar tank with a minimum capacity of 1 litre) with an initial load of 1.2 bar

TOP MULTI-TECH pumps are fitted with an internal electronic device which starts the pump when the pressure of the system falls below 1.5 bar (eg. when opening a tap) and stops it when the flow falls below 3 litres per minute.

It protects the pump against dry running and against blockage: after long periods of inactivity the electronic device starts the pump every 48 hours for 10 seconds.



TOP DRAINAGE PUMPS FOR CLEAR WATER

MODEL		POWER P ₂		PERFORMANCE Q		PORT	HOSETAIL FITTING	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN	mm	€
TOP 1	48TOP11A1	0.25	0.33	20 – 160	6 – 1	1 1/4"	Ø 25	132.00
TOP 2	48TOP12A1	0.37	0.50	20 – 220	8 – 1		Ø 35	137.00
TOP 3	48TOP13A1	0.55	0.75	20 – 260	10 – 2		Ø 41	160.00
TOP 4	48TOP142A1U	0.75	1	20 – 320	12.5 – 3	1 1/2"	Ø 41	259.00
TOP 5	48TOP152A1U	0.92	1.25	20 – 360	15 – 2.5		Ø 41	269.00

- Power cable:
 - 5 metres standard equipment with Schuko plug
 - 10 metres standard equipment for TOP 4-5 with Schuko plug in single-phase versions
- Two mechanical seals separated by an oil chamber for TOP 4-5
- External float switch standard issue
- Shaft: AISI 431 stainless steel
- Patent Pending n. BO2015A000116
- Registered EU Design n. 342159-0011

VERSION WITH MAGNETIC FLOAT SWITCH (suitable for small drainage traps)

TOP 1 - GM	48TOP11A1SJR	0.25	0.33	20 – 160	6 – 1	1 1/4"	Ø 25	153.00
TOP 2 - GM	48TOP12A1SJR	0.37	0.50	20 – 220	8 – 1		Ø 35	158.00
TOP 3 - GM	48TOP13A1SJR	0.55	0.75	20 – 260	10 – 2		Ø 41	181.00
TOP 4 - GM	48TOP142A1USJR	0.75	1	20 – 320	12.5 – 3	1 1/2"	Ø 41	280.00
TOP 5 - GM	48TOP152A1USJR	0.92	1.25	20 – 360	15 – 2.5		Ø 41	290.00

- Power cable:
 - 5 metres standard equipment with Schuko plug
 - 10 metres standard equipment with Schuko plug for TOP 4-5 GM
- Liquid level vertical sliding magnetic float switch (adjustable)

VERSIONS SUITABLE FOR AGGRESSIVE LIQUIDS

TOP 2 - LA	48TOPX12A1U	0.37	0.50	20 – 220	8 – 1	1 1/4"	Ø 35	192.00
TOP 3 - LA	48TOPX13A1U	0.55	0.75	20 – 260	10 – 2		Ø 35	212.00

- Power cable: 10 metres standard equipment with Schuko plug

• TOP-LA version: metallic components in contact with the pumped liquid in AISI 316 stainless steel

TOP-FLOOR LOW SUCTION PUMPS FOR CLEAR WATER

MODEL		POWER P ₂		PERFORMANCE Q		PORT	HOSETAIL FITTING	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN	mm	€
TOP 1 - FLOOR	48TOPF11A1	0.25	0.33	20 – 120	6 – 1	1 1/4"	Ø 25	132.00
TOP 2 - FLOOR	48TOPF12A1	0.37	0.50	20 – 160	8 – 1		Ø 35	137.00

- Power cable: 5 metres standard equipment with Schuko plug
- Registered EU Design n. 342159-0011

• The pump is designed so as to guarantee suction down to 2 mm above ground level

VERSIONS SUITABLE FOR AGGRESSIVE LIQUIDS

TOP 1 - FLOOR/LA	48TOPFX11A1U	0.25	0.33	20 – 120	6 – 1	1 1/4"	Ø 25	186.00
TOP 2 - FLOOR/LA	48TOPFX12A1U	0.37	0.50	20 – 160	8 – 1		Ø 35	192.00

- Power cable: 10 metres standard equipment with Schuko plug

• TOP-FLOOR/LA version: metallic components in contact with the pumped liquid in AISI 316 stainless steel

For the model TOP FLOOR and TOP FLOOR-LA with an external float switch, add

€ 14.00

Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications

For the version with a 10 metres long power supply cable apply a surcharge of

€ 14.00



TOP-VORTEX PUMPS FOR DIRTY WATER

MODEL		POWER P ₂		PERFORMANCE Q		PORT	PASSAGE of solids mm	HOSETAIL FITTING mm	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN			€
TOP 2 - VORTEX	48TOPV12A1	0.37	0.50	20 – 180	6.5 – 1.5	1 1/4"	Ø 25	Ø 35	147.00
TOP 3 - VORTEX	48TOPV13A1	0.55	0.75	20 – 180	8 – 2.5				170.00

- Power cable: 5 metres standard equipment with Schuko plug
- External float switch standard issue
- Impeller: VORTEX in technopolymer
- Patent Pending n. BO2015A000116
- Registered EU Design n. 342159-0011



VERSION WITH MAGNETIC FLOAT SWITCH (suitable for small drainage traps)

TOP 2 - VORTEX / GM	48TOPV12A1SJR	0.37	0.50	20 – 180	6.5 – 1.5	1 1/4"	Ø 25	Ø 35	168.00
TOP 3 - VORTEX / GM	48TOPV13A1SJR	0.55	0.75	20 – 180	8 – 2.5				190.00

- Power cable: 5 metres standard equipment with Schuko plug
- Liquid level vertical sliding magnetic float switch (adjustable)

ON REQUEST FOR THE TOP SERIES

1 1/4" threaded sleeve with an incorporated clapet valve | Code ASR5023118W |



€ 5.00




TEX VORTEX PUMPS FOR DIRTY WATERS

MODEL		POWER P ₂		PERFORMANCE Q		PORT	PASSAGE of solids mm	HOSETAIL FITTING mm	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN			€
TEX 2	48TEX02A1	0.37	0.50	20 – 200	7.5 – 1.5	1 1/4"	Ø 30	Ø 40	170.00
TEX 3	48TEX03A1	0.55	0.75	20 – 240	9.5 – 2				185.00

- Power cable: 5 metres standard equipment with Schuko plug
- Liquid level vertical sliding magnetic float switch (adjustable)
- Impeller: VORTEX in glass fibre reinforced technopolymer
- Hose fitting supplied as a standard
- Registered EU Design n. 005205556
- TEX® Registered European Trade Mark n° 017884160

Selector for automatic or manual operation



Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications

For the version with a 10 metres long power supply cable apply a surcharge of

€ 14.00

PLUG & DRAIN EMERGENCY KIT FOR PREVENTING FLOODS

Code ASSKPLUGDRAIN

COMPONENTS

PRICE €



SUBMERSIBLE TOP2-FLOOR PUMP

- Single-phase **230 V - 50 Hz**
- Windings with built-in thermal overload protector
- **10 metres** power cable fitted with Schuko plug
- External float switch
- **"FASTFIT 1.25"** rapid connection
- Performance:
 - H max= **9 m**
 - Q max= **160 l/min**
- Emptying level down to **2 mm** from the bottom



PVC HOSE

- **"FASTFIT 1.25"** rapid connection
- Length of tube **15 m**
- Diameter of tube **1 1/4"**



CRATE-FILTER

- Complete with a system for fixing the pump for a stable operation and an easy detachment for use of the pump without the crate-filter
- Complete with a lid so as to put away PLUG & DRAIN in order and have it always ready for use



362.00



PLUG & DRAIN

PLUG & DRAIN is the indispensable and practical emergency kit for tackling flooding in garages, cellars and basements with efficacy and speed.

Thanks to the versatile drainage pump and the 15 metres long PVC hose it is possible to swiftly drain the flooded area, if necessary using the plastic crate as a filter.

With **PLUG & DRAIN** you can completely drain the area affected by flooding: the pump can in fact suck up water down to a level of only 2 mm from the bottom.

With **PLUG & DRAIN** you have everything you require ready for use:

- pump with a ready-fitted connector, a 10 metres long power cable with Schuko plug and an external float switch;
- PVC hose with a rapid connector;
- crate-filter to prevent possible bulky residues blocking water drainage.



RX PUMPS FOR CLEAR WATER

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	€
RXm 1	48TXP11A1	0.25	0.33	20 – 160	6.5 – 1	1¼"	190.00
RXm 2	48TXP12A1	0.37	0.50	20 – 220	9.5 – 2		196.00
RXm 3	48TXP13A1	0.55	0.75	20 – 220	11.5 – 3		208.00
RXm 4	48TXP24A1U	0.75	1	20 – 260	15 – 4	1½"	540.00
RXm 5	48TXP25A1U	1.1	1.5	20 – 300	19.5 – 5		565.00

Three-phase		POWER P ₂		PERFORMANCE Q H		PORT	PRICE
RX 1	Code	kW	HP	l/min	m	DN	€
RX 1	48TXP11A	0.25	0.33	20 – 160	6.5 – 1	1¼"	205.00
RX 2	48TXP12A	0.37	0.50	20 – 220	9.5 – 2		211.00
RX 3	48TXP13A	0.55	0.75	20 – 220	11.5 – 3		223.00
RX 4	48TXP24AU	0.75	1	20 – 260	15 – 4	1½"	550.00
RX 5	48TXP25AU	1.1	1.5	20 – 300	19.5 – 5		565.00

VERSION WITH MAGNETIC FLOAT SWITCH (suitable for small drainage traps)

Single-phase		POWER P ₂		PERFORMANCE Q H		PORT	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	€
RXm 1 - GM	48TXPG11A1	0.25	0.33	20 – 160	6.5 – 1	1¼"	211.00
RXm 2 - GM	48TXPG12A1	0.37	0.50	20 – 220	9.5 – 2		217.00
RXm 3 - GM	48TXPG13A1	0.55	0.75	20 – 220	11.5 – 3		229.00
RXm 4 - GM	48TXPG24A1U	0.75	1	20 – 260	15 – 4	1½"	560.00
RXm 5 - GM	48TXPG25A1U	1.1	1.5	20 – 300	19.5 – 5		585.00

- Liquid level vertical sliding magnetic float switch (adjustable)

RX-VORTEX PUMPS FOR DIRTY WATERS

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	mm	€
RXm 2/20	48TXV12A1	0.37	0.50	20 – 180	6.5 – 2	1¼"	Ø 20	203.00
RXm 3/20	48TXV13A1	0.55	0.75	20 – 180	8 – 3			219.00
RXm 4/40	48TXV24A1U	0.75	1	20 – 280	9.5 – 2	1½"	Ø 40	560.00
RXm 5/40	48TXV25A1U	1.1	1.5	20 – 380	12.5 – 2			580.00

Three-phase		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
RX 2/20	Code	kW	HP	l/min	m	DN	mm	€
RX 2/20	48TXV12A	0.37	0.50	20 – 180	6.5 – 2	1¼"	Ø 20	217.00
RX 3/20	48TXV13A	0.55	0.75	20 – 180	8 – 3			234.00
RX 4/40	48TXV24AU	0.75	1	20 – 280	9.5 – 2	1½"	Ø 40	570.00
RX 5/40	48TXV25AU	1.1	1.5	20 – 380	12.5 – 2			580.00

VERSION WITH MAGNETIC FLOAT SWITCH (suitable for small drainage traps)

Single-phase		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	mm	€
RXm 2/20 - GM	48TXV12A1	0.37	0.50	20 – 180	6.5 – 2	1¼"	Ø 20	223.00
RXm 3/20 - GM	48TXV13A1	0.55	0.75	20 – 180	8 – 3			239.00
RXm 4/40 - GM	48TXV24A1U	0.75	1	20 – 280	9.5 – 2	1½"	Ø 40	580.00
RXm 5/40 - GM	48TXV25A1U	1.1	1.5	20 – 380	12.5 – 2			600.00

- Liquid level vertical sliding magnetic float switch (adjustable)

- Power cable:
 - 5 metres standard equipment with Schuko plug in single-phase versions
 - 10 metres standard equipment for RX 4-5, RX 4-5/40, with Schuko plug in single-phase versions
- Two mechanical seals separated by an oil chamber for RX 4-5, RX 4-5/40
- Impeller: AISI 304 stainless steel – Shaft: AISI 431 stainless steel (RX4-5)
- Patent n. EP2313658 – Patent Pending n. BO2015A000116 (RX 1-2-3)

ON REQUEST FOR THE RX SERIES

1¼" threaded sleeve with an incorporated clapet valve | Code ASR5023218W |



€ 7.00

Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications

For the version with a 10 metres long power supply cable apply a surcharge of

€ 14.00



VX-ST SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
VXm 8/35 - ST	48SGV96A0A1U	0.55	0.75	50 – 350	8.5 – 1	1½"	Ø 40	335.00
VXm 10/35 - ST	48SGV96B0A1U	0.75	1	50 – 400	10.5 – 2			345.00
VXm 15/35 - ST	48SGV96C0A1U	1.1	1.5	50 – 500	14 – 2			390.00
VXm 8/50 - ST	48SGV96D0A1U	0.55	0.75	50 – 450	7 – 1.5	2"	Ø 50	345.00
VXm 10/50 - ST	48SGV96E0A1U	0.75	1	50 – 550	9.5 – 1.5			355.00
VXm 15/50 - ST	48SGV96F0A1U	1.1	1.5	50 – 650	13 – 2			400.00

Three-phase

VX 8/35 - ST	48SGV96A0AU	0.55	0.75	50 – 350	8.5 – 1	1½"	Ø 40	350.00
VX 10/35 - ST	48SGV96B0AU	0.75	1	50 – 400	10.5 – 2			360.00
VX 15/35 - ST	48SGV96C0AU	1.1	1.5	50 – 500	14 – 2			390.00
VX 8/50 - ST	48SGV96D0AU	0.55	0.75	50 – 450	7 – 1.5	2"	Ø 50	360.00
VX 10/50 - ST	48SGV96E0AU	0.75	1	50 – 550	9.5 – 1.5			370.00
VX 15/50 - ST	48SGV96F0AU	1.1	1.5	50 – 650	13 – 2			400.00

• Impeller: VORTEX AISI 304 stainless steel

● Shaft in AISI 316L stainless steel available on request

+ 8%



BC-ST SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
BCm 10/50-ST	48SGM88A0A1U	0.75	1	50 – 600	11 – 2	2"	Ø 50	390.00
BCm 15/50-ST	48SGM88B0A1U	1.1	1.5	50 – 750	14 – 2			425.00
Three-phase								
BC 10/50-ST	48SGM88A0AU	0.75	1	50 – 600	11 – 2	2"	Ø 50	405.00
BC 15/50-ST	48SGM88B0AU	1.1	1.5	50 – 750	14 – 2			425.00

• Impeller: DOUBLE-CHANNEL precision cast AISI 304 stainless steel

● Shaft in AISI 316L stainless steel available on request

+ 8%

- Pump body: AISI 304 pressed stainless steel
- Power cable: 10 metres standard equipment with Schuko plug in single-phase versions
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

SEWAGE LIFTING SYSTEM

HORIZONTAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For VX /35-ST	Code ASSPVX35ST	DN 2"	€ 75.00
For VX /50-ST, BC /50-ST	Code ASSPVX50ST	DN 2"	€ 80.00

- Kit consisting of:
 - footing connection
 - slide guide with ring nut and seal
 - support for the guide tubes

VERTICAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For VX /35-ST	Code ASSPVX35STV	DN 2½"	€ 135.00
For VX /50-ST, BC /50-ST	Code ASSPVX50STV	DN 2½"	€ 140.00

- Kit consisting of:
 - footing connection complete with counterflange
 - slide guide with ring nut and seal
 - support for the guide tubes

SLIDE GUIDE (also to be ordered separately)

For VX /35-ST	Code ASSFL005	€ 27.00
For VX /50-ST, BC /50-ST	Code ASSFL006	€ 32.00

- Complete with ring nut and seal


INTERMEDIATE SUPPORT (on request)

For guide tubes Ø ¾"	Code 859SV340INTFA	€ 98.00
----------------------	--------------------	----------------

GUIDE TUBES (AISI 304 stainless steel)


Guide tube Ø ¾"	Code 54SARTG005	€ 20.00 per metre
-----------------	-----------------	--------------------------

- In order to ensure stability, insert the intermediate support every 2 metres
- Maximum length of the tube plank: 6 metres



- 1 - Footing connection
 2 - Slide guide
 (also to be ordered separately)
 3 - Intermediate support
 (on request)
 4 - Support for the guide tubes

STANDARD INSTALLATION





VX-MF SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
VXm 8/35 - MF	48SGV92A0A1U	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	525.00
VXm 10/35 - MF	48SGV92B0A1U	0.75	1	50 – 400	10 – 2			535.00
VXm 15/35 - MF	48SGV92C0A1U	1.1	1.5	50 – 500	13.5 – 2			580.00
VXm 8/50 - MF	48SGV92D0A1U	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	530.00
VXm 10/50 - MF	48SGV92E0A1U	0.75	1	50 – 550	8.5 – 1.5			540.00
VXm 15/50 - MF	48SGV92F0A1U	1.1	1.5	50 – 650	11 – 2			585.00

Three-phase

VX 8/35 - MF	48SGV92A0AU	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	540.00
VX 10/35 - MF	48SGV92B0AU	0.75	1	50 – 400	10 – 2			550.00
VX 15/35 - MF	48SGV92C0AU	1.1	1.5	50 – 500	13.5 – 2			580.00
VX 8/50 - MF	48SGV92D0AU	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	545.00
VX 10/50 - MF	48SGV92E0AU	0.75	1	50 – 550	8.5 – 1.5			555.00
VX 15/50 - MF	48SGV92F0AU	1.1	1.5	50 – 650	11 – 2			585.00

- Impeller: VORTEX AISI 304 stainless steel



BC-MF SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
BCm 10/50-MF	48SGM85A0A1U	0.75	1	50 – 600	11 – 2	2"	Ø 50	580.00
BCm 15/50-MF	48SGM86A0A1U	1.1	1.5	50 – 750	14 – 2			625.00
Three-phase								
BC 10/50-MF	48SGM85A0AU	0.75	1	50 – 600	11 – 2	2"	Ø 50	595.00
BC 15/50-MF	48SGM86A0AU	1.1	1.5	50 – 750	14 – 2			625.00

- Impeller: DOUBLE-CHANNEL precision cast AISI 304 stainless steel

• Pump body: cast AISI 316L stainless steel

- Power cable: 10 metres standard equipment with Schuko plug in single-phase versions
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 316L stainless steel
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

SEWAGE LIFTING SYSTEM

HORIZONTAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For VX /35-MF	Code ASSPVX35ST	DN 2"	€ 75.00
For VX /50-MF, BC /50-MF	Code ASSPVX50ST	DN 2"	€ 80.00

- Kit consisting of:
 - footing connection;
 - slide guide with ring nut and seal;
 - support for the guide tubes.

VERTICAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For VX /35-MF	Code ASSPVX35STV	DN 2½"	€ 135.00
For VX /50-MF, BC /50-MF	Code ASSPVX50STV	DN 2½"	€ 140.00

- Kit consisting of:
 - footing connection complete with counterflange;
 - slide guide with ring nut and seal;
 - support for the guide tubes.

SLIDE GUIDE (also to be ordered separately)

For VX /35-MF	Code ASSFL005	€ 27.00
For VX /50-MF, BC /50-MF	Code ASSFL006	€ 32.00

- Complete with ring nut and seal


INTERMEDIATE SUPPORT (on request)

For guide tubes Ø ¾"	Code 859SV340INTFA	€ 98.00
----------------------	--------------------	----------------

GUIDE TUBES (AISI 304 stainless steel)

Guide tube Ø ¾"	Code 54SARTG005	€ 20.00 per metre
-----------------	-----------------	--------------------------

- In order to ensure stability, insert the intermediate support every 2 metres
- Maximum length of the tube plank: 6 metres



- 1 - Footing connection
- 2 - Slide guide
(also to be ordered separately)
- 3 - Intermediate support
(on request)
- 4 - Support for the guide tubes



STANDARD INSTALLATION



D PUMPS FOR CLEAR WATER

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	€
Dm 8	48SGD908A1	0.55	0.75	25 – 250	12.5 – 3	1½"	278.00
Dm 10	48SGD910A1	0.75	1	25 – 300	15.5 – 3		283.00
Dm 20	48SGD920A1	0.75	1	25 – 250	19 – 8		293.00
Dm 30	48SGD930A1U	1.1	1.5	25 – 275	26 – 9		335.00
Three-phase							
D 8	48SGD908A	0.55	0.75	25 – 250	12.5 – 3	1½"	293.00
D 10	48SGD910A	0.75	1	25 – 300	15.5 – 3		298.00
D 20	48SGD920A	0.75	1	25 – 250	19 – 8		308.00
D 30	48SGD930AU	1.1	1.5	25 – 275	26 – 9		335.00

- Power cable:
 - 5 metres standard equipment with Schuko plug in single-phase versions
 - 10 metres standard equipment for D30 with Schuko plug in single-phase versions
- Impeller: technopolymer
- Two mechanical seals separated by an oil chamber (For D30-N shaft with double mechanical seal with sealing ring)
- Shaft: AISI 431 stainless steel
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**



ZX2 SUBMERSIBLE "VORTEX" PUMPS FOR DIRTY WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
ZXm 2/30	48SDZX230A1	0.55	0.75	25 – 320	12.5 – 2	1½"	Ø 30	260.00
ZXm 2/40	48SDZX240A1	0.55	0.75	25 – 400	11 – 2		Ø 40	265.00

- Power cable: 5 metres standard equipment with Schuko plug
- Pump body in technopolymer
- Impeller: VORTEX in technopolymer
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- Hose fitting supplied as a standard
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**



VERSION WITH MAGNETIC FLOAT SWITCH (suitable for small drainage traps)

ZXm 2/30-GM	48SDZX230A1SJR	0.55	0.75	25 – 320	12.5 – 2	1½"	Ø 30	275.00
ZXm 2/40-GM	48SDZX240A1SJR	0.55	0.75	25 – 400	11 – 2		Ø 40	280.00

- Power cable: 5 metres standard equipment with Schuko plug
- Liquid level vertical sliding magnetic float switch (adjustable)
- Pump body in technopolymer
- Impeller: VORTEX in technopolymer
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- Hose fitting supplied as a standard

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**

Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications



ZX1 SUBMERSIBLE "VORTEX" PUMPS FOR DIRTY WATER

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	m	DN		€
ZXm 1B/40	48SDZE4BA1	0.50	0.70	25 – 350	8.5 – 1	1½"	Ø 40	260.00
ZXm 1A/40	48SDZE4AA1	0.60	0.85	25 – 400	10.5 – 1.5			265.00

- Power cable: 5 metres standard equipment with Schuko plug
- Impeller: VORTEX in technopolymer
- Hose fitting supplied as a standard

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**



VX SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	m	DN		€
VXm 8/35	48SGV90A0A1	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	290.00
VXm 10/35	48SGV91A0A1	0.75	1	50 – 400	10 – 2			295.00
VXm 15/35	48SGV91B0A1U	1.1	1.5	50 – 500	13.5 – 2			348.00
VXm 8/50	48SGV91C0A1	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	300.00
VXm 10/50	48SGV91D0A1	0.75	1	50 – 550	8.5 – 1.5			305.00
VXm 15/50	48SGV91E0A1U	1.1	1.5	50 – 650	11 – 2			358.00

Three-phase

VX 8/35	48SGV90A0A	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	305.00
VX 10/35	48SGV91A0A	0.75	1	50 – 400	10 – 2			310.00
VX 15/35	48SGV91B0AU	1.1	1.5	50 – 500	13.5 – 2			348.00
VX 8/50	48SGV91C0A	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	315.00
VX 10/50	48SGV91D0A	0.75	1	50 – 550	8.5 – 1.5			320.00
VX 15/50	48SGV91E0AU	1.1	1.5	50 – 650	11 – 2			358.00

- Power cable:
 - 5 metres standard equipment with Schuko plug in single-phase versions
 - 10 metres standard equipment for VX15/35, VX15/50 with Schuko plug in single-phase versions
- Impeller: VORTEX AISI 304 stainless steel – Shaft: AISI 431 stainless steel
- Two mechanical seals separated by an oil chamber
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**



BC SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	m	DN		€
BCm 10/50	48SGM81A0A1	0.75	1	50 – 600	11 – 2	2"	Ø 50	337.00
BCm 15/50	48SGM82A0A1U	1.1	1.5	50 – 750	14 – 2			383.00

Three-phase

BC 10/50	48SGM81A0A	0.75	1	50 – 600	11 – 2	2"	Ø 50	352.00
BC 15/50	48SGM82A0AU	1.1	1.5	50 – 750	14 – 2			383.00

- Power cable:
 - 5 metres standard equipment with Schuko plug in single-phase versions
 - 10 metres standard equipment for BC15/50 with Schuko plug in single-phase versions
- Impeller: DOUBLE-CHANNEL AISI 304 precision cast stainless steel – Shaft: AISI 431 stainless steel
- Two mechanical seals separated by an oil chamber
- Patent n. EP2313658 – Patent Pending n. BO2015A000116

● For the version with a 10 metres long power supply cable apply a surcharge of **€ 14.00**

Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications



VXC SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE Q		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN		€
VXCm 8/35	48SGV95A0A1U	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	335.00
VXCm 10/35	48SGV95B0A1U	0.75	1	50 – 400	10 – 2			345.00
VXCm 15/35	48SGV95C0A1U	1.1	1.5	50 – 500	13.5 – 2			380.00
VXCm 8/45	48SGV95D0A1U	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	345.00
VXCm 10/45	48SGV95E0A1U	0.75	1	50 – 550	8.5 – 1.5			355.00
VXCm 15/45	48SGV95F0A1U	1.1	1.5	50 – 650	11 – 2			400.00

Three-phase

VXC 8/35	48SGV95A0AU	0.55	0.75	50 – 350	8 – 1	1½"	Ø 40	350.00
VXC 10/35	48SGV95B0AU	0.75	1	50 – 400	10 – 2			360.00
VXC 15/35	48SGV95C0AU	1.1	1.5	50 – 500	13.5 – 2			380.00
VXC 8/45	48SGV95D0AU	0.55	0.75	50 – 450	6 – 1.5	2"	Ø 50	360.00
VXC 10/45	48SGV95E0AU	0.75	1	50 – 550	8.5 – 1.5			370.00
VXC 15/45	48SGV95F0AU	1.1	1.5	50 – 650	11 – 2			400.00

- Power cable: 10 metres standard equipment with Schuko plug in single-phase versions
- External float switch: standard issue on single-phase versions
- Impeller: VORTEX AISI 304 stainless steel – Shaft: AISI 431 stainless steel
- Two mechanical seals separated by an oil chamber
- Patent n. EP2313658 – Patent Pending n. BO2015A000116
- Registered EU Design n. 002501486-0003



MC SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE Q		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	l/min	H m	DN		€
MCm 10/45	48SGM91A0A1U	0.75	1	50 – 600	11 – 2	2"	Ø 50	395.00
MCm 15/45	48SGM92A0A1U	1.1	1.5	50 – 750	14 – 2			440.00

Three-phase

MC 10/45	48SGM91A0AU	0.75	1	50 – 600	11 – 2	2"	Ø 50	410.00
MC 15/45	48SGM92A0AU	1.1	1.5	50 – 750	14 – 2			440.00

- Power cable: 10 metres standard equipment with Schuko plug in single-phase versions
- External float switch: standard issue on single-phase versions
- Impeller: DOUBLE-CHANNEL AISI 304 precision cast stainless steel – Shaft: AISI 431 stainless steel
- Two mechanical seals separated by an oil chamber
- Patent n. EP2313658 – Patent Pending n. BO2015A000116
- Registered EU Design n. 002501486-0003

DC CAST IRON DRAINAGE PUMPS FOR CLEAR WATER



MODEL		POWER P ₂		PERFORMANCE Q H		PORT	PRICE
Single-phase	Code	kW	HP	l/min	m	DN	€
DCm 8	48SGDC908A1U	0.55	0.75	25 – 250	12.5 – 3	1½"	325.00
DCm 10	48SGDC910A1U	0.75	1	25 – 300	15.5 – 3		335.00
DCm 20	48SGDC920A1U	0.75	1	25 – 250	19 – 8		335.00
DCm 30	48SGDC930A1U	1.1	1.5	25 – 275	26 – 9		380.00
Three-phase							
DC 8	48SGDC908AU	0.55	0.75	25 – 250	12.5 – 3	1½"	340.00
DC 10	48SGDC910AU	0.75	1	25 – 300	15.5 – 3		350.00
DC 20	48SGDC920AU	0.75	1	25 – 250	19 – 8		350.00
DC 30	48SGDC930AU	1.1	1.5	25 – 275	26 – 9		380.00

- Power cable: 10 metres standard equipment with Schuko plug in single-phase versions
- External float switch: standard issue on single-phase versions
- Impeller: technopolymer
- Two mechanical seals separated by an oil chamber
(For DC30 shaft with double mechanical seal with sealing ring)
- Shaft: AISI 431 stainless steel
- Patent n. EP2313658 – Patent Pending n. BO2015A000116
- Registered EU Design n. 002501486-0001

STANDARD INSTALLATION






TRITUS SUBMERSIBLE PUMPS WITH GRINDER							
MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
TRm 0.75	48SHT00A1	0.75	1	20 – 125	15 – 2	1¼"	700.00
TRm 0.9	48SHT04A1	0.9	1.25	20 – 170	15 – 2		710.00
TRm 1.1	48SHT01A1	1.1	1.5	20 – 140	21.5 – 2		735.00
TRm 1.3	48SHT05A1	1.3	1.75	20 – 220	22.5 – 2		745.00
Three-phase							
TR 0.75	48SHT00A	0.75	1	20 – 125	15 – 2	1¼"	660.00
TR 0.9	48SHT04A	0.9	1.25	20 – 170	15 – 2		680.00
TR 1.1	48SHT01A	1.1	1.5	20 – 140	21.5 – 2		690.00
TR 1.3	48SHT05A	1.3	1.75	20 – 220	22.5 – 2		705.00



MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
TRm 1.5	48SHT02A1	1.5	2	20 – 270	25 – 2	DN 40 (PN6) 1½"	1,170.00
Three-phase							
TR 1.5	48SHT02A	1.5	2	20 – 270	25 – 2	DN 40 (PN6)	1,040.00
TR 2.2	48SHT03A	2.2	3	20 – 280	30 – 2	1½"	1,150.00

- Flanged (DN40) and threaded (1½") delivery port

- High resistance tempered stainless steel grinder
- Power cable: 10 metres standard equipment
- Impeller:
 - technopolymer for TR 0.75, TR 0.9, TR 1.1, TR 1.3
 - precision cast AISI 304 stainless steel for TR 1.5, TR 2.2
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- Standard supply single-phase version:
 - control panel
 - windings with built-in thermal overload protector
 - external float switch
- Patent n. EP2313658 – Patent Pending n. BO2015A000116
- Registered EU Design n. 002501486-0002 (TR 0.75, TR 0.9, TR 1.1, TR 1.3)
- TRITUS® Registered trade mark n. 013017181



- 1 - Footing connection
- 2 - Slide guide
(also to be ordered separately)
- 3 - Intermediate support
(on request)
- 4 - Support for the guide tubes

SEWAGE LIFTING SYSTEM

HORIZONTAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For TR 0.75, TR 0.9 TR 1.1, TR 1.3	Code ASSPTRITUS11	DN 2"	€ 80.00
For TR 1.5, TR 2.2	Code ASSPTRITUS22		€ 80.00

- Kit consisting of:
 - footing connection;
 - slide guide with ring nut and seal (screws and seals for TR 1.5 and TR 2.2);
 - support for the guide tubes.

VERTICAL DELIVERY VERSION WITH ¾" GUIDE TUBES

For TR 0.75, TR 0.9 TR 1.1, TR 1.3	Code ASSPTRITUS11V	DN 2½"	€ 135.00
For TR 1.5, TR 2.2	Code ASSPTRITUS22V		€ 135.00

- Kit consisting of:
 - footing connection complete with counterflange;
 - slide guide with ring nut and seal (screws and seals for TR 1.5 and TR 2.2);
 - support for the guide tubes.

SLIDE GUIDE (also to be ordered separately)

For TR 0.75, TR 0.9, TR 1.1, TR 1.3	Code ASSFL003	€ 28.00
For TR 1.5, TR 2.2	Code ASSFL004	€ 28.00

- Complete with ring nut and seal (screws and seals for TR 1.5 and TR 2.2)

INTERMEDIATE SUPPORT (on request)


For guide tubes Ø ¾"	Code 859SV340INTFA	€ 98.00
----------------------	--------------------	---------

GUIDE TUBES (AISI 304 stainless steel)

Guide tube Ø ¾"	Code 54SARTG005	€ 20.00 per metre
-----------------	-----------------	-------------------

- In order to ensure stability, insert the intermediate support every 2 metres
- Maximum length of the tube plank: 6 metres

STANDARD INSTALLATION





VXC SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN		€
VXCm 15/50	48SGV93C0A1	1.1	1.5	100 – 600	10.5 – 2	2½"	Ø 50	720.00
VXCm 20/50	48SGV93B0A1	1.5	2	100 – 700	12 – 2			767.00
VXCm 30/50	48SGV93A0A1	2.2	3	100 – 850	15 – 2			1,275.00
VXCm 15/70	48SGV947CA1	1.1	1.5	200 – 850	5.5 – 1	3"	Ø 70	780.00
VXCm 20/70	48SGV947BA1	1.5	2	200 – 1000	7.4 – 1			825.00
VXCm 30/70	48SGV947AA1	2.2	3	200 – 1200	9.7 – 1.5			1,330.00
Three-phase								
VXC 15/50	48SGV93C0A	1.1	1.5	100 – 600	10.5 – 2	2½"	Ø 50	720.00
VXC 20/50	48SGV93B0A	1.5	2	100 – 700	12 – 2			740.00
VXC 30/50	48SGV93A0A	2.2	3	100 – 850	15 – 2			765.00
VXC 15/70	48SGV947CA	1.1	1.5	200 – 850	5.5 – 1	3"	Ø 70	780.00
VXC 20/70	48SGV947BA	1.5	2	200 – 1000	7.4 – 1			800.00
VXC 30/70	48SGV947AA	2.2	3	200 – 1200	9.7 – 1.5			820.00

- Power cable: 10 metres standard equipment
- Impeller: cast iron VORTEX
- Shaft: AISI 431 stainless steel

• **Standard supply single-phase version:**

- External float switch
- Control panel
- Capacitor (inside the control panel)
- Thermal overload protector build into the motor winding

● **2.2 kW single-phase pumps, the thermal overload protector must be connected to the external control panel**

• **Standard supply three-phase version:**

- **For three-phase water pumps three thermal overload protectors in series are built into the winding and these must be connected to the control box**

- Patent Pending n. BO2015A000116 – Registered EU Design n. 342159-0017



MC SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER								
MODEL		POWER		PERFORMANCE		PORT	PASSAGE of solids	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	mm	€
MCm 15/50	48SGM93C0A1	1.1	1.5	100 – 800	14 – 1	2½"	Ø 50	760.00
MCm 20/50	48SGM93B0A1	1.5	2	100 – 900	16 – 1			805.00
MCm 30/50	48SGM93A0A1	2.2	3	100 – 1100	22 – 2			1,320.00
MCm 30/70	48SGM947AA1	2.2	3	200 – 1500	12 – 2	3"	Ø 70	1,355.00
Three-phase								
MC 15/50	48SGM93C0A	1.1	1.5	100 – 800	14 – 1	2½"	Ø 50	760.00
MC 20/50	48SGM93B0A	1.5	2	100 – 900	16 – 1			780.00
MC 30/50	48SGM93A0A	2.2	3	100 – 1100	22 – 2			810.00
MC 40/50	48SGM94050A	3	4	100 – 1100	24 – 4			990.00
MC 30/70	48SGM947AA	2.2	3	200 – 1500	12 – 2	3"	Ø 70	860.00
MC 40/70	48SGM94070A	3	4	200 – 1600	15 – 4			1,075.00

- Power cable: 10 metres standard equipment
- Impeller: DOUBLE-CHANNEL AISI 304 precision cast stainless steel
- Shaft: AISI 431 stainless steel
- **Standard supply single-phase version:**
 - External float switch
 - Control panel
 - Capacitor (inside the control panel)
 - Thermal overload protector build into the motor winding
- **2.2 kW single-phase pumps, the thermal overload protector must be connected to the external control panel**
- **Standard supply three-phase version:**
 - **For three-phase water pumps three thermal overload protectors in series are built into the winding and these must be connected to the control box**
- Patent Pending n. BO2015A000116 – Registered EU Design n. 342159-0017

VXC-F SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PASSAGE of solids mm	PRICE
Single-phase	Code	kW	HP	Q l/min	H m		€
VXCm 15/50-F	48SGY93C0A1	1.1	1.5	100 – 600	10.5 – 2	Ø 50	760.00
VXCm 20/50-F	48SGY93B0A1	1.5	2	100 – 700	12 – 2		805.00
VXCm 30/50-F	48SGY93A0A1	2.2	3	100 – 850	15 – 2		1,320.00
VXCm 15/70-F	48SGY947CA1	1.1	1.5	200 – 850	5.5 – 1	Ø 70	825.00
VXCm 20/70-F	48SGY947BA1	1.5	2	200 – 1000	7.4 – 1		870.00
VXCm 30/70-F	48SGY947AA1	2.2	3	200 – 1200	9.7 – 1.5		1,350.00
Three-phase							
VXC 15/50-F	48SGY93C0A	1.1	1.5	100 – 600	10.5 – 2	Ø 50	760.00
VXC 20/50-F	48SGY93B0A	1.5	2	100 – 700	12 – 2		780.00
VXC 30/50-F	48SGY93A0A	2.2	3	100 – 850	15 – 2		810.00
VXC 15/70-F	48SGY947CA	1.1	1.5	200 – 850	5.5 – 1	Ø 70	825.00
VXC 20/70-F	48SGY947BA	1.5	2	200 – 1000	7.4 – 1		845.00
VXC 30/70-F	48SGY947AA	2.2	3	200 – 1200	9.7 – 1.5		860.00

- Power cable: 10 metres standard equipment
- Impeller: cast iron VORTEX
- Shaft: AISI 431 stainless steel

MC-F SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE Q		PASSAGE of solids mm	PRICE €
Single-phase	Code	kW	HP	l/min	H m		
MCm 15/50-F	48SGQ93C0A1	1.1	1.5	100 – 800	14 – 1	Ø 50	805.00
MCm 20/50-F	48SGQ93B0A1	1.5	2	100 – 900	16 – 1		850.00
MCm 30/50-F	48SGQ93A0A1	2.2	3	100 – 1100	22 – 2		1,360.00
MCm 30/70-F	48SGQ947AA1	2.2	3	200 – 1500	12 – 2	Ø 70	1,415.00
Three-phase							
MC 15/50-F	48SGQ93C0A	1.1	1.5	100 – 800	14 – 1	Ø 50	805.00
MC 20/50-F	48SGQ93B0A	1.5	2	100 – 900	16 – 1		825.00
MC 30/50-F	48SGQ93A0A	2.2	3	100 – 1100	22 – 2		850.00
MC 40/50-F	48SGQ94050A	3	4	100 – 1100	24 – 4		1,075.00
MC 30/70-F	48SGQ947AA	2.2	3	200 – 1500	12 – 2	Ø 70	905.00
MC 40/70-F	48SGQ94070A	3	4	200 – 1600	15 – 4		1,130.00

- Power cable: 10 metres standard equipment
- Impeller: DOUBLE-CHANNEL AISI 304 precision cast stainless steel
- Shaft: AISI 431 stainless steel


• Standard supply single-phase version:

- External float switch
- Control panel
- Capacitor (inside the control panel)
- Thermal overload protector build into the motor winding

● **2.2 kW single-phase pumps, the thermal overload protector must be connected to the external control panel**

• Standard supply three-phase version:

- **For three-phase water pumps three thermal overload protectors in series are built into the winding and these must be connected to the control box**



(A)



(B)



(C)

- 1 - Footing connection
 2 - Slide guide
 (also to be ordered separately)
 3 - Intermediate support
 (on request)
 4 - Support for the guide tubes

SEWAGE LIFTING SYSTEM

HORIZONTAL DELIVERY VERSION WITH 3/4" GUIDE TUBES (A)

For VXC /50-F, MC /50-F	Code ASSVXCF050	DN 2"	€ 90.00
--------------------------------	-----------------	-------	----------------

- Kit consisting of:
 - footing connection;
 - slide guide with screws and seals;
 - support for the guide tubes.

VERTICAL DELIVERY VERSION WITH 3/4" GUIDE TUBES (B)

For VXC /50-F, MC /50-F	Code ASSVXCF050V	DN 2½"	€ 145.00
For VXC /70-F, MC /70-F	Code ASSVXCF070V	DN 3"	€ 180.00

VERTICAL DELIVERY VERSION WITH 2" GUIDE TUBES (C)

For VXC /50-F, MC /50-F	Code ASSVXCF0703V	DN 3"	€ 755.00
For VXC /70-F, MC /70-F			

- Kit consisting of:
 - footing connection complete with counterflange;
 - slide guide with screws and seals;
 - support for the guide tubes.

SLIDE GUIDE (also to be ordered separately)

For VXC /50-F, MC /50-F with guide tubes Ø 3/4"	Code ASSFL007	€ 40.00
For VXC /70-F, MC /70-F with guide tubes Ø 3/4"	Code ASSFL008	€ 46.00
For VXC /50-F, MC /50-F with guide tubes Ø 2"	Code ASSFL070	€ 87.00
For VXC /70-F, MC /70-F with guide tubes Ø 2"		

- Complete with screws and seals

INTERMEDIATE SUPPORT (on request)

For guide tubes Ø 3/4"	Code 859SV340INTFA	€ 98.00
For guide tubes Ø 2"	Code 859SV349INTFA	€ 75.00

GUIDE TUBES (AISI 304 stainless steel)

Guide tube Ø 3/4"	Code 54SARTG005	€ 20.00 per metre
Guide tube Ø 2"	Code 54SARTG006	€ 48.00 per metre

- In order to ensure stability, insert the intermediate support:
 - every 2 metres with 3/4" guide tubes (compulsory);
 - every 3 metres with 2" guide tubes (recommended).
- Maximum length of the tube plank: 6 metres

STANDARD INSTALLATION





VX 40 - VX 50 - VX 65 SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Three-phase	Code	kW	HP	Q l/min	H m	DN		€
VX 40/40	48SGV970DA	3	4	100 – 800	22 – 5	DN 50 (PN6) 2"	Ø 40	1,220.00
VX 55/40	48SGV970EA	4	5.5	100 – 850	25 – 6			1,305.00
VX 40/50	48SGV970GA	3	4	100 – 900	22 – 5.5	DN 50 (PN10) 2"	Ø 50	1,235.00
VX 55/50	48SGV970HA	4	5.5	100 – 1000	25 – 6.5			1,320.00
VX 40/65	48SGV970LA	3	4	200 – 1200	15.6 – 2.5	DN 65 (PN10) 2½"	Ø 65	1,320.00
VX 55/65	48SGV970MA	4	5.5	200 – 1350	19.4 – 3.7			1,410.00
VX 75/65	48SGV970NA	5.5	7.5	200 – 1500	23.6 – 5.5			1,470.00

- Impeller: cast iron VORTEX with an Epoxy Electro Coating treatment
- Registered EU Design n. 003863158-0002




BC 35 SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

MODEL		POWER P ₂		PERFORMANCE		PORT	PASSAGE of solids mm	PRICE
Three-phase	Code	kW	HP	Q l/min	H m	DN		€
BC 40/35	48SGM970CA	3	4	300 – 1500	18.5 – 5.5	DN 65 (PN10) 2½"	Ø 35	1,365.00
BC 55/35	48SGM970DA	4	5.5	300 – 1700	22.5 – 7.5			1,450.00
BC 75/35	48SGM970EA	5.5	7.5	300 – 1900	27.5 – 10			1,510.00

- Impeller: cast iron DOUBLE-CHANNEL with an Epoxy Electro Coating treatment
- Registered EU Design n. 003863158-0001

- Power cable: 10 metres standard equipment
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- In the three-phase pump the thermal overload cut-off is inserted inside the motor



SEWAGE LIFTING SYSTEM

HORIZONTAL DELIVERY VERSION WITH 3/4" GUIDE TUBES (A)

For VX /40	Code ASSPVX40	DN 2"	€ 90.00
For VX /50	Code ASSPVX50	DN 2"	€ 108.00

- Kit consisting of:
 - footing connection;
 - slide guide with screws and seals;
 - support for the guide tubes.

VERTICAL DELIVERY VERSION WITH 3/4" GUIDE TUBES (B)

For VX /40	Code ASSPVX40V	DN 2 1/2"	€ 155.00
For VX /50	Code ASSPVX503V	DN 2 1/2"	€ 170.00
For VX /65, BC /35	Code ASSPVX653V	DN 3"	€ 205.00

VERTICAL DELIVERY VERSION WITH 2" GUIDE TUBES (C)

For VX /50	Code ASSPVX50V	DN 3"	€ 795.00
For VX /50, VX /65, BC /35	Code ASSPVX65V	DN 3"	€ 800.00

- Kit consisting of:
 - footing connection complete with counterflange;
 - slide guide with screws and seals;
 - support for the guide tubes.

SLIDE GUIDE (also to be ordered separately)

For VX /40 with guide tubes Ø 3/4"	Code ASSFL011	€ 29.00
For VX /50 with guide tubes Ø 3/4"	Code ASSFL009	€ 43.00
For VX /50 with guide tubes Ø 2"	Code ASSFL050	€ 87.00
For VX /65, BC /35 with guide tubes Ø 3/4"	Code ASSFL010	€ 55.00
For VX /65, BC /35 with guide tubes Ø 2"	Code ASSFL065	€ 96.00

- Complete with screws and seals

INTERMEDIATE SUPPORT (on request)

For guide tubes Ø 3/4"	Code 859SV340INTFA	€ 98.00
For guide tubes Ø 2"	Code 859SV349INTFA	€ 75.00

GUIDE TUBES (AISI 304 stainless steel)

Guide tube Ø 3/4"	Code 54SARTG005	€ 20.00 per metre
Guide tube Ø 2"	Code 54SARTG006	€ 48.00 per metre

- **In order to ensure stability, insert the intermediate support:**
 - every 2 metres with 3/4" guide tubes (compulsory);
 - every 3 metres with 2" guide tubes (recommended).
- **Maximum length of the tube plank: 6 metres**

STANDARD INSTALLATION



- 1 - Footing connection
 2 - Slide guide
 (also to be ordered separately)
 3 - Intermediate support
 (on request)
 4 - Support for the guide tubes

VXC4 SUBMERSIBLE "VORTEX" PUMPS FOR SEWAGE WATER

4 POLES n= 1450 min⁻¹

MODEL		POWER P ₂		PERFORMANCE Q l/min		PORT DN	PASSAGE of solids mm	PRICE €
Three-phase	Code	kW	HP					
VXC4 40/100	48SGVP970CA	3	4	300 – 1700	7.6 – 2	DN 100 (PN10)	Ø 100	2,400.00
VXC4 50/100	48SGVP970DA	3.7	5	300 – 2000	10.2 – 2.7			2,450.00
VXC4 55/100	48SGVP970EA	4	5.5	300 – 2200	11.7 – 3			2,500.00
VXC4 80/90	48SGVP980CE	6	8	400 – 2400	12.3 – 2.6	DN 100 (PN10)	Ø 90	4,520.00
VXC4 95/90	48SGVP980DE	7	9.5	400 – 2700	14.2 – 3.4			4,740.00
VXC4 125/80	48SGVP980FE	9.2	12.5	600 – 3200	14.6 – 4.7		Ø 80	5,090.00
VXC4 150/80	48SGVP980GE	11	15	600 – 3600	16.8 – 6			5,320.00
VXC4 180/80	48SGVP980HE	13	18	600 – 4000	19.5 – 7.5			5,680.00

• Impeller: cast iron VORTEX

MC4 SUBMERSIBLE "DOUBLE-CHANNEL" PUMPS FOR SEWAGE WATER

4 POLES n= 1450 min⁻¹

MODEL		POWER P ₂		PERFORMANCE Q l/min		PORT DN	PASSAGE of solids mm	PRICE €
Three-phase	Code	kW	HP					
MC4 40/55	48SGMP970CA	3	4	400 – 2200	10.5 – 3.5	DN 80 (PN10)	Ø 55	2,470.00
MC4 50/55	48SGMP970DA	3.7	5	400 – 2400	12.5 – 4.8			2,520.00
MC4 55/55	48SGMP970EA	4	5.5	400 – 2600	13.9 – 5.3			2,570.00
MC4 80/80	48SGMP980CE	6	8	600 – 3300	14 – 4.6	DN 100 (PN10)	Ø 80	4,740.00
MC4 95/80	48SGMP980DE	7	9.5	600 – 3600	16 – 5.5			5,090.00
MC4 110/80	48SGMP980EE	8	11	600 – 3900	18 – 6.4			5,320.00
MC4 125/80	48SGMP980FE	9.2	12.5	600 – 4200	20.2 – 7.4			5,680.00

• Impeller: cast iron DOUBLE-CHANNEL

- Power cable: 10 metres standard equipment
- Two mechanical seals separated by an oil chamber
- Shaft: AISI 431 stainless steel
- **Winding equipped with three thermal overload cut-offs in series, to link to the external electricity panel as necessary**
- Registered EU Design n. 003863158-0003 for VXC4 – n° 003863158-0004 for MC4

• OPTIONS AVAILABLE ON REQUEST

- Pumps equipped with internal probes detecting the presence of water in the oil chamber
- Pumps with double cable for star/delta start

COUNTERFLANGE (on request)

For VXC4, MC4 /80	Code ASS14FL100VXC4	DN 100	€ 70.00
For MC4 /55	Code ASS14FL080MC4	DN 80	€ 55.00

• Complete with screws and seal

BASE (on request)

For VXC4 /90, VXC4 /80, MC4 /80	Code ASSB01VXC4	€ 480.00
---------------------------------	-----------------	----------

• Complete with screws



- 1 - Footing connection
- 2 - Slide guide
(also to be ordered separately)
- 3 - Intermediate support
(on request)
- 4 - Support for the guide tubes

SEWAGE LIFTING SYSTEM

VERTICAL DELIVERY VERSION WITH 2" GUIDE TUBES

For VXC4, MC4 /80	Code ASSPVXC4V	DN 4"	€ 830.00
For MC4 /55	Code ASSPMC4V	DN 3"	€ 800.00

- Kit consisting of:
 - footing connection complete with counterflange;
 - slide guide with screws and seals;
 - support for the guide tubes.

SLIDE GUIDE (also to be ordered separately)

For VXC4, MC4 /80	Code ASSFL100	€ 98.00
For MC4 /55	Code ASSFL080	€ 106.00

- Complete with screws and seals

INTERMEDIATE SUPPORT (on request)

For guide tubes Ø 2"	Code 859SV349INTFA	€ 75.00
----------------------	--------------------	----------------


GUIDE TUBES (AISI 304 stainless steel)

Guide tube Ø 2"	Code 54SARTG006	€ 48.00 per metre
-----------------	-----------------	--------------------------

- In order to ensure stability, insert the intermediate support every three metres of guide tube (recommended)
- Maximum length of the tube plank: 6 metres



STANDARD INSTALLATION



SAR 40 CLEAR WASTE WATER - RAINWATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 40 - TOP 1	KSF04TOP11A1	0.25	0.33	40	160	6	395.00
SAR 40 - TOP 2	KSF04TOP12A1	0.37	0.50	40	220	8	400.00
SAR 40 - TOP 3	KSF04TOP13A1	0.55	0.75	40	260	10	423.00
SAR 40 - RXm 1	KSF04TXP11A1	0.25	0.33	40	160	6.5	460.00
SAR 40 - RXm 2	KSF04TXP12A1	0.37	0.50	40	220	9.5	466.00
SAR 40 - RXm 3	KSF04TXP13A1	0.55	0.75	40	220	11.5	478.00

SAR 40 DIRTY OR SEWAGE WASTE WATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 40 - TOP 2-VORTEX	KSF04TOPV12A1	0.37	0.50	40	180	6.5	400.00
SAR 40 - TEX 2	KSF04TEX02A1	0.37	0.50	40	200	7.5	440.00
SAR 40 - TEX 3	KSF04TEX03A1	0.55	0.75	40	240	9.5	460.00
SAR 40 - RXm 2/20 VORTEX	KSF04TXV12A1	0.37	0.50	40	180	6.5	465.00

COMPONENTS

- 40-litre polyethylene tank with cover plate
- Pump with float switch
- Power cable: 5 metres standard equipment with Schuko plug
- Non-return valve
- Lifting stations with inlet pipe G 1½", discharge pipe G 1¼" and vent pipe G ½"

For the version with a 10 metres long power supply cable apply a surcharge of

€ 14.00

Attention: Standard EN 60335-2-41 requires the use of a 10 metres long cable for outdoor applications

DIMENSIONS



SAR 100 CLEAR WASTE WATER - RAINWATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 100 - TOP 2	KSF10TOP12A1U	0.37	0.50	100	220	8	600.00
SAR 100 - TOP 3	KSF10TOP13A1U	0.55	0.75	100	260	10	623.00
SAR 100 - TOP 4	KSF10TOP142A1	0.75	1	100	320	12.5	708.00
SAR 100 - TOP MULTI 1	KSF10TPM050A1U	0.37	0.50	100	70	25	650.00
SAR 100 - TOP MULTI 2	KSF10TPM070A1U	0.55	0.75	100	80	40	721.00
SAR 100 - TOP MULTI 3	KSF10TPM170A1U	0.55	0.75	100	120	32	731.00
SAR 100 - RXm 2	KSF10TXP12A1U	0.37	0.50	100	220	9.5	670.00
SAR 100 - RXm 3	KSF10TXP13A1U	0.55	0.75	100	220	11.5	682.00
SAR 100 - Dm 10	KSF10SGD910A1U	0.75	1	100	300	15.5	770.00
SAR 100 - Dm 20	KSF10SGD920A1U	0.75	1	100	250	19	780.00
SAR 100 - Dm 30	KSF10SGD930A1U	1.1	1.5	100	275	26	808.00

SAR 100 DIRTY OR SEWAGE WASTE WATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 100 - TOP 2-VORTEX	KSF10TOPV12A1U	0.37	0.50	100	180	6.5	620.00
SAR 100 - TOP 3-VORTEX	KSF10TOPV13A1U	0.55	0.75	100	180	8	643.00
SAR 100 - RXm 2/20	KSF10TXV12A1U	0.37	0.50	100	180	6.5	685.00
SAR 100 - RXm 3/20	KSF10TXV13A1U	0.55	0.75	100	180	8	701.00
SAR 100 - ZXm 2/30	KSF10SDZX230A1U	0.55	0.75	100	320	12.5	755.00
SAR 100 - ZXm 2/40	KSF10SDZX240A1U	0.55	0.75	100	400	11	760.00
SAR 100 - VXm 8/35	KSF10SGV90A0A1U	0.55	0.75	100	350	8	770.00
SAR 100 - VXm 10/35	KSF10SGV91A0A1U	0.75	1	100	400	10	775.00
SAR 100 - VXm 8/50	KSF10SGV91C0A1U	0.55	0.75	100	450	6	780.00
SAR 100 - VXm 10/50	KSF10SGV91D0A1U	0.75	1	100	550	8.5	785.00
SAR 100 - BCm 10/50	KSF10SGM81A0A1U	0.75	1	100	600	11	830.00

SAR 100 WITH GRINDER PUMPS (TRITUS)

Single-phase							
SAR 100 - TRm 0.75	KSF10SHT00A1	0.75	1	100	125	15	1,215.00
SAR 100 - TRm 1.1	KSF10SHT01A1	1.1	1.5	100	140	21.5	1,250.00

COMPONENTS

- 100-litre polyethylene tank with cover plate
- Pump with float switch
- Power cable: 10 metres standard equipment with Schuko plug
- Control panel (only for SAR 100 - TR)
- Lifting stations with inlet pipe Ø 110 mm, discharge pipe G 1¼" or G 1½" or G 2" and vent pipe Ø 50 mm

DIMENSIONS



SAR 250 CLEAR WASTE WATER - RAINWATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 250 - TOP 3	KSE25TOP13A1U	0.55	0.75	250	260	10	915.00
SAR 250 - TOP 4	KSE25TOP142A1	0.75	1	250	320	12.5	1,000.00
SAR 250 - TOP 5	KSE25TOP152A1	0.92	1.25	250	360	15	1,010.00
SAR 250 - RXm 3	KSE25TXP13A1U	0.55	0.75	250	220	11.5	990.00
SAR 250 - RXm 4	KSE25TXP24A1U	0.75	1	250	260	15	1,308.00
SAR 250 - RXm 5	KSE25TXP25A1U	1.1	1.5	250	300	19.5	1,333.00
SAR 250 - Dm 10	KSE25SGD910A1U	0.75	1	250	300	15.5	1,055.00
SAR 250 - Dm 20	KSE25SGD920A1U	0.75	1	250	250	19	1,065.00
SAR 250 - Dm 30	KSE25SGD930A1U	1.1	1.5	250	275	26	1,093.00

SAR 250 DIRTY OR SEWAGE WASTE WATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 250 - TOP 2-VORTEX	KSE25TOPV12A1U	0.37	0.50	250	180	6.5	915.00
SAR 250 - TOP 3-VORTEX	KSE25TOPV13A1U	0.55	0.75	250	180	8	938.00
SAR 250 - RXm 3/20	KSE25TXV13A1U	0.55	0.75	250	180	8	987.00
SAR 250 - RXm 4/40	KSE25TXV24A1U	0.75	1	250	280	9.5	1,280.00
SAR 250 - RXm 5/40	KSE25TXV25A1U	1.1	1.5	250	380	12.5	1,300.00
SAR 250 - VXm 10/35-ST	KSE25SGV96B0A1U	0.75	1	250	400	10.5	1,220.00
SAR 250 - VXm 10/50-ST	KSE25SGV96E0A1U	0.75	1	250	550	9.5	1,230.00
SAR 250 - BCm 10/50-ST	KSE25SGM88A0A1U	0.75	1	250	600	11	1,265.00
SAR 250 - VXm 10/35	KSE25SGV91A0A1U	0.75	1	250	400	10	1,065.00
SAR 250 - VXm 15/35	KSE25SGV91B0A1U	1.1	1.5	250	500	13.5	1,104.00
SAR 250 - VXm 10/50	KSE25SGV91D0A1U	0.75	1	250	550	8.5	1,075.00
SAR 250 - VXm 15/50	KSE25SGV91E0A1U	1.1	1.5	250	650	11	1,114.00
SAR 250 - BCm 10/50	KSE25SGM81A0A1U	0.75	1	250	600	11	1,120.00
SAR 250 - BCm 15/50	KSE25SGM82A0A1U	1.1	1.5	250	750	14	1,152.00

SAR 250 WITH GRINDER PUMPS (TRITUS)

Single-phase							
SAR 250 - TRm 0.75	KSE25SHT00A1	0.75	1	250	125	15	1,460.00
SAR 250 - TRm 1.1	KSE25SHT01A1	1.1	1.5	250	140	21.5	1,495.00
SAR 250 - TRm 1.5	KSE25SHT02A1	1.5	2	250	270	25	1,930.00

COMPONENTS

- 250-litre polyethylene tank with cover plate
- Pump with float switch
- Power cable: 10 metres standard equipment with Schuko plug
- Control panel (only for SAR 250 - TR)
- Lifting stations with inlet pipe Ø 110 mm, discharge pipe G 1¼" or G 1½" or G 2" and vent pipe DN 50 or DN 75
- Footing connection and guide tubes for lowering the pump (only for VX-ST e BC-ST)

OPTIONALS AVAILABLE ON REQUEST

Alarm KIT (Code KSKIT-ALLARME)	€ 405.00
Kit includes: control box, self-powered siren, float switch	
300 mm extension kit (Code KSKIT-308MA)	€ 130.00
Extension kit for the installation of the polyethylene "SAR" tank at greater depths	
"SAR" stations with ball check valves and ball valve in the discharge pipe	An request



DIMENSIONS



SAR 550 CLEAR WASTE WATER - RAINWATER

MODEL		POWER P ₂		TANK CAPACITY	MAXIMUM FLOW RATE (1 pump)	MAXIMUM HEAD	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 550 - TOP 4	KSE55TOP142A1	0.75	1	550	320	12.5	2,360.00
SAR 550 - TOP 5	KSE55TOP152A1	0.92	1.25	550	360	15	2,380.00
SAR 550 - RXm 4	KSE55TXP24A1U	0.75	1	550	260	15	2,840.00
SAR 550 - RXm 5	KSE55TXP25A1U	1.1	1.5	550	300	19.5	2,890.00
SAR 550 - Dm 10	KSE55SGD910A1U	0.75	1	550	300	15.5	2,410.00
SAR 550 - Dm 20	KSE55SGD920A1U	0.75	1	550	250	19	2,430.00
SAR 550 - Dm 30	KSE55SGD930A1U	1.1	1.5	550	275	26	2,486.00

SAR 550 DIRTY OR SEWAGE WASTE WATER

MODEL		POWER P ₂		TANK	PORTATA MAX (1 pump)	PREVALENZA MAX	PRICE
Single-phase	Code	kW	HP	litres	l/min	m	€
SAR 550 - RXm 4/40	KSE55TXV24A1U	0.75	1	550	280	9.5	2,820.00
SAR 550 - RXm 5/40	KSE55TXV25A1U	1.1	1.5	550	380	12.5	2,860.00
SAR 550 - VXm 10/35-ST	KSE55SGV96B0A1U	0.75	1	550	400	10.5	2,730.00
SAR 550 - VXm 10/50-ST	KSE55SGV96E0A1U	0.75	1	550	550	9.5	2,750.00
SAR 550 - BCm 10/50-ST	KSE55SGM88A0A1U	0.75	1	550	600	11	2,980.00
SAR 550 - VXm 10/35	KSE55SGV91A0A1U	0.75	1	550	400	10	2,410.00
SAR 550 - VXm 15/35	KSE55SGV91B0A1U	1.1	1.5	550	500	13.5	2,488.00
SAR 550 - VXm 10/50	KSE55SGV91D0A1U	0.75	1	550	550	8.5	2,430.00
SAR 550 - VXm 15/50	KSE55SGV91E0A1U	1.1	1.5	550	650	11	2,508.00
SAR 550 - BCm 10/50	KSE55SGM81A0A1U	0.75	1	550	600	11	2,530.00
SAR 550 - BCm 15/50	KSE55SGM82A0A1U	1.1	1.5	550	750	14	2,594.00
Three-phase							
SAR 550 - VX 15/50	KSE55SGV91E0AU	1.1	1.5	550	650	11	2,508.00
SAR 550 - BC 15/50	KSE55SGM82A0AU	1.1	1.5	550	750	14	2,594.00

SAR 550 WITH GRINDER PUMPS (TRITUS)

Single-phase							
SAR 550 - TRm 0.75	KSE55SHT00A1	0.75	1	550	125	15	3,160.00
SAR 550 - TRm 1.1	KSE55SHT01A1	1.1	1.5	550	140	21.5	3,230.00
SAR 550 - TRm 1.5	KSE55SHT02A1	1.5	2	550	270	25	4,100.00
Three-phase							
SAR 550 - TR 1.1	KSE55SHT01A	1.1	1.5	550	140	21.5	3,140.00

COMPONENTS

- 550-litre polyethylene tank with cover plate
- Control panel
- Three float switches for: 1) the alternate start-up of one of the two pumps, 2) maximum level for starting-up the second pump, 3) minimum level for switching the pumps off

- Power cable: 10 metres standard equipment
- Lifting stations with inlet pipe Ø 110 mm, discharge pipe G 1¼" or G 1½" or G 2" and vent pipe DN 50 or DN 75
- Footing connection and guide tubes for lowering the pump (only for VX-ST e BC-ST)

OPTIONALS AVAILABLE ON REQUEST

Alarm KIT (Code KSKIT-ALLARME) **€ 405.00**

Kit includes: control box, self-powered siren, float switch

300 mm extension kit (Code KSKIT-308MA) **€ 130.00**

Extension kit for the installation of the polyethylene "SAR" tank at greater depths

"SAR" stations with ball check valves and ball valve in the discharge pipe **An request**

DIMENSIONS





PQ-EKO PUMPS WITH PERIPHERAL IMPELLER

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Single-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
PQm 60-EKO	41PQE60A1	0.37	0.50	–	1 – 32	37 – 5	½"	½"	100.00
Three-phase									
PQ 60-EKO	41PQTE60A	0.37	0.50	IE3	1 – 32	37 – 5	½"	½"	115.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

● Pump body in cast iron with an anti-block treatment

• Impeller: brass



PQ-PRO PUMPS WITH PERIPHERAL IMPELLER

Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
PQm 60-PRO	41PQP60A1	0.37	0.50	-	5 – 35	38 – 4	1"	1"	120.00
PQm 65-PRO	41PQP65A1	0.55	0.75		5 – 45	50 – 4			160.00
PQm 70-PRO	41PQP70A1	0.60	0.85		5 – 45	66 – 12			200.00
PQm 81-PRO	41PQ88A1	0.45	0.60		2 – 18	80 – 5	½"	½"	185.00
PQm 90-PRO	41PQP90A1	0.75	1		2 – 37	86 – 5	¾"	¾"	210.00
PQm 100-PRO	41PQP100A1	1.1	1.5		5 – 70	80 – 15	1"	1"	300.00
PQm 200-PRO	41PQP200A1	1.5	2		5 – 80	86 – 10			320.00
PQm 300-PRO	41PQP300A1	2.2	3		5 – 90	95 – 10			360.00
Three-phase									
PQ 60-PRO	41PQTP60A	0.37	0.50	IE3	5 – 35	38 – 4	1"	1"	135.00
PQ 65-PRO	41PQTP65A	0.55	0.75		5 – 45	50 – 4			175.00
PQ 70-PRO	41PQTP70A	0.60	0.85		5 – 45	66 – 12			215.00
PQ 81-PRO	41PQT88A	0.45	0.60		2 – 18	80 – 5	½"	½"	200.00
PQ 90-PRO	41PQTP90A	0.75	1		2 – 37	86 – 5	¾"	¾"	225.00
PQ 100-PRO	41PQTP100A	1.1	1.5		5 – 70	80 – 15	1"	1"	300.00
PQ 200-PRO	41PQTP200A	1.5	2		5 – 80	86 – 10			320.00
PQ 300-PRO	41PQTP300A	2.2	3		5 – 90	95 – 10			360.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

● Pump body in cast iron with an anti-block treatment

• Impeller: brass



PQ-Bs PUMPS WITH PERIPHERAL IMPELLER

Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
PQm 60-Bs	41PNQ60YA1	0.37	0.50	-	5 – 35	38 – 4	1"	1"	170.00
PQm 65-Bs	41PNQ67YA1	0.55	0.75		5 – 45	50 – 4			230.00
PQm 81-Bs	41PQ86YA1	0.45	0.60		2 – 18	80 – 5	½"	½"	230.00
Three-phase									
PQ 60-Bs	41PNQ60YA	0.37	0.50	IE3	5 – 35	38 – 4	1"	1"	185.00
PQ 65-Bs	41PNQ67YA	0.55	0.75		5 – 45	50 – 4			245.00
PQ 81-Bs	41PQT86YA	0.45	0.60		2 – 18	80 – 5	½"	½"	245.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

● Pump body in forged brass

• Impeller: brass



PQA PUMPS WITH PERIPHERAL IMPELLER

Single-phase	Code	kW	HP	▲	l/min	m	DN1	DN2	€
PQAm 50	41PNQA5PA1	0.18	0.25	-	2 – 28	25 – 5	½"	½"	140.00
PQAm 60	41PNQA6PA1	0.37	0.50		2 – 32	38 – 5			140.00
PQAm 70	41PQA71PA1	0.55	0.75		2 – 45	62 – 8	215.00		
PQAm 72	41PQA7PA1	0.55	0.75		5 – 50	62 – 12	1"	1"	227.00
PQAm 90	41PQA9PA1	0.75	1		2 – 37	83 – 5	½"	½"	235.00
Three-phase									
PQA 50	41PNQA5PA	0.18	0.25	IE3	2 – 28	25 – 5	½"	½"	155.00
PQA 60	41PNQA6PA	0.37	0.50		2 – 32	38 – 5			155.00
PQA 70	41PQAT71PA	0.55	0.75		2 – 45	62 – 8	230.00		
PQA 72	41PQAT7PA	0.55	0.75		5 – 50	62 – 12	1"	1"	242.00
POA 90	41POAT9PA	0.75	1		2 – 37	83 – 5	½"	½"	250.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

● Pump body in PPS technopolymer with threaded brass inserts

• Impeller: brass

• Front cover of the pump body: forged brass



PQ3000 PUMP WITH PERIPHERAL IMPELLER

MODEL		POWER P ₂			PERFORMANCE		PORTS		PRICE
Three-phase	Code	kW	HP	▲	Q l/min	H m	DN ₁	DN ₂	€
PQ 3000	41PQT949A5	2.2	3	IE3	5 – 50	180 – 50	¾"	¾"	570.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body in cast iron with anti-block treatment
- Impeller: bronze



PQ3000-MF PUMP WITH PERIPHERAL IMPELLER

Three-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
PQ 3000-MF	41PQT948A5	2.2	3	IE3	5 – 50	180 – 50	¾"	¾"	640.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body and protective cover in AISI 316 cast stainless steel
- Impeller: bronze



PV PERIPHERAL PUMPS WITH BRASS PUMP BODY

Single-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
PVm 55 (*)	41PNV55A1N	0.18	0.25	-	2 – 10	35 – 5	¼"	¼"	165.00
PVm 60	41PNV60A1	0.37	0.50		2 – 32	41 – 5	½"	½"	195.00
PVm 81	41PNV81A1	0.37	0.50		2 – 17	75 – 5			210.00
PVm 65	41PNV65A1	0.60	0.85		2 – 42	55 – 5			215.00
PVm 70	41PNV70A1	0.90	1.20		2 – 45	70 – 5	¾"	¾"	240.00
PVm 90	41PNV90A1	0.90	1.20		2 – 35	95 – 5			250.00

Three-phase	Code	kW	HP	▲	l/min	m	DN ₁	DN ₂	€
PV 55 (*)	41PNV55AN	0.18	0.25	IE3	2 – 10	35 – 5	¼"	¼"	180.00
PV 60	41PNV60A	0.37	0.50		2 – 32	41 – 5	½"	½"	210.00
PV 81	41PNV81A	0.37	0.50		2 – 17	75 – 5			225.00
PV 65	41PNV65A	0.60	0.85		2 – 42	55 – 5			230.00
PV 70	41PNV70A	0.90	1.20		2 – 45	70 – 5	¾"	¾"	255.00
PV 90	41PNV90A	0.90	1.20		2 – 35	95 – 5			265.00

▲ Three phase motor efficiency class (IEC 60034-30-1)

- Pump body: forged brass with side-by-side suction and discharge ports
- Impeller: brass

(*) The PVm55 and PV55 are also designed to work at 60 Hz with the following performances		Q l/min	H m
		2 – 10	46 – 10

INCREASES IN PRICE FOR SPECIAL SEALS

Materials	Elastomer	Shaft diameter	Increase in price
Silicon carbide/Graphite	EPDM	Ø 12 mm	€ 10.00
Silicon carbide/Graphite	Viton		€ 15.00
Ceramic/Graphite	EPDM	Ø 14 mm	€ 10.00
Ceramic/Graphite	Viton		€ 15.00
Ceramic/Graphite	EPDM	Ø 18 mm	€ 10.00
Ceramic/Graphite	Viton		€ 50.00

SUBMERSIBLE MULTI-STAGE PUMPS DESIGNED TO PUMP ADBLUE®



TOP MULTI-AD SUBMERSIBLE PUMPS DESIGNED TO PUMP AdBlue®

MODEL		POWER P ₂		PERFORMANCE		PORT	PRICE
Single-phase	Code	kW	HP	Q l/min	H m	DN	€
TOP MULTI 1-AD	48TPM050A1ADB	0.37	0.50	10 – 70	25 – 5	1¼"	210.00

- Multistage submersible pumps TOP MULTI 1-AD are designed to pump clean liquid, which is defined according to standard ISO 22241 as AUS 32 (Aqueous Urea Solution 32.5%)
- This liquid is equivalent to other commercial trademarks known as:
 - AdBlue® (trademark registered by Verband der AutomobilindustrieVDA)
 - DEF (Diesel Exhaust Fluid)
 - Arla 32 (Agente Redutor Liquido de Óxido de Nitrogênio Automotivo)

HYDROFRESH AUTOCLAVE SETS

MODEL		POWER (P ₂)		Flow rate ⁽¹⁾	Setting ⁽²⁾	PRICE
Single-phase	Code	kW	HP	l/min	bar	€

HYDROFRESH 05VT

PKm 60 - 05 VT	N41PNK60A1	0.37	0.50	32	1.4 – 2.8	150.00
JCRm 1B - 05 VT	N46JCN1B0A1	0.48	0.65	60	1.4 – 2.8	229.00
JSWm 1BX - 05 VT	N46JSNP1BA1	0.48	0.65	50	1.4 – 2.8	206.00
JSWm 1AX - 05 VT	N46JSNP6AA1	0.55	0.75	55	1.8 – 3.2	214.00

HYDROFRESH 24 SF

PKm 60 - 24 SF	H41PNK60A1P	0.37	0.50	32	1.4 – 2.8	178.00
PKm 65 - 24 SF	H41PNK67A1P	0.50	0.70	40	1.5 – 3.0	195.00
JCRm 1B - 24 SF	H46JCN1B0A1P	0.48	0.65	50	1.4 – 2.8	257.00
JCRm 1A - 24 SF	H46JCN1A0A1P	0.55	0.75	55	1.8 – 3.2	264.00
JSWm 1CX - 24 SF	H46JSNP1CA1P	0.37	0.50	50	1.2 – 2.6	228.00
JSWm 1BX - 24 SF	H46JSNP1BA1P	0.48	0.65	50	1.4 – 2.8	230.00
JSWm 1AX - 24 SF	H46JSNP1AA1P	0.55	0.75	55	1.8 – 3.2	238.00
JSWm 2CX - 24 SF	H46JSNP7A10A1P	0.75	1	70	2.0 – 3.5	245.00
JSWm 2BX - 24 SF	H46JSNP7A12A1P	0.90	1.25	70	2.4 – 3.8	257.00
JSWm 2AX - 24 SF	H46JSNP7A15A1P	1.1	1.5	70	2.8 – 4.0	267.00
PLURIJETm 3/60X - 24 SF	H43PJA6053A1P	0.37	0.50	60	1.0 – 2.8	268.00
PLURIJETm 3/80X - 24 SF	H43PJA6063A1P	0.48	0.65	60	1.5 – 3.2	273.00
PLURIJETm 4/80X - 24 SF	H43PJA6084A1P	0.55	0.75	60	2.0 – 4.2	284.00
PLURIJETm 3/100X - 24 SF	H43PJA6083A1P	0.55	0.75	100	1.2 – 3.2	284.00
PLURIJETm 4/100X - 24 SF	H43PJA5104A1P	0.75	1	100	2.2 – 4.4	325.00

HYDROFRESH 24 CL

PKm 60 - 24 CL	I41PNK60A1P	0.37	0.50	32	1.4 – 2.8	192.00
PKm 65 - 24 CL	I41PNK67A1P	0.50	0.70	40	1.5 – 3.0	209.00
CPm 158 - 24 CL	I44CI16A1P	0.75	1	90	1.8 – 3.2	280.00
CPm 170 - 24 CL	I44CM17A1P	1.1	1.5	120	2.2 – 3.5	404.00
JCRm 1B - 24 CL	I46JCN1B0A1P	0.48	0.65	50	1.4 – 2.8	277.00
JCRm 1A - 24 CL	I46JCN1A0A1P	0.55	0.75	55	1.8 – 3.2	284.00
JCRm 2C - 24 CL	I46JCR2A10A1P	0.75	1	70	1.9 – 3.4	306.00
JCRm 2A - 24 CL	I46JCR2A15A1P	1.1	1.5	70	2.7 – 4.0	328.00
JSWm 1BX - 24 CL	I46JSNP1BA1P	0.48	0.65	50	1.4 – 2.8	250.00
JSWm 1AX - 24 CL	I46JSNP1AA1P	0.55	0.75	55	1.8 – 3.2	258.00
JSWm 2CX - 24 CL	I46JSNP7A10A1P	0.75	1	70	2.0 – 3.5	260.00
JSWm 2BX - 24 CL	I46JSNP7A12A1P	0.90	1.25	70	2.4 – 3.8	272.00
JSWm 2AX - 24 CL	I46JSNP7A15A1P	1.1	1.5	70	2.8 – 4.0	282.00
PLURIJETm 3/80X - 24 CL	I43PJA6063A1P	0.48	0.65	60	1.5 – 3.2	292.00
PLURIJETm 4/80X - 24 CL	I43PJA6084A1P	0.55	0.75	60	2.0 – 4.2	303.00
PLURIJETm 3/100X - 24 CL	I43PJA6083A1P	0.55	0.75	100	1.2 – 3.2	303.00
PLURIJETm 4/100X - 24 CL	I43PJA5104A1P	0.75	1	100	2.2 – 4.4	344.00

HYDROFRESH 60 CL

JSWm 2CX - 60 CL	L46JSNP7A10A1P	0.75	1	70	2.0 – 3.5	360.00
JSWm 2BX - 60 CL	L46JSNP7A12A1P	0.90	1.25	70	2.4 – 3.8	372.00
JSWm 2AX - 60 CL	L46JSNP7A15A1P	1.1	1.5	70	2.8 – 4.0	382.00
PLURIJETm 4/80X - 60 CL	L43PJA6084A1P	0.55	0.75	60	2.0 – 4.2	400.00
PLURIJETm 3/100X - 60 CL	L43PJA6083A1P	0.55	0.75	100	1.2 – 3.2	400.00
PLURIJETm 4/100X - 60 CL	L43PJA5104A1	0.75	1	100	2.2 – 4.4	441.00

COMPONENTS

- Single-phase pump
- Tank
- Pressure switch PSG-1
- Pressure gauge (for 24SF, 24CL and 60CL)
- Hose (for 24CL and 60CL)
- Brass connector
- 1.5 m power cable with Schuko plug

⁽¹⁾ Maximum flow rate at the minimum recommended pressure switch pressure

⁽²⁾ Recommended pressure range

CB2 PRESSURE BOOSTING SETS

MODEL		POWER INSTALLED (P ₂)			MAXIMUM FLOW RATE*	MAX HEAD	PORTS		PRICE
Single-phase	Code	kW	HP	▲	m ³ /h	m	DN ₁	DN ₂	€
CB2 - MKm 3/3	KCPM3003A1	2x0.75	2x1	-	9.6	52	2"	1½"	1,895.00
CB2 - MKm 3/4	KCPM3004A1	2x1.1	2x1.5		9.6	69.5			1,920.00
CB2 - MKm 3/5	KCPM3005A1	2x1.1	2x1.5		9.6	87			1,940.00
CB2 - MKm 3/6	KCPM3006A1	2x1.5	2x2		9.6	104			2,000.00
CB2 - MKm 5/4	KCPM5004A1	2x1.1	2x1.5	-	14.4	56	2"	1½"	1,920.00
CB2 - MKm 5/5	KCPM5005A1	2x1.1	2x1.5		14.4	70			1,940.00
CB2 - MKm 5/6	KCPM5006A1	2x1.5	2x2		14.4	84			2,000.00
CB2 - MKm 8/4	KCPM8004A1	2x1.5	2x2		21.6	56	2½"	1½"	2,110.00
CB2 - 4CPm 100	KCCPN2860A1	2x0.75	2x1	-	15.6	50	1½"	1½"	1,320.00
CB2 - 3CRm 80	KCCR08D3A1	2x0.45	2x0.60	-	9.6	40	1½"	1½"	1,320.00
CB2 - 4CRm 80	KCCR08D4A1	2x0.55	2x0.75		9.6	52			1,330.00
CB2 - 5CRm 80	KCCR0805A1	2x0.75	2x1		9.6	67			1,390.00
CB2 - 4CRm 100	KCCR10D4A1	2x0.75	2x1		15.6	50			1,415.00
CB2 - 5CRm 100	KCCR1005A1	2x1.1	2x1.5	-	15.6	63	2"	1½"	1,440.00
CB2 - 2CPm 25/130	KC2CT130NA1	2x0.75	2x1		12.0	42			1,360.00
CB2 - 2CPm 25/14B	KC2CT26160BA1	2x1.1	2x1.5		12.0	54			1,660.00
CB2 - 2CPm 25/16C	KC2CT26140CA1	2x1.1	2x1.5		14.4	47			1,670.00
CB2 - 2CPm 25/16B	KC2CT26140BA1	2x1.5	2x2		16.8	58			1,745.00
Three-phase									
CB2 - MK 3/3	KCPM3003A	2x0.75	2x1	IE3	9.6	52	2"	1½"	2,010.00
CB2 - MK 3/4	KCPM3004A	2x1.1	2x1.5		9.6	69.5			2,070.00
CB2 - MK 3/5	KCPM3005A	2x1.1	2x1.5		9.6	87			2,090.00
CB2 - MK 3/6	KCPM3006A	2x1.5	2x2		9.6	104			2,150.00
CB2 - MK 5/4	KCPM5004A	2x1.1	2x1.5	IE3	14.4	56	2"	1½"	2,070.00
CB2 - MK 5/5	KCPM5005A	2x1.1	2x1.5		14.4	70			2,090.00
CB2 - MK 5/6	KCPM5006A	2x1.5	2x2		14.4	84			2,150.00
CB2 - MK 5/7	KCPM5007A	2x1.8	2x2.5		14.4	98			2,170.00
CB2 - MK 5/8	KCPM5008A	2x2.2	2x3	IE3	14.4	112	2½"	1½"	2,200.00
CB2 - MK 8/4	KCPM8004A	2x1.5	2x2		21.6	56			2,260.00
CB2 - MK 8/5	KCPM8005A	2x1.8	2x2.5		21.6	70			2,280.00
CB2 - MK 8/6	KCPM8006A	2x2.2	2x3		21.6	86			2,310.00
CB2 - 2CP 25/130	KC2CT130NA	2x0.75	2x1	IE3	12.0	42	2"	1½"	1,520.00
CB2 - 2CP 25/14B	KC2CT26160BA	2x1.1	2x1.5		12.0	54			1,820.00
CB2 - 2CP 25/16C	KC2CT26140CA	2x1.1	2x1.5		14.4	47			1,830.00
CB2 - 2CP 25/16B	KC2CT26140BA	2x1.5	2x2		16.8	58			1,895.00
CB2 - 2CP 25/16A	KC2CT26140AA	2x2.2	2x3	IE3	19.2	68	3"	2"	1,915.00
CB2 - 2CP 32/200C	KC2CT3030CA	2x3	2x4		30.0	70			2,980.00
CB2 - 2CP 32/200B	KC2CT3130BA	2x4	2x5.5		30.0	85			3,070.00
CB2 - 2CP 32/210B	KC2CT3430BA	2x5.5	2x7.5		30.0	94			3,290.00
CB2 - 2CP 32/210A	KC2CT3530AA	2x7.5	2x10	IE3	30.0	112	4"	3"	3,400.00
CB2 - 2CP 40/180C	KC2CT3830CA	2x4	2x5.5		42.0	64			4,000.00
CB2 - 2CP 40/180B	KC2CT3930BA	2x5.5	2x7.5		48.0	76			4,060.00
CB2 - 2CP 40/180A	KC2CT4030AA	2x7.5	2x10		48.0	88	DN 100	DN 80	4,150.00

* Maximum flow rate of the pressure boosting set with both pumps running

▲ Three phase motor efficiency class (IEC 60034-30-1)



CB2 - MK



CB2 - CR



CB2 - 2CP



CB2 - 2CP



COMPONENTS EASYPUMP - EP 1:

- Single-phase pump
- **EASYPRESS-1M** with pressure gauge
- GSR quick-fit joint
- 1.5 metres power cable with Schuko plug

EASYPUMP-EP 1

PUMPS WITH ELECTRONIC PRESSURE REGULATOR

MODEL		POWER (P ₂)		PRICE
Single-phase	Code	kW	HP	€
PKm 60 - EP 1	K61PNK60A1	0.37	0.50	202.00
PKm 65 - EP 1	K61PNK67A1	0.50	0.70	219.00
3CPm 80 - EP 1	K63CPN382A1	0.45	0.60	280.00
4CPm 80 - EP 1	K63CPN283A1	0.55	0.75	298.00
3CPm 100 - EP 1	K63CPN384A1	0.55	0.75	295.00
4CPm 100 - EP 1	K63CPN286A1	0.75	1	329.00
3CRm 80 - EP 1	K63CR08D3A1	0.45	0.60	298.00
4CRm 80 - EP 1	K63CR08D4A1	0.55	0.75	314.00
5CRm 80 - EP 1	K63CR0805A1	0.75	1	353.00
3CRm 100 - EP 1	K63CR10D3A1	0.55	0.75	310.00
4CRm 100 - EP 1	K63CR10D4A1	0.75	1	349.00
JSWm 1B - EP 1	K66JSN1BA1	0.48	0.65	272.00
JSWm 1A - EP 1	K66JSN1AA1	0.55	0.75	281.00
JSWm 2C - EP 1	K66JSN7A10A1	0.75	1	296.00
JSWm 2CL - EP 1	K66JSN7AL10A1	0.75	1	299.00
JSWm 2B - EP 1	K66JSN7A12A1	0.90	1.25	309.00
JSWm 2CX - EP 1	K66JSNP7A10A1	0.75	1	286.00
JSWm 2BX - EP 1	K66JSNP7A12A1	0.90	1.25	298.00
PLURIJETm 3/60X - EP 1	K63PJA6053A1	0.37	0.50	304.00
PLURIJETm 3/80X - EP 1	K63PJA6063A1	0.48	0.65	309.00
PLURIJETm 4/80X - EP 1	K63PJA6084A1	0.55	0.75	320.00
PLURIJETm 3/100X - EP 1	K63PJA6083A1	0.55	0.75	320.00
PLURIJETm 4/100X - EP 1	K63PJA5104A1	0.75	1	361.00

EASYPUMP-EP 2

PUMPS WITH ELECTRONIC PRESSURE REGULATOR

MODEL		POWER (P ₂)		PRICE
Single-phase		kW	HP	€
2CPm 25/14B - EP 2	K652CM2616BA1	1.1	1.5	490.00
JSWm 2A - EP 2	K66JSN7A15A1	1.1	1.5	315.00
PLURIJETm 5/90X - EP 2	K63PJB25058A1	1.1	1.5	635.00
PLURIJETm 3/130X - EP 2	K63PJC15038A1	1.1	1.5	592.00
PLURIJETm 3/200X - EP 2	K63PJD15038A1	1.1	1.5	592.00



COMPONENTS EASYPUMP - EP 2:

- Single-phase pump
- **EASYPRESS-2M** with pressure gauge
- GSR quick-fit joint
- 1.5 metres power cable with Schuko plug

EASYPUMP Small pumps fitted with an electronic pressure switch that starts and stops the pump as required when a tap is turned on or off. The pump is also protected against dry running.

ELECTRONIC PRESSURE REGULATORS

MODEL	CODE	Power (P ₂)		Volt	Hz	Current	Fittings	PRICE € each			
		kW	HP					1 pcs.	5 pcs.	10 pcs.	25 pcs.
EASYSMALL-1 Without pressure gauge	50066/315	0.75	1	230	50/60	12 A	1" x 1"	52.00	50.50	50.00	49.50
EASYSMALL-1M With pressure gauge	50066/315P							57.00	56.00	55.00	54.50
EASYSMALL-2 Without pressure gauge	50066/415	1.5	2	230	50/60	16 A	1" x 1"	54.00	52.50	52.00	51.00
EASYSMALL-2M With pressure gauge	50066/415P							59.00	58.00	56.50	56.00

- Registered EU Design n. 001774928
- Registered trade mark n. 0001511131 EASYSMALL®
- ⇒ Pump start pressure EASYSMALL: 1.5 bar
- ⇒ Maximum flow rate: 12 m³/h

Spare electronic card and cover for EASYSMALL-1 (code 500699CS60) € 36.00

Spare electronic card and cover for EASYSMALL-2 (code 500699CS65) € 37.00

VASO D'ACCUMULO

MODEL	CODE	Fitting	Capacity	Pre-set	PRICE €
ES-05	500668	1" M	0.5 litres	1 bar	17.00

- To avoid repeated starts and to save energy, we recommend that EASYSMALL is installed with a small pressure vessel

MODEL	CODE	Power (P ₂)		Volt	Hz	Current	Fittings	PRICE € each			
		kW	HP					1 pcs.	5 pcs.	10 pcs.	25 pcs.
EASYPRESS-1 Without pressure gauge	50066/115	0.75	1	230	50/60	10 A	1" x 1"	74.50	73.50	72.50	71.50
EASYPRESS-1M With pressure gauge	50066/115P							77.50	76.50	75.50	74.50
EASYPRESS-2 Without pressure gauge	50066/215	1.5	2	230	50/60	16 A	1" x 1"	76.00	75.00	74.00	73.00
EASYPRESS-2M With pressure gauge	50066/215P							79.00	78.00	77.00	76.50

- Registered EU Design n. 868062
- Patent n. IT 1388969, IT 1388970
- Registered trade mark n. 0001334481 EASYPRESS®
- ⇒ EASYPRESS start-up pressure: 1.5 bar. 0.8 bar or 2.2 bar setting available on request
- ⇒ Maximum flow rate: 12 m³/h

Spare electronic card for EASYPRESS-1 (code 50066/115SB) € 32.00

Spare electronic card for EASYPRESS-2 (code 50066/215SB) € 32.00

MODEL	CODE	Power (P ₂)		Volt	Hz	Current	Fittings	PRICE €
EASYPRO	50068/201	1.5	2	230	50/60	16 A	1" x 1"	150.00

- Registered EU Design n. 976824
- Patent n. IT 1388969, IT 1388970
- Registered trade mark n. 0001334546 EASYPRO®
- ⇒ EASYPRO permits the selection of a pump start-up pressure within the range of 1 and 5 bar.
- ⇒ EASYPRO is fitted with a digital pressure gauge, 3 litre surge tank and amperometric protection of the pump.
- ⇒ Maximum flow rate: 12 m³/h

Spare electronic card for EASYPRO (code 50068/201SE) € 87.00

QUICK FIT JOINT

GSR	Code 5006991	Fitting 1" M	€ 10.50
-----	--------------	--------------	---------

Electronic devices that start (when a tap is turned on) and stop (when the tap is turned off) single-phase pumps. All models guarantee the protection of the pump against dry running in the event of a lack of water and the automatic restart of the pump when water returns.



SF SPHERICAL TANK

MODEL	CODE	FITTING	CAPACITY	PRICE € each			
				1 pcs.	5 pcs.	10 pcs.	20 pcs.
24 SF	50011	1"	24 litres	29.50	29.00	28.50	28.00
Diaphragm	50019						€ 13.50

- Maximum working pressure 8 bar
- Replaceable butyl rubber diaphragm



CL CYLINDRICAL TANKS

MODEL	CODE	FITTING	CAPACITY	PRICE € each			
				1 pcs.	5 pcs.	10 pcs.	20 pcs.
24 CL	50012	1"	20 litres	35.00	34.00	33.50	32.50
60 CL	50031	1"	60 litres	116.00	–	–	–
100 CL	50032	1"	100 litres	196.00	–	–	–
200 CL	50033	1½"	200 litres	368.00	–	–	–
300 CL	50034	1½"	300 litres	480.00	–	–	–

Diaphragm	24 CL	60 CL	100 CL	200 CL	300 CL
CODE	50019	5001960	50019100	50019200C	50019300
PRICE €	13.50	49.00	79.00	134.00	178.00

- Maximum working pressure 10 bar
- Replaceable butyl rubber diaphragm



VT VERTICAL TANKS

MODEL	CODE	FITTING	CAPACITY	PRICE € each		
				1 pcs.	5 pcs.	10 pcs.
05 VT	500668/2P	½"	0.5 litres	19.00	–	–
8 VT	50051	1"	8 litres	27.50	27.00	26.50
19 VT	50052	1"	19 litres	33.50	33.00	32.00
60 VT	50040	1"	60 litres	116.00	–	–
100 VT	50041	1"	100 litres	196.00	–	–
200 VT	50042	1½"	200 litres	368.00	–	–
300 VT	50043	1½"	300 litres	480.00	–	–
500 VT	50044	1½"	500 litres	825.00	–	–

Diaphragm	8 VT	19 VT	60 VT	100 VT	200 VT	300 VT	500 VT
CODE	5001905/8	50019	5001960	50019100	50019200C	50019300	50019500
PRICE €	9.00	13.50	49.00	79.00	134.00	178.00	330.00

- Maximum working pressure 10 bar (8 bar for 8 VT and 19 VT)

SPHERICAL KIT



KSP-24

MODEL	CODE	PRICE € each			
		1 pcs.	5 pcs.	10 pcs.	20 pcs.
KSP-24 • 24 litres spherical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Pressure switch "PSG-1"	50008SP24	50.60	49.50	49.00	48.00
KSD-24 • 24 litres spherical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Pressure switch "FSG2"	50010	55.60	54.50	54.00	53.00

CYLINDRICAL KIT



KCP-24

MODEL	CODE	PRICE € each			
		1 pcs.	5 pcs.	10 pcs.	20 pcs.
KCP-24 • 20 litres cylindrical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Hose 1" gas (500 mm) • Pressure switch "PSG-1"	50008CP24	66.80	64.00	63.00	62.00
KCD-24 • 20 litres cylindrical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Hose 1" gas (500 mm) • Pressure switch "FSG2"	50009	71.80	69.00	68.00	67.00



KCP-60

MODEL	CODE	PRICE € each		
		1 pcs.	5 pcs.	10 pcs.
KCP-60 • 60 litres cylindrical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Hose 1" gas (600 mm) • Pressure switch "PSG-1"	50008CP60	149.80	144.00	141.00
KCD-60 • 60 litres cylindrical tank • 0 – 6 bar pressure gauge • 5-way fitting - 1" G • Hose 1" gas (600 mm) • Pressure switch "FSG2"	50009/67	154.80	152.00	149.00



AIRFLO AUTOMATIC AIR FEEDERS FOR SURGE TANKS

MODEL	CODE	SUITABLE FOR TANKS	PRICE €
AIRFLO 1	50021	100 – 500 litres	47.00
AIRFLO 2	50022	750 – 2000 litres	76.00

• Air feeders suitable for maintaining the air cushion in surge tanks without a diaphragm.

NA - WAY NIPPLE FOR AIR FEEDERS

MODEL	CODE	FITTING	DOUBLE CENTRAL FITTING	PRICE €
NA 1.00	50023	1" x 1"	1/2" x 1/4" (male/female)	13.00
NA 1.25	50023/1	1 1/4" x 1 1/4"	1/2" x 1/4" (male/female)	19.00
NA 1.50	50023/2	1 1/2" x 1 1/2"	1/2" x 1/4" (male/female)	24.00
NA 2.00	50023/3	2" x 2"	1/2" x 1/4" (male/female)	29.00

• 3-way brass fittings for connections with air feeders (AIRFLO)

ACCESSORIES FOR SUBMERSIBLE PUMPS



MODEL	CODE	ROPE DIAMETER	ROPE WEIGHT	MAXIMUM LOAD	PRICE € per metre
SECURITY ROPE (in polypropylene)	116310	Ø 8 mm	30 g/m	960 kg	0.55
	116311	Ø 10 mm	45 g/m	1425 kg	0.75
	116312	Ø 12 mm	65 g/m	2030 kg	1.20
	116313	Ø 14 mm	90 g/m	2790 kg	1.60
	116314	Ø 16 mm	115 g/m	3500 kg	2.10

- Twisted rope in UV stabilized polypropylene threads
- Maximum length available per roll: 220 metres



SECURITY ROPE (in AISI 316 stainless steel)	116305	Ø 5 mm	100 g/m	1500 kg	€3.00 per metre
--	--------	--------	---------	---------	------------------------

- 49-core rope in AISI 316 stainless steel
- Maximum length available per roll: 250 metres



MODEL	CODE	PRICE €
STRAIGHT SHACKLE WITH PIN (for 8 mm wire rope) (in AISI 316 stainless steel)	1160305	3.40

5 mm WIRE ROPE CLAMP (in AISI 316 stainless steel)	1160304	2.10
---	---------	-------------

FLOAT SWITCHES



MODEL	CODE		LENGTH	PRICE € each			
	CABLE H07 RN-F	CABLE PVC		H07 RN-F 1 pcs.	1 pcs.	PVC 5 pcs.	10 pcs.
0315/3	50014H	50014	3 metres	20.50	15.80	14.80	14.30
0315/5	500145H	500145	5 metres	27.50	19.00	18.50	18.00
0315/10	5001410H	5001410	10 metres	39.80	25.00	–	–

- With **H07 RN-F** cable: single function (emptying) floats, with 10 A switch
- With **PVC** cable: dual function (emptying and filling) floats, with 10 A switch



T 80/3	50014/1H	50014/1	3 metres	24.50	17.80	17.30	16.80
T 80/5	50014/5H	50014/5	5 metres	29.60	21.00	20.50	20.00
T 80/10	50014/10H	50014/10	10 metres	42.80	27.00	–	–

- With **H07 RN-F** cable: single function (emptying) floats, with double watertight protection chamber and 10 A switch
- With **PVC** cable: dual function (emptying and filling) floats, double watertight protection chamber and 10 A switch



SMALL 3	50014S4	ASS50014S3	3 metres	21.00	17.30	16.80	16.30
SMALL 5	50014S5	50014S51	5 metres	27.00	20.00	19.50	19.00

- With **H07 RN-F** cable: single function (emptying) floats, with double watertight protection chamber and 10 A switch
- With **PVC** cable: dual function (emptying and filling) floats, double watertight protection chamber and 10 A switch



MODEL	CODE	CAVO	LENGTH	PRICE €
MAC 5	54SARGL001	PVC	10 metres	65.00

- Tilting float: dual function (emptying and filling), double watertight protection chamber with 10 A switch
- Recommended for use with waste water collection stations (SAR)



MT 1 FLOW METER

MODEL	CODE	MAXIMUM FLOW RATE	MAXIMUM PRESSURE	FITTINGS	PRICE €
MT 1	504550	120 l/min	3.5 bar	1" x 1"	130.00

- Mechanical flow meter for private use, suitable for: diesel, kerosene (for heating), solvents, antifreeze, very light oils (kinematic viscosity max. 300 cSt)
Attention: IT IS NOT SUITABLE for all the others fluids, including water, petrol/gasoline and hydro-chloric acid.

➔ Recommended for use with "CK" series pumps



NZ DISPENSING NOZZLE WITH HOSE

MODEL	CODE	ELBOW CONNECTION	PRICE €
NZ-1	50430B	3/4"	64.00
NZ-2	50430A	1"	64.00

- Aluminium dispensing nozzle complete with 4 metres long hose, with threaded fittings

➔ Recommended for use with CKm 50-BP or CK 50-BP series pumps



PSG



FSG

PRESSURE SWITCHES

MODEL	CODE	FITTING	STANDARD SETTING ADJUSTABLE	PRICE € each			
				1 pcs.	46 pcs.	92 pcs.	184 pcs.
PSG-1	50018/8	1/4" female	1.4 – 2.8 bar	10.50	10.00	9.50	9.00
PSG-1M	50018/8M	1/4" male	1.4 – 2.8 bar	10.50	10.00	9.50	9.00
FSG 2	50018	1/4" female	1.4 – 2.8 bar	15.50	15.20	14.70	–
FYG 22	50018/1	1/4" female	5.4 – 7.0 bar	25.50	25.00	24.50	–
FYG 32	50018/2	1/4" female	8 – 10.5 bar	26.00	25.50	25.00	–
PT/5 SK ⁽¹⁾	50018/8T	1/4" female	1.4 – 2.8 bar	14.00	13.50	–	–

- Registered EU Design n. 002248955 PSG

⁽¹⁾ Three-phase



MC



MR



MCG



MRG

PRESSURE GAUGES

MODEL	CODE	FITTING	Ø mm	SCALE	PRICE € each		
					1 pcs.	10 pcs.	50 pcs.
MC 6	50015/2	1/4" - central	50	0 – 6 bar	3.80	3.50	3.30
MR 6	50015	1/4" - radial	63	0 – 6 bar	3.80	3.50	3.30
MR 10	50015/0	1/4" - radial	63	0 – 10 bar	3.80	3.50	3.30

GLYCERINE FILLED PRESSURE GAUGES

MODEL	CODE	FITTING	Ø mm	SCALE	PRICE € each
MCG 6	50015/2G	1/4" - central	50	0 – 6 bar	13.50
MRG 6	50015G	1/4" - radial	63	0 – 6 bar	13.50
MRG 10	50015/0G	1/4" - radial	63	0 – 10 bar	13.50



R 3



R 4



R 5

3 - 5 WAY FITTINGS

MODEL	CODE	FITTING	PRICE € each			
			1 pcs.	10 pcs.	20 pcs.	50 pcs.
R 3 - 3 vie	50017	1"	6.50	6.00	5.50	5.30
R 4 - 4 vie	50016V8	1"	8.20	7.60	7.40	7.20
R 5 - 5 vie	50016	1"	6.80	6.10	5.60	5.40

- R 3: three-way brass fittings with 1" gas connections
- R 4: four-way brass fittings with 1/2" gas and 1/4" gas connections
- R 5: five-way brass fittings with 1" gas and 1/4" gas connections

HOSES

MODEL	CODE	PIPE	FITTINGS	LENGTH	PRICE € each					
					1 pcs.	5 pcs.	10 pcs.	20 pcs.	50 pcs.	100 pcs.
TF 5	50013	1"	1" x 1"	500 mm	11.70	11.20	10.70	10.20	10.00	9.80
TF 6	50013/1	1"	1" x 1"	600 mm	12.30	11.80	11.30	10.80	10.50	10.30
TF 10	50013/6	1"	1" x 1"	1000 mm	15.30	14.80	14.30	13.80	13.50	13.20

HOSES COMPLETE WITH ELBOW

MODEL	CODE	PIPE	FITTINGS	LENGTH	PRICE € each				
					1 pcs.	5 pcs.	10 pcs.	50 pcs.	100 pcs.
TFG 5	50013/01	3/4"	1" x 1"	500 mm	10.70	10.20	9.70	9.40	9.20
TFG 6	50013/10	1"	1" x 1"	600 mm	12.70	12.20	11.20	10.90	10.70

- Flexible EPDM rubber hoses
- Maximum working pressure 10 bar

FLEXIBLE HOSE FITTINGS

MODEL	CODE	Female Hose Fitting Diameter	Threaded Male Fitting	PRICE €
FASTFIT 1.25	5027125	Ø 32 mm	1 1/4"	23.50
FASTFIT 1.5	5027150	Ø 38 mm	1 1/2"	26.50
FASTFIT 2	5027200	Ø 50 mm	2"	25.50
FASTFIT 3	5027300	Ø 75 mm	3"	44.00

- Polypropylene flexible hose fittings kit:
 - n.1 female Hose Fitting
 - n.1 threaded male fitting

HOSETAIL FITTINGS

MODEL	CODE	HOSETAIL	THREADED FITTING	PRICE € each	
				1 pcs.	10 pcs.
RP 0.75	50210	Ø 25 mm	3/4"	2.30	1.90
RP 1	50211	Ø 30 mm	1"	2.60	2.20
RP 1.25	50212	Ø 35 mm	1 1/4"	3.50	3.00
RP 1.5	50213	Ø 40 mm	1 1/2"	3.70	3.40
RP 2	50214	Ø 50 mm	2"	5.50	5.20

MODEL	CODE	HOSETAIL	THREADED FITTING	PRICE € each	
				1 pcs.	10 pcs.
RPG 0.75	50220	Ø 25 mm	3/4"	2.80	2.50
RPG 1	50221	Ø 30 mm	1"	3.50	3.10
RPG 1.25	50222	Ø 35 mm	1 1/4"	5.00	4.60
RPG 1.5	50223	Ø 40 mm	1 1/2"	5.00	4.80
RPG 2	50224	Ø 50 mm	2"	7.50	7.30

- Nylon fittings

FLAT PVC HOSE



MODEL	CODE			FITTING	PRICE €		
	Lengths 5 metres	Lengths 10 metres	Lengths 20 metres		5 metres	10 metres	20 metres
TP 1.25	50013P125A	50013P125B	50013P125C	1¼"	33.00	52.00	89.00
TP 1.50	50013P150A	50013P150B	50013P150C	1½"	41.00	67.00	119.00
TP 2.00	50013P200A	50013P200B	50013P200C	2"	49.00	83.00	150.00
TP 2.50	50013P250A	50013P250B	50013P250C	2½"	116.00	158.00	247.00
TP 3.00	50013P300A	50013P300B	50013P300C	3"	133.00	187.00	293.00

- Flat, abrasion and weather resistant plasticized delivery hoses, complete with hosetail
- ➔ Ideal for irrigation even with fertilisers and for draining water in combination with DRAINAGE PUMPS



FLEXIBLE SUCTION HOSE

MODEL	CODE	FITTING	LENGTH	PRICE €
GARDEN KIT	50200	1"	7 metres	33.00

- Flexible hose complete with foot valve



VF FOOT VALVES

MODEL	CODE	FITTING	PRICE € each			
			1 pcs.	5 pcs.	10 pcs.	20 pcs.
VF 0.5	50100	½"	4.40	3.70	3.30	–
VF 0.75	50101	¾"	6.10	5.70	5.40	–
VF 1	50102	1"	8.50	8.10	7.70	7.50
VF 1.25	50103	1¼"	11.40	11.20	11.00	10.80
VF 1.5	50104	1½"	15.60	15.40	15.20	15.00
VF 2	50105	2"	25.00	24.60	24.30	24.00

- Brass foot valves, stainless steel suction filter



VR CHECK VALVES

MODEL	CODE	FITTINGS	PRICE € each			
			1 pcs.	5 pcs.	10 pcs.	20 pcs.
VR 0.5	50110	½"	4.10	3.80	3.60	3.50
VR 0.75	50111	¾"	6.70	6.30	5.90	5.70
VR 1	50112	1"	7.80	7.30	7.10	6.90
VR 1.25	50113	1¼"	13.00	12.60	12.40	12.20
VR 1.5	50114	1½"	15.90	15.70	15.50	15.30
VR 2	50115	2"	26.00	25.50	25.20	25.00

- Brass check valves



VR-FT



VR-FF

VR-FT / VR-FF BALL CHECK VALVES

MODEL	CODE	FITTINGS	PRICE €
VR-FT 1.25	501201	1¼"	60.00
VR-FT 1.5	501202	1½"	73.00
VR-FT 2	501203	2"	87.00
VR-FF/DN 65 - FLANGED	501210	DN 65 (PN16) 2½"	228.00
VR-FF/DN 80 - FLANGED	501212	DN 80 (PN16) 3"	296.00
VR-FF/DN 100 - FLANGED	501214	DN 100 (PN16) 4"	347.00

- Check valves for submersible pumps (sewage and waste water)
- Max. working pressure 16 bar
- Min. working pressure 0.3 bar
- Working temperature 0 °C ÷ +80 °C



SCHUKO PLUG WITH PROTECTION CASE

MODEL	CODE	PRICE €
PSC	117985	16.50

- Protection against water and dust with IP 65 or IP 67 grade protection
- Mechanical protection against tearing



POWER CABLE FOR LEVEL PROBES

MODEL	CODE	LENGTH	SECTION	WEIGHT PER METRE	PRICE €
CSL-100	117FE00C01	100 m	1.5 mm ²	1.9 kg	50.00
CSL-200	117FE00C02	200 m	1.5 mm ²	3.8 kg	100.00
CSL-500	117FE00C05	500 m	1.5 mm ²	9.5 kg	250.00
CSL-1500	117FE00C15	1500 m	1.5 mm ²	28.5 kg	750.00



POWER CABLES FOR SUBMERSIBLE PUMPS

MODEL	CODE	MODEL	WEIGHT PER METRE	PRICE € per metre
4 x 1 mm ²	117G100AN	H07 RN-F	0.165 kg	2.40
4 x 1.5 mm ²	117G150AN	H07 RN-F	0.205 kg	2.70
4 x 2.5 mm ²	117G200AN	H07 RN-F	0.290 kg	4.10
4 x 4 mm ²	117G250AN	H07 RN-F	0.420 kg	5.80
4 x 6 mm ²	117G300AN	H07 RN-F	0.505 kg	10.00
4 x 10 mm ²	117G350AN	H07 RN-F	1.030 kg	14.20
4 x 16 mm ²	117G400AN	H07 RN-F	2.050 kg	21.50



POWER CABLES WITH PLUG

MODEL	CODE	CABLE SECTION	LENGTH	PLUG	PRICE € each		
					1 pcs.	50 pcs.	100 pcs.
H05 VV-F (PVC)	117FGA21G	3 x 0.75 mm ²	150 cm	SCHUKO	3.20	3.00	2.80
H07 RN-F (NEOPRENE)	117GLA21G	3 x 1 mm ²	150 cm	SCHUKO	4.50	4.30	4.10



(RECOMMENDED)

POWER CABLE RESIN JOINT KIT

MODEL	CODE	NUMBER OF CORES	CABLE SECTION	EXTERNAL JUNCTION DIAMETER	PRICE € each	
					1 pcs.	5 pcs.
RPS 1	530GT3M82A1	4	1 - 2.5 mm ²	Ø 32 mm	41.00	40.00
RPS 2	530GT3M82A2	4	1 - 10 mm ²	Ø 42 mm	80.00	75.00
RPS 3	530GT3M92A1	4	4 - 16 mm ²	Ø 48 mm	69.00	67.00

⇒ Assembly cost for cable joint KIT if required

€ 43.00



(ECONOMIC)

POWER CABLE HEAT-SHRINK JOINT KIT

MODEL	CODE	NUMBER OF CORES	CABLE SECTION	PRICE € each	
				1 pcs.	5 pcs.
GPS 1	530GT3MGPS1	4	1 - 2.5 mm ²	18.00	17.00
GPS 2	530GT3MGPS2	4	4 - 6 mm ²	27.00	26.00
GPS 3	530GT3MGPS3	4	10 mm ²	33.00	32.00
GPS 4	530GT3MGPS4	4	16 mm ²	39.00	38.00
GPS 5	530GT3MGPS5	4	25 mm ²	43.00	42.00
GPS 6	530GT3MGPS6	4	35 mm ²	46.00	45.00

⇒ Assembly cost for cable joint KIT if required

€ 32.00



F - FILTER HOLDERS WITH PLASTIC HEAD

MODEL	CODE	THREADED FITTINGS	CARTRIDGE HEIGHT	PRICE €
MEDIUM - F 0.75	504F075M	¾"	5"	21.50
MEDIUM - F 1	504F100M	1"	5"	23.00
JUNIOR - F 0.75	504F075J	¾"	7"	23.00
JUNIOR - F 1	504F100J	1"	7"	23.00
SENIOR - F 0.75	504F075S	¾"	10"	23.00
SENIOR - F 1	504F100S	1"	10"	24.50

- Maximum working pressure 5 bar (at temperature +20°C)
- Maximum temperature + 45°C (at pressure 2 bar)



Kit for disassembly of filter holders F (code 504KNPP)

€ 4.60



RL - POLYESTER FILTER CARTRIDGES

MODEL	CODE	FILTRATION	CARTRIDGE HEIGHT	FILTER HOLDER	PRICE €
RL 5	504C05	50 µm	5"	MEDIUM-F	7.00
RL 7	504C07	50 µm	7"	JUNIOR-F	8.00
RL 10	504C10	50 µm	10"	SENIOR-F	9.90



FA - POLYPROPYLENE FILTER CARTRIDGES

MODEL	CODE	FILTRATION	CARTRIDGE HEIGHT	FILTER HOLDER	PRICE €
FA 5	504F05	50 µm	5"	MEDIUM-F	4.20
FA 7	504F07	50 µm	7"	JUNIOR-F	4.30
FA 10	504F10	50 µm	10"	SENIOR-F	4.50



HA - FILTER CARTRIDGE WITH POLYPHOSPHATE CRYSTALS

MODEL	CODE	CARTRIDGE HEIGHT	FILTER HOLDER	PRICE €
HA 10	504F08	10"	SENIOR-F	18.60



LA - FILTER CARTRIDGE WITH ACTIVATED CARBON

MODEL	CODE	CARTRIDGE HEIGHT	FILTER HOLDER	PRICE €
LA 10 BX	504LA10BX	10"	SENIOR-F	9.00



TEFLON TAPE FOR HYDRAULIC JOINTS

MODEL	CODE	LENGTH	WIDTH	PRICE € each	
				1 pcs.	100 pcs.
TFN 1	14TFN/1	12 m	12 mm	0.75	0.65
TFN 2	14TFN/21	30 m	12 mm	3.20	2.70
TFN 3	14TFN/3	12 m	19 mm	2.10	1.85



AEROSOL PAINT

MODEL	CODE	COLOUR	CAPACITY	PRICE €
SPRAY 1	120200A/2	Pedrollo blue	400 ml	14.00

BEARINGS FOR PUMPS AND ELECTRIC MOTORS

MODEL	CODE	DIMENSIONS	PRICE € each	
			1 pcs.	20 pcs.
6201 ZZ	113001	12 x 32 x 10 mm	1.60	1.40
6201 ZZ - C3E	113001C3E	12 x 32 x 10 mm	2.60	2.40
6201 2RS - C3	113001SC3E	12 x 32 x 10 mm	2.80	2.60
6202 ZZ - C3	113012	15 x 35 x 11 mm	2.40	2.20
6203	113002A	17 x 40 x 12 mm	2.40	2.20
6203 ZZ	113002	17 x 40 x 12 mm	2.00	1.80
6203 ZZ - C3E	113002C3E	17 x 40 x 12 mm	2.70	2.50
6203 2RS - C3E	113002RC3E	17 x 40 x 12 mm	3.60	3.40
6204 ZZ - C3	113003C3E	20 x 47 x 14 mm	3.40	3.20
6204 ZZ - C3E	113003	20 x 47 x 14 mm	3.40	3.20
6205 ZZ	113004	25 x 52 x 15 mm	4.40	4.20
6206 ZZ - C3	113005C3E	30 x 62 x 16 mm	7.70	7.50
			1 pcs.	10 pcs.
6208 ZZ - C3	113008	40 x 80 x 18 mm	17.50	15.50
6003 ZZ - C3	113010	17 x 35 x 10 mm	3.40	3.20
6212 ZZ - C3	113020	60 x 110 x 22 mm	37.00	35.00
6303 2RS - C3	113014SC3	17 x 47 x 14 mm	5.70	5.50
6304 ZZ	113013	20 x 52 x 15 mm	5.30	5.10
6304 ZZ - C3	113013C3E	20 x 52 x 15 mm	6.00	5.50
6304 2RS - C3	113013SC3	20 x 52 x 15 mm	6.90	6.70
6306 ZZ - C3	113015	30 x 72 x 19 mm	11.70	11.20
6307 ZZ - C3	113017	35 x 80 x 21 mm	16.00	15.00
6308 ZZ - C3	113018	40 x 90 x 23 mm	23.50	22.50
6309 ZZ - C3	1130185	45 x 100 x 25 mm	33.00	32.00
6310 ZZ - C3	113019	50 x 110 x 27 mm	42.00	40.00
6312 ZZ - C3	113021	60 x 130 x 31 mm	69.00	67.00
6313 ZZ - C3	113023	65 x 140 x 33 mm	84.00	82.00
6314 ZZ - C3	113024	70 x 150 x 35 mm	86.00	84.00
3203 B 2RS - C3	113040RC3E	17 x 40 x 17.5 mm	27.50	25.50
3304 B ZZ - C3	113041	20 x 52 x 22.2 mm	34.00	32.00
7202 B	113029	15 x 35 x 22.2 mm	8.00	7.50

FANS FOR PUMPS AND ELECTRIC MOTORS

MODEL	CODE	DIMENSIONS	SHAFT DIAMETER	PRICE €
FAN-63	14VN059	104 x 21 mm	12 mm	1.35
FAN-63/1	14VN067	99 x 22 mm	12 mm	1.35
FAN-63/2	14VN068	99 x 26 mm	12 mm	1.35
FAN-71R	14VN07	125 x 24 mm	14.5 mm	1.75
FAN-71	14VN076	114 x 20 mm	14.5 mm	1.75
FAN-71/1	14VN072	116 x 23 mm	14.5 mm	1.75
FAN-80R	14VN08	138 x 27 mm	20 mm	2.30
FAN-80	14VN081	132 x 27 mm	20 mm	2.30
FAN-80 IPX5	14VN0815	132 x 27 mm	20 mm	2.60
FAN-90R	14VN09	162 x 32 mm	24 mm	2.60
FAN-90	14VN095	148 x 33 mm	24 mm	3.50
FAN-100R	14VN10	176 x 38 mm	28 mm	6.00
FAN-100	14VN10162	155 x 37 mm	28 mm	5.50
FAN-132	14VN132	165 x 45 mm	36 mm	7.00
FAN-180	14VN180	240 x 60 mm	55 mm	9.50

CAPACITORS WITH FASTON CONNECTIONS



Type F

Capacitor with faston connections

MODEL	CODE	CAPACITY	VOLTAGE	PRICE € each	
				1 pcs.	10 pcs.
10 F	111010F	10 μ F	450 VL	2.10	1.60
10 FC*	111010FC	10 μ F	450 VL	2.20	1.70
12 F	111012F	12.5 μ F	450 VL	2.70	2.20
14 F	111014F	14 μ F	450 VL	2.80	2.30
16 F - 500	111016F5	16 μ F	500 VL	4.10	3.60
16 F - 450	111016F		450 VL	3.10	2.60
16 F - 250	112016F		250 VL	2.90	2.40
20 F - 500	111020F5	20 μ F	500 VL	4.40	3.90
20 F - 450	111020F		450 VL	3.50	3.00
25 F - 450	111025F	25 μ F	450 VL	4.30	3.80
25 F - 250	112025F		250 VL	3.60	3.10
30 F - 250	112030F	30 μ F	250 VL	5.10	4.60
31 F	111031F	31.5 μ F	450 VL	5.10	4.60
35 F	111035F	35 μ F	450 VL	5.90	5.40
35 FC*	111035F1	35 μ F	450 VL	6.10	5.60
40 F	111040F	40 μ F	450 VL	6.60	6.10
45 F	111045F	45 μ F	450 VL	7.10	6.10
50 F	111050F	50 μ F	450 VL	8.70	7.70
60 F - 450	111060F	60 μ F	450 VL	12.20	11.20
60 F - 300	112061F		300 VL	10.20	9.20
60 F - 250	112060F		250 VL	9.70	8.70
70 F	111070F	70 μ F	450 VL	12.20	11.20
80 F	112080F	80 μ F	250 VL	12.70	11.70
90 F	111090F	90 μ F	450 VL	17.30	16.30

* FC = Special capacitor with reduced dimensions

• Capacitors with CE marking and VDE-IMQ approval

CAPACITORS WITH CABLE CONNECTIONS



Type C

Capacitor with cable connections

MODEL	CODE	CAPACITY	VOLTAGE	PRICE € each	
				1 pcs.	5 pcs.
10 C	1110102F	10 μ F	450 VL	2.80	2.50
12 C	1110122F	12.5 μ F	450 VL	3.30	2.80
16 C - 500	1110162F5	16 μ F	500 VL	3.80	3.30
16 C - 450	1110162F		450 VL	3.60	3.10
20 C - 500	1110202F5	20 μ F	500 VL	4.60	4.10
20 C - 450	1110202F		450 VL	3.50	3.00
25 C - 450	1110252F	25 μ F	450 VL	4.70	4.20
30 C - 250	1120302F	30 μ F	250 VL	5.00	4.50
31 C - 500	1110312F5	31.5 μ F	500 VL	5.90	5.40
31 C - 450	1110312F		450 VL	5.60	5.10
35 C - 500	1110352F5	35 μ F	500 VL	7.70	6.70
35 C - 450	1110352F		450 VL	6.60	5.60
35 CC* - 450	1110352F1	35 μ F	450 VL	6.70	5.70
40 C	1110402F	40 μ F	450 VL	7.00	6.00
50 C	1110502F	50 μ F	450 VL	9.50	8.50
60 C	1120602F	60 μ F	250 VL	12.50	11.50
70 C - 450	1110702F	70 μ F	450 VL	14.00	13.00
70 C - 250	1120702F5	70 μ F	250 VL	13.50	12.50
75 C	1110752F	75 μ F	450 VL	14.50	13.50
80 C	1120802F	80 μ F	250 VL	15.50	14.50

* CC = Special capacitor with reduced dimensions

• Capacitors with CE marking and VDE-IMQ approval

CAPACITORS WITH DECOUPLER



MODEL	CODE	CAPACITY	VOLTAGE	PRICE € each	
				1 pcs.	5 pcs.
80 D	111080D2F	80 μ F	320-480 VL	49.00	47.00

• Capacitor for submersible pumps with grinder (TRITUS)



AR



ST1



FN, FH

MECHANICAL SEALS FOR SURFACE PUMPS

MODEL	CODE	PUMP	MATERIALS				SHAFT	PRICE € each	
			Fixed ring	Rotating ring	Elastomer	Spring		1 pcs.	10 pcs.
AR-12	115161012012	PK60-65-70-80, PQ60-65-70-80, PKS60-65-70-80, PQ60-EKO, CP100-130-132, CP100-130-132 ST4, JSW1, JCR1, HF50	Ceramic	Graphite	NBR	AISI304	Ø 12 mm	3.40	3.00
AR-12 ST6	11516101214	CP100-130-132 ST6				AISI316	Ø 12 mm	3.70	3.30
AR-12V	11516101203	CK, CKR			VITON	AISI304	Ø 12 mm	5.60	5.20
AR-13	11516101301	2-5CR, 2-4CP, PLURIJET/60-80-100, DG PED, TS1-4CP 100, TS1-4/5CR 100			HNBR		Ø 13 mm	3.60	3.10
AR-14	11516121401	CP150-158, CP150-158 ST4, 2CP25/130, JSW2, JCR2, NGA, TS1-2CP 25/130, HF4-5-51			NBR		Ø 14 mm	3.70	3.30
AR-14 ST6	11516121404	CP150-158 ST6				AISI316	Ø 14 mm	4.60	4.10
AR-14S	11516141402	NGA-PRO			VITON		Ø 14 mm	13.00	12.00
ST1-12	11516471200	PK90, PQ90, PQ60-65-70-81-90 PRO, PQ60-65-81 Bs, PQA, PV	Silicon carbide	Ceramic	NBR	AISI316	Ø 12 mm	22.00	20.00
FN-14	11516301401	PK100-200-300, PQ100-200-300, PQ100-200-300 PRO	Graphite				Ø 14 mm	5.50	5.00
								1 pcs.	5 pcs.
FN-18	11516301801	CP160-170-170M-190-200, CP170-170M-180-190-200 ST4, MK, 3-7CR, 2CP25/14, 2CP25/16, JSW3, SKR, PLURIJET/90-130-200, TS1-2CP 25/14-16, TS2, HF5M-6-70	Graphite	Ceramic	NBR	AISI316	Ø 18 mm	6.50	6.00
FN-18 ST6	11516301810	CP170-170M-180-190-200 ST6					Ø 18 mm	7.50	6.50
FN-18 NU	11516301821	PQ3000, PQ3000-MF					Ø 18 mm	11.00	10.00
FN-20	11516302001	CP220B-C, CP230C, 2CP32/200, HF8-20, F-F4 32/160, F 40/125, F-F4 40/160, F-F4 50/125	Graphite	Ceramic	VITON		Ø 20 mm	7.50	7.00
FN-20 NUD	11516302030	FG32/160, FG40/125, FG40/160, FG50/125					Ø 20 mm	29.50	27.50
FN-24	11516302401	CP210, CP220A-AH, CP230B-A, CP250B, 2CP32/210, 2CP40/180, HF30, F-F4 32/200, F-F4 40/200, F-F4 50/160, F-F4 65/125					Ø 24 mm	10.00	9.00
FN-24 NUD	11516302430	FG32/200, FG40/200, FG50/160, FG65/125	Graphite	Silicon carbide	Ø 24 mm		37.00	35.00	
FN-24 SV	11516302408	F-INOX	Silicon carbide	Silicon carbide	Ø 24 mm		97.00	92.00	
FN-32 NU	11516303220	CP250A, 2CP40/200, F-F4 50/200, F-F4 65/160, F-F4 65/200, F-F4 80/160, F-F4 100/160	Graphite	Ceramic	NBR		Ø 32 mm	31.00	29.00
FN-32 NUD	11516303230	FG50/200, FG65/160, FG65/200, FG80/160, FG100/160					Ø 32 mm	51.00	49.00
FN-35 NUD	11516303530	FG32/250, FG40/250, FG50/250					Ø 35 mm	63.00	61.00
FN-38	11516803801	F-F4 32/250, F-F4 40/250, F-F4 50/250					Ø 38 mm	51.00	49.00
FN-40 NU	11516314010	F-F4 65/250, F-F4 80/200, F 80/250B, F-F4 100/200, FG80/200, FG 100/200					Ø 40 mm	70.00	66.00
FH-43 NU	11516314300	FG65/250, FG80/250, FG100/250					Ø 43 mm	255.00	252.00
FH-45 NU	11516314500	F 80/250A, F4 80/250, F-F4 100/250					Ø 45 mm	230.00	225.00

➡ Special mechanical seals available on request

ACCESSORIES



AR, STA



ST1, MG1



MG1-D, ED560



ST4

MECHANICAL SEALS FOR SUBMERSIBLE PUMPS

MODEL	CODE	PUMP	MATERIALS				SHAFT	PRICE € each	
			Fixed ring	Rotating ring	Elastomer	Spring		1 pcs.	10 pcs.
STA-12R	11516101250	TOP MULTI 1, TOP1-2-3, TOP FLOOR, TOP VORTEX, TEX, RX1-2-3, ZX1	Ceramic	Graphite	NBR	AISI304	Ø 12 mm	3.80	3.30
STA-12R SIC	11516101248	RX2-3/20	Ceramic	Silicon carbide		AISI304	Ø 12 mm	11.00	10.00
STA-12R SGE	11516101244	TOP MULTI 1-AD	Silicon carbide	Graphite	EPDM	AISI304	Ø 12 mm	11.00	10.00
STA-12R SG	11516101247	TOP MULTI 2-3, TOP MULTI 2-3 EVO, TOP MULTI-TECH 2-3, TOP MULTI-EVOTECH 2-3	Silicon carbide	Graphite	NBR	AISI304	Ø 12 mm	7.50	6.50
STA-13R	11516101313	TOP MULTI 2-3, TOP MULTI 2-3 EVO, TOP MULTI-TECH 2-3, TOP MULTI-EVOTECH 2-3	Ceramic	Graphite		AISI304	Ø 13 mm	3.80	3.30
AR-12R LA	11516101245	TOP 2-3LA, TOP FLOOR/LA	Ceramic	Graphite		AISI316	Ø 12 mm	4.90	4.40
AR-14	11516121401	DAVIS	Ceramic	Graphite		AISI304	Ø 14 mm	3.70	3.30
ST1-14 SIC	11516151002	DAVIS, D30, DC30	Ceramic	Silicon carbide		AISI316	Ø 14 mm	13.00	12.00
MG1-14D SIC	11516152000	TOP4-5, RX4-5, RX 4-5/40, VX-ST, BC-ST, VX-MF, BC-MF, D8-10-20, ZX2, VX8-10-15/35-50, BC10-15/50, VXC/35-45, MC/45, DC8-10-20, TR0.75-0.9-1.1-1.3	Silicon carbide - Silicon carbide	Graphite - Silicon carbide		AISI316	Ø 14 mm	27.50	25.50
ST1-16	11516521600	FLUID SOLAR, 4BLOCK, UP, NK	Silicon carbide	Graphite	NBR	AISI316	Ø 16 mm	12.50	11.50
STA-17	11516201705	FLUID SOLAR, 4BLOCK, UP, NK	Ceramic	Graphite		AISI316	Ø 17 mm	8.50	8.00
STA-19	11516601901	TR1.5-2.2, VXC/50-70, MC/50-70, VXC-F/50-70, MC-F/50-70	Silicon carbide	Silicon carbide		AISI304	Ø 19 mm	30.50	28.50
STA-20	11516602000	TR1.5-2.2, VXC/50-70, MC/50-70, VXC-F/50-70, MC-F/50-70	Ceramic	Graphite		AISI304	Ø 20 mm	11.00	10.00
ED560-25	11516172501	VX40-55/40, VX40-55/50	Silicon carbide - Silicon carbide	Graphite - Silicon carbide		AISI304	Ø 25 mm	122.00	117.00
AR-25	11516122501	VX/65, BC/35	Silicon carbide	Silicon carbide		AISI304	Ø 25 mm	90.00	85.00
AR-27	11516122701	VX/65, BC/35	Silicon carbide	Graphite		AISI304	Ø 27 mm	29.50	27.50
AR-35	5FAR5413327	VXC4/80-90 MC4/80	Ceramic	Graphite		AISI304	Ø 35 mm	70.00	65.00
ST4-16	5PMR0700815	4PD	Ceramic	Graphite		AISI316	Ø 16 mm	8.50	8.00
ST4-25	5PMR0600804	6PD	Ceramic	Graphite		AISI304	Ø 25.4 mm	50.00	48.00
MG91-40D	11516174001	VXC4 40-50-55/100, MC4 40-50-55/55	Ceramic - Silicon carbide	Graphite - Silicon carbide		AISI304	Ø 40 mm	350.00	340.00
MG1-40	5FAR5413448	VXC4/80-90 MC4/80	Silicon carbide	Silicon carbide		AISI316	Ø 40 mm	112.00	107.00

➡ Special mechanical seals available on request



QEM/3 Control boxes for 3" single-phase submersible pumps

MODEL	CODE	MOTOR POWER (P ₂)		CAPACITOR CAPACITY	RATED CURRENT A	PRICE €
		kW	HP			
Single-phase						
QEM/3-050	530ECS305A1	0.37	0.50	12.5 µF	5	42.50
QEM/3-075	530ECS307A1	0.55	0.75	16 µF	6	42.50
QEM/3-100	530ECS310A1	0.75	1	20 µF	7	42.50

- Single-phase 230 V 50 Hz



QEM Control boxes for 4" single-phase submersible pumps

MODEL	CODE	MOTOR POWER (P ₂)		CAPACITOR CAPACITY	RATED CURRENT A	PRICE €
		kW	HP			
Single-phase						
QEM 050	530ECN05A1	0.37	0.50	20 µF	5	42.50
QEM 075	530ECN07A1	0.55	0.75	25 µF	6	42.50
QEM 100	530ECN10A1	0.75	1	35 µF	7	42.50
QEM 150	530EC15A1	1.1	1.5	40 µF	11	42.50
QEM 200	530ECN20A1	1.5	2	60 µF	13	42.50
QEM 300	530EC30A1	2.2	3	75 µF	18	52.00

- Single-phase 230 V 50 Hz



QET Control boxes for 4" and 6" three-phase submersible pumps

MODEL	CODE	MOTOR POWER (P ₂)		RATED CURRENT A	PRICE €
		kW	HP		
Three-phase					
QET 050	530TNF05A	0.37	0.50	1.7	143.50
QET 075	530TNF07A	0.55	0.75	2	143.50
QET 100	530TNF10A	0.75	1	2.5	143.50
QET 150	530TNF15A	1.1	1.5	3.9	143.50
QET 200	530TNF20A	1.5	2	4.8	143.50
QET 300	530TNF30A	2.2	3	7	143.50
QET 400	530TNF40A	3	4	9	143.50
QET 550	530TNF55A	4	5.5	11.5	143.50
QET 750	530TNF75A	5.5	7.5	15.5	153.00
QET 1000	530AD100A	7.5	10	21.5	302.00
QET 1250	530AD125A	9.2	12.5	23.5	335.00
QET 1500	530AD150A	11	15	27.5	436.00
QET 2000	530AD200A	15	20	36	514.00
QET 2500	530AD250A	18.5	25	45	587.00
QET 3000	530AD300A	22	30	54	587.00
QET 4000	530AD400A	30	40	68	770.00
QET 5000	530AD500A	37	50	85	955.00

- The control box has a selector for manual or automatic operation plus socket for float switch (or pressure switch, etc.).
- Three-phase 400 V 50 Hz



Level probes

QSM Control boxes for 4" single-phase pumps with level probes

MODEL	CODE	MOTOR POWER (P ₂)		CAPACITOR	RATED CURRENT	PRICE
Single-phase		kW	HP	CAPACITY	A	€
QSM 050	530MFLCN05A1	0.37	0.50	20 μF	5	184.00
QSM 075	530MFLCN07A1	0.55	0.75	25 μF	6	184.00
QSM 100	530MFLCN10A1	0.75	1	35 μF	7	184.00
QSM 150	530MFLC15A1	1.1	1.5	40 μF	11	184.00
QSM 200	530MFLCN20A1	1.5	2	60 μF	13	196.00
QSM 300	530MFLC30A1	2.2	3	75 μF	18	306.00

- The control box is equipped with a selector for manual or automatic operation (with float switch, pressure switch, etc.) and may be connected to level probes that protect the pump against dry running.
- **Single-phase 230 V 50 Hz**



Level probes

QST Control boxes for 4" and 6" three-phase pumps with level probes

MODEL	CODE	MOTOR POWER (P ₂)		RATED CURRENT	PRICE
Three-phase		kW	HP	A	€
QST 50	530TFLC05A	0.37	0.50	1.7	293.00
QST 75	530TFLC07A	0.55	0.75	2	293.00
QST 100	530TFLC10A	0.75	1	2.5	293.00
QST 150	530TFLC15A	1.1	1.5	3.9	293.00
QST 200	530TFLC20A	1.5	2	4.8	293.00
QST 300	530TFLC30A	2.2	3	7	293.00
QST 400	530TFLC40A	3	4	9	293.00
QST 550	530TFLC55A	4	5.5	11.5	293.00
QST 750	530TFLC75A	5.5	7.5	15.5	310.00
QST 1000	530ADL100A	7.5	10	21.5	451.00
QST 1250	530ADL125A	9.2	12.5	23.5	490.00
QST 1500	530ADL150A	11	15	27.5	538.00
QST 2000	530ADL200A	15	20	36	695.00
QST 2500	530ADL250A	18.5	25	45	773.00
QST 3000	530ADL300A	22	30	54	809.00
QST 4000	530ADL400A	30	40	68	940.00
QST 5000	530ADL500A	37	50	85	1,085.00

- The control box is equipped with a selector for manual or automatic operation (with float switch, pressure switch, etc.) and may be connected to level probes that protect the pump against dry running.
- **Three-phase 400 V 50 Hz**



EVOLUTION Electronic control box for submersible pumps

MODEL	CODE	VOLTAGE	RATED CURRENT A	PRICE €
EVOLUTION-MONO	532DOM003M	single-phase 230V 50 Hz	from 2 to 18	218.00
EVOLUTION-TRI/1	532DOM075T	three-phase 400V 50 Hz	from 2 to 16	296.00
EVOLUTION-TRI/2	532DOM100T	three-phase 400V 50 Hz	from 16 to 22	330.00

- The control box contains a circuit board that makes it possible to adjust the limit at which the overload and shortcircuit protection intervenes; the circuit board also protects the pump against dry running by controlling the cos ϕ value without additional level probes.
- The control box may be connected to a float switch (or a pressure switch, etc.).

Spare electronic card for EVOLUTION-MONO (code 532DSC003M) € 165.00

Spare electronic card for EVOLUTION-TRI/1 (code 532DSC075T) € 165.00

Spare electronic card for EVOLUTION-TRI/2 (code 532DSC100T) € 185.00



QES Control boxes for single-phase drainage pumps

MODEL	CODE	MOTOR POWER (P ₂)		CAPACITOR	RATED CURRENT	PRICE
Single-phase		kW	HP	CAPACITY	A	€
QES 300 MONO	52VX300A1	2.2	3	60 μ F	16	240.00
QES 300 MONO-AL *	52VX300A1AL	2.2	3	60 μ F	16	240.00

- The control box is designed for connection to the thermal overload protector built into the motor windings of the VXCm 30, VXCm 30-F, MCm 30, MCm 30-F drainage pumps.
- **Single-phase 230 V 50 Hz**

(*) QES 300 MONO-AL, control box with contacts for connection to a level alarm auxiliary float switch



QES Control boxes for three-phase drainage pumps

MODEL	CODE	MOTOR POWER (P ₂)		RATED CURRENT	PRICE
Three-phase		kW	HP	A	€
QES 150	532QES150A	1.1	1.5	4.2	157.00
QES 200	532QES200A	1.5	2	5.2	157.00
QES 300	532QES300A	2.2	3	6.5	157.00
QES 400	532QES400A	3	4	8	162.00

- The control box is equipped with a selector for manual or automatic operation (with float switch) and is designed to be connected to the thermal overload protector built into the motor windings of the VXC, VXC-F, MC, MC-F drainage pumps.
- **Three-phase 380 – 415V 50 Hz**



QED1 Electronic control box for 1 drainage pump

MODEL	CODE	VOLTAGE	RATED CURRENT A	PRICE €
QED 1- MONO	533QED01M	single-phase 230V 50 Hz	from 2 to 18	199.00
QED 1- TRI/1	533QED01T	three-phase 400V 50 Hz	from 2 to 9	263.00
QED 1- TRI/2	533QED012T	three-phase 400V 50 Hz	from 2 to 16	277.00
QED 1- TRI/3	533QED013T	three-phase 400V 50 Hz	from 16 to 25	325.00

- The control box contains an electronic card that makes it possible to regulate the threshold at which the protection intervenes against overload currents and short-circuits.
- The control box is designed to be connected to the thermal overload protector built into the motor windings of the VXC, VXC-F, MC, MC-F, VX 50, VX 65, BC 35, VXC4, MC4 drainage pumps and to three float switches (start-up, shut-off and alarm level).

Spare electronic card for QED 1- MONO (code 533QEDSC00M) € 155.00

Spare electronic card for QED 1- TRI/1, QED 1- TRI/2 (code 533QEDSC00T) € 165.00

Spare electronic card for QED 1- TRI/3 (code 533QEDSC003T) € 165.00



QED2 Electronic control box for 2 drainage pumps

MODEL	CODE	VOLTAGE	RATED CURRENT A	PRICE €
QED 2- MONO	533QED02M	single-phase 230V 50 Hz	from 2 to 18	270.00
QED 2- TRI/1	533QED02T	three-phase 400V 50 Hz	from 2 to 9	381.00
QED 2- TRI/2	533QED022T	three-phase 400V 50 Hz	from 2 to 16	394.00
QED 2- TRI/3	533QED023T	three-phase 400V 50 Hz	from 16 to 25	555.00

- The control box contains an electronic card that makes it possible to regulate the threshold at which the protection intervenes against overload currents and short-circuits.
- The control box is designed to be connected to the thermal overload protector built into the motor windings of the VXC, VXC-F, MC, MC-F, VX 50, VX 65, BC 35, VXC4, MC4 drainage pumps and to four float switches (alternate start-up of the first pump, alternate start-up of the second pump, shut-off and alarm level).

Spare electronic card for QED 2- MONO (code 533QEDSC01M) € 180.00

Spare electronic card for QED 2- TRI/1, QED 2- TRI/2 (code 533QEDSC01T) € 195.00

Spare electronic card for QED 2- TRI/3 (code 533QEDSC013T) € 195.00



ALARM KIT Electronic control box for SAR 250 and SAR 550

MODEL	CODE	VOLTAGE	PRICE €
KIT ALLARME	KSKIT-ALLARME	single-phase 230V 50 Hz	405.00

- The panel contains an electronic board, a back-up battery to supply the board, a red warning light and an alarm siren of 90 dB at 1 m. distance.
- The panel is designed for the connection of a float (included in the kit) which sets off the alarm when the contact is closed.



QE2 Electronic control box for pressure boosting sets CB2

MODEL	CODE	VOLTAGE	RATED CURRENT A	PRICE €
QE2- MONO	54CB2SM2M030	single-phase 230V 50 Hz	from 2 to 18	230.00
QE2- TRI/1	54CB2SM2T075	three-phase 400V 50 Hz	from 2 to 12	335.00
QE2- TRI/2	54CB2SM2T100	three-phase 400V 50 Hz	from 2 to 16	375.00

- The control box contains an electronic card that makes it possible to regulate the threshold at which the protection intervenes against overload currents and short-circuits.
- The control box is set to accept 2 pressure switch links (running first pump and second pump alternately) as well as one float switch (for minimum water level) to prevent dry running.

Spare electronic card for QE2- MONO (code 54CB2SC020) € 150.00

Spare electronic card for QE2- TRI/1, QE 2-TRI/2 (code 54CB2SC025) € 155.00

SINGLE-PHASE 230 V - 50 Hz

MOTOR POWER (P ₂)		cable section in mm ²						
kW	HP	4 x 1	4 x 1.5	4 x 2.5	4 x 4	4 x 6	4 x 10	4 x 16
maximum cable length in metres								
0.37	0.50	60	90	140				
0.55	0.75	45	70	110	180			
0.75	1	35	50	85	140	210		
1.1	1.5	25	35	60	95	145	240	
1.5	2		30	45	75	115	190	305
2.2	3			30	50	75	125	200

THREE-PHASE 230 V - 50 Hz

MOTOR POWER (P ₂)		cable section in mm ²										
kW	HP	4x1	4 x 1.5	4 x 2.5	4 x 4	4 x 6	4 x 10	4 x 16	4 x 25	4 x 35	4 x 50	4 x 70
maximum cable length in metres												
0.37	0.50	100	152	255								
0.55	0.75	83	126	210	338							
0.75	1	65	99	165	265	405						
1.1	1.5	48	72	120	192	292	485					
1.5	2		53	88	142	215	360					
2.2	3			60	97	147	245	392				
3	4			47	73	110	183	295	510			
4	5.5				55	83	138	220	380			
5.5	7.5					60	100	160	275	385		
7.5	10					45	73	114	195	275	395	
9.2	12.5						64	100	157	220	315	
11	15						54	87	135	190	270	378
13	17.5							75	117	164	236	330
15	20							65	102	144	205	287
18.5	25								82	114	162	225
22	30								69	95	137	190
30	40									70	102	142
37	50									52	68	95


THREE-PHASE 400 V - 50 Hz

MOTOR POWER (P ₂)		cable section in mm ²										
kW	HP	4x1	4 x 1.5	4 x 2.5	4 x 4	4 x 6	4 x 10	4 x 16	4 x 25	4 x 35	4 x 50	4 x 70
maximum cable length in metres												
0.37	0.50	300										
0.55	0.75	250	380									
0.75	1	195	295									
1.1	1.5	145	215	360								
1.5	2	105	160	265	425							
2.2	3	70	110	180	290	440						
3	4	55	85	140	220	330						
4	5.5	40	60	105	165	250	415					
5.5	7.5		45	75	120	180	300	480				
7.5	10		35	55	95	135	220	340	585			
9.2	12.5			47	75	115	190	300	470			
11	15			40	65	95	160	260	405			
13	17.5				60	85	140	225	350	490		
15	20				50	75	125	195	305	430		
18.5	25					58	100	155	245	340	485	
22	30					49	85	130	205	285	410	570
30	40					36	63	96	152	210	305	425
37	50						47	74	115	156	205	284

Voltage drop 3% - Maximum environment temperature + 30 °C

LOAD LOSS CHART

(for straight pipes with 15-250 mm internal diameter and flow rates from 8 to 8330 l/min)



The data in the table refers to cold water and other liquids with the same kinematic viscosity and new cast iron pipes. The load losses (**hv**) indicated in the table must be multiplied by: **0.8** for new steel pipes, **1.25** for old, slightly rusty iron pipes, and **1.7** for old pipes where the build-up of incrustation must be taken into account.

➔ **EXAMPLE:** Flow rate data **Q = 500 l/min**, new steel pipe Ø 80 mm, pipe length 50 m.

Find the flow rate on the horizontal axis and move vertically until you meet the DN 80 mm line.

The corresponding load losses can thus be found on the vertical axis.

hv = 4.6 m for every 100 m of pipe.

hv1 = 4.6 x 0.8 = 3.68 m/100 (steel pipe).

Considering the real length of the pipe:

hv2 = 3.68 x 50:100 = 1.84 m (for 50 m of pipe).

The flow speed is determined by considering the position of the intersection point which is between the oblique lines with values of 1.5-2 m/sec. In the case being considered the result is approximately: **C = 1.7 metres/sec**



the spring of life

PEDROLLO S.p.A. 37047 San Bonifacio (Verona) ITALY - Via E. Fermi 7

Tel. +39 045 6136311 - Fax +39 045 7614663

sales@pedrollo.com - www.pedrollo.com

Cap. Soc. € 100,000,000.00 int. vers. - Iscritta Registro Imprese VR n. 00451260236

C.C.I.A.A. 139573 VR - Cod. Fiscale/Part. IVA IT00451260236 - Mec. Imp. VR008908

Società con unico socio

Società sottoposta alla direzione e coordinamento di PEDROLLO GROUP S.r.l.

ORDER N.	Date
----------	------

Client

Address

ZIP Code City

Tel. Fax

E-mail

VAT registration number

Price list 52/2019 Delivery terms

[illegible]

Extra notes

GENERAL SALES CONDITIONS

1) ORDERS AND ORDER ACCEPTANCE

Orders must clearly specify the exact name and type of product. Orders are understood to be binding only if they are confirmed in writing by PEDROLLO S.p.A.

2) PRICES

Prices do not include V.A.T. Packing and shipping costs are invoiced at cost and are not bound by the offer or by the delivery contract but are subject to any cost increases which may take place before shipment.

3) DELIVERY TERMS

Although we shall do all in our power to meet them, the delivery terms indicated in our order confirmation are understood to be indicative and not binding.

PEDROLLO S.p.A. shall not be responsible for any damage caused by delays in delivery.

PEDROLLO S.p.A. reserves the right to extend delivery terms or to cancel the contract without any obligation to pay any indemnity in the following cases:

- a) Force majeure causes such as strikes, fires on our premises or in those of our suppliers, insufficient power or power failure or any other cause beyond our control.
- b) Difficulties in acquiring raw materials.
- c) Purchaser's mistakes, errors or delays in providing us with the information necessary to fulfil the order;
- d) Purchaser's failure to comply with payment terms.
- e) Modifications of the order, even if we have accepted them after our order confirmation.

4) DELIVERY

Goods are understood to be delivered when they are placed at the Customer's disposal or handed over to the Carrier or Shipper.

5) SHIPMENT

Shipment is always understood to be undertaken on behalf of the purchaser and at his use, risk and peril, even when delivery is agreed "free to destination".

Claims for missing or damaged goods must always be filed by the consignee with the Shipper.

We consider claims regarding changes in types or differences in quantity are only taken into consideration if they are made in writing within 8 days from date of receipt of the goods. In the case of differences in quantity reference must be made to the gross weight of the package recorded on its arrival.

Choice of the means of shipment, Carrier and Shipper, unless we receive specific instructions from the Customer, shall be an unquestionable prerogative of our Company.

6) PAYMENT

Payment of invoices must be made directly to our address, according to the procedures and terms indicated on the invoice itself.

Any payments made to agents or representatives shall not be deemed to have been made until said sums reach the seller. When payment terms elapse without being honoured an **interest rate will be charged in accordance with the law**, without any advance notice.

We reserve the right, in case of delay in payment or failure to pay, to suspend manufacture and delivery of goods still on order, giving notice of this to the Customer. Said suspension shall not entitle to any kind of Compensation or claims, nor will it prejudice any of our other rights.

No claims regarding goods under production or ready for shipment or already shipped or in the Customer's possession shall relieve the latter from his obligation to take delivery of the entire quantity ordered and to make payments at the specified expiry dates.

WARRANTY

Pedrollo S.p.A. warrants for a 24 month period from the date of purchase, to be proven by dated proof of purchase, that the product will be free of material and construction defects, at the following conditions:

- 1) only products purchased from Pedrollo S.p.A. or resellers authorised by Pedrollo S.p.A. will be covered by this warranty;
- 2) the warranty does not include any failure resulting from errors in the connection to power supply, lack of adequate protection, defective installation, faulty handling and, however, inaccuracies in system operation.
Pursuant to regulations on the sale of consumer goods (art. 1519-bis and following of the Italian Civil Code), it is hereby specified that Pedrollo products should be installed by technically qualified personnel, as they are not designed to be installed by generic consumers.
- 3) this warranty does not include:
 - material failures resulting from corrosion or scraping of any kind caused by pumped liquids;
 - failure to work well due to bad installation;
 - failure to work well or product breakdown due to loads exceeding label limits;
- 4) in case of operation under warranty, Pedrollo S.p.A. only ensures repairing or replacing of the pump or device at their premises or one of our authorized service center and if recognized as defective, excluding any claim for damages and/or compensation.
- 5) allegedly defective product should be sent "carriage paid" to Pedrollo's registered office or to an authorized service center. Pedrollo reserves a final decision on the reason of the failure and on how to repair or replace the device. Following the repairing or replacement, the device will be returned by Pedrollo "carriage forward" to the Customer.
- 6) this warranty decays if:
 - 6a) the customer has failed to comply with payment terms;
 - 6b) the equipment or part were tampered by any non authorised third party;
 - 6c) the flaw and/or malfunction are not reported by the compulsory term of eight days.
- 7) Pedrollo S.p.A. do not sell directly to purchasers that may be qualified as consumers pursuant to regulations on "sale of consumer goods" (art. 1519-bis and following of the Italian Civil Code).
If the main purchaser from Pedrollo S.p.A. (direct customer of Pedrollo S.p.A.) resells a product to a final purchaser that may be qualified as consumer pursuant to the above-mentioned law, Pedrollo S.p.A. warrants a withdrawal right pursuant to art. 1519-quinquies and following of the Italian Civil Code, without prejudice of the warranty conditions as per previous points 1-6, and at the following conditions:
 - 7a) Pedrollo S.p.A. shall be informed by registered letter with advice of receipt by the compulsory term of 8 days since the first consumer's claim, under penalty of warranty decay;
 - 7b) Pedrollo S.p.A. shall be informed in the same manner and under the same penalty as per point 7a above, about any customer's extra-judicial or judicial initiative;
 - 7c) a withdrawal right will only be acknowledged if the customer's prompt reaction is either recognised by Pedrollo or ascertained by a Court along with the validity of this warranty pursuant to the conditions stated in all previous paragraphs.
 - 7d) warranty conditions as per previous arts. 1-6 will also apply
- 8) Pedrollo S.p.A. reserves the right to make any changes with no previous notice;
- 9) In the event of disputes related to the persistence and operation of this warranty, and however related or consequent to this warranty, the Court placed in the same area as Pedrollo S.p.A. registered office will have exclusive jurisdiction.

THIS PRICE LIST CANCELS AND REPLACES ALL PREVIOUS PRICE LISTS.

INTERNATIONAL SALES NETWORK

HEAD OFFICE (International)

Pedrollo S.p.A.

Via Enrico Fermi, 7 - 37047 San Bonifacio (Verona) Italy

tel. +39 045 6136311

fax +39 045 7614663

sales@pedrollo.com

www.pedrollo.com



FRANCE

PEDROLLO FRANCE

14 rue Albert Calmette

69740 Genas France

tel. +33 04 72 478 030

fax +33 04 72 478 039

info@pedrollo.fr

www.pedrollo.fr



HUNGARY

PEDROLLO HUNGÁRIA KFT

H-5000 Szolnok

Újszászi út 11.

Hungary

tel. +36 56 515 276

fax +36 56 515 275

info@pedrollo.hu

www.pedrollo.hu



ROMANIA

PEDROLLO ROMANIA

Str. Gheorghe Doja nr 97/A

Loc. Zalau, jud. Salaj, Romania


tel. +40 0260 610 330

+40 0260 617 010

fax +40 0260 661 589

info@pedrollo.ro

www.pedrollo.ro



COLOMBIA

PEDROLLO COLOMBIA LTDA

Autopista Medellín Vía al Parque La Florida Km 1.1

Parque Industrial Terrapuerto Bodegas 48-49

Bogotá Colombia

tel. +571 8764 666

fax +571 8764 652

info@pedrollo.com.co

www.pedrollo.com.co



MEXICO

PEDROLLO MEXICO S.A. de C.V.

CALLE NORTE 79-B, N° 121

Entre calle Salónica y Calle Aquiles Elorduy

02060 AZCAPOTZALCO, CIUDAD DE MEXICO, D.F.,

MEXICO

tel. +52 55 53 864 661

fax +52 55 53 864 660

www.pedrollo.com.mx

ventas@pedrollo.com.mx



DUBAI (UAE)

PEDROLLO GULF FZE

Dubai Airport Free Zone

Dubai, U.A.E.

P.O. Box: 293533

tel. +971 4 701 7803, 7804, 7805

fax +971 4 701 7806

sales@pedrollodxb.ae

www.pedrollo.ae

